Version: 5.0

Date of Issue: 07 July 2021 Date of First Issue: 20 March 2012



www.vishaypg.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

# **SECTION 1: IDENTIFICATION**

Product identifier used on the label M-Bond AE Resin

Other means of identification Not applicable

Recommended use of the chemical and restrictions

on use

Recommended use Adhesives.
Restrictions on use None known.

Details of the supplier of the safety data sheet

Supplier VISHAY MEASUREMENTS GROUP, INC.

Address of Supplier Post Office Box 27777
Raleigh, NC 27611

USA

 Telephone
 +1 919-365-3800

 Fax
 +1 919-365-3945

 E-Mail (competent person)
 mm.us@vishaypg.com

Emergency telephone number 1-800-424-9300 CHEMTREC (24 hours)

# SECTION 2: HAZARD(S) IDENTIFICATION

Classification of the substance or mixture in accordance with paragraph (d) of 29 CFR 1910.1200

Physical hazards

Not classified

Health hazards Skin Corrosion/Irritation, Category 2

Skin Sensitisation, Category 1 Eye Damage, Category 1

Germ cell mutagenicity, Category 2

Specific target organ toxicity — single exposure, Category 1 Specific target organ toxicity — single exposure, Category 2 Hazardous to the aquatic environment, Chronic, Category 2

Hazard Symbol

Environmental hazards









Signal Word(s) DANGER

Hazard Statement(s) Causes skin irritation.

May cause an allergic skin reaction.
Causes serious eye damage.
Suspected of causing genetic defects.

Causes damage to organs (CNS and blood effects - Oral). May cause damage to organs (Respiratory tract - Oral).

Toxic to aquatic life with long lasting effects.

Precautionary Statement(s)

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe vapour.

Wash hands and exposed skin thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

14039 Page: 1 of 9

Version: 5.0

Date of Issue: 07 July 2021 Date of First Issue: 20 March 2012 MICRO E MEASUREMENTS

www.vishaypg.com

### ACCORDING TO OSHA HCS (29 CFR 1910.1200)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water.

If skin irritation or rash occurs: Get medical advice/attention. IF exposed: Call a POISON CENTER or doctor/physician.

Avoid release to the environment.

Other hazards None known

Percent of the mixture consists of ingredient(s) of unknown acute toxicity:

0%

# **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

Substances - Not applicable

Mixtures - Substances in preparations / mixtures

Chemical identity of the substance	%W/W	CAS No.	EC No.	Hazard classification	
Bis-[4-(2,3-epoxipropoxi)phenyl] propane	< 75	1675-54-3	216-823-5	Skin Corrosion/Irritation, Category 2 Skin Sensitisation, Category 1 Eye Irritation, Category 2 Hazardous to the aquatic environment, Chronic, Category 2	
Bisphenol A Diglycidyl Ether	15 – 25	25085-99-8	-	Skin Corrosion/Irritation, Category 2 Skin Sensitisation, Category 1 Eye Irritation, Category 2 Hazardous to the aquatic environment, Chronic, Category 2	
2,3-Epoxypropyl o-tolyl ether	< 5	2210-79-9	218-645-3	Skin Corrosion/Irritation, Category 2 Skin Sensitisation, Category 1 Germ cell mutagenicity, Category 2 Hazardous to the aquatic environment, Chronic, Category 2	
Resorcinol	< 5	108-46-3	203-585-2	Acute toxicity, Category 4 – Oral Skin Corrosion/Irritation, Category 2 Eye Damage, Category 1 Skin Sensitisation, Category 1B Specific target organ toxicity — single exposure, Category 1 Specific target organ toxicity — single exposure, Category 2 Hazardous to the aquatic environment, Acute, Category 1 Hazardous to the aquatic environment, Chronic, Category 3	

### **SECTION 4: FIRST AID MEASURES**



#### Description of first aid measures

Self-protection of the first aider

Inhalation

Skin Contact

Use personal protective equipment as required. Wear appropriate personal protective equipment, avoid direct contact. Ensure adequate ventilation. Avoid all contact. Do not breathe vapour.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention.

IF ON SKIN: Remove contaminated clothing and wash all affected areas with plenty of water. If irritation (redness, rash, blistering) develops, get medical attention. IF exposed or concerned: Get medical advice/attention.

14039 Page: 2 of 9

Version: 5.0

Date of Issue: 07 July 2021 Date of First Issue: 20 March 2012



www.vishaypg.com

### ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Eye Contact

Ingestion

Most important symptoms and effects, both acute and delayed

Indication of any immediate medical attention and special treatment needed Notes to a physician:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER/doctor.

IF SWALLOWED: Rinse mouth. Make victim drink plenty of water. Do not induce vomiting unless instructed to do so by medical personnel. Call a POISON CENTER/doctor if you feel unwell. IF exposed or concerned: Get medical advice/attention.

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Suspected of causing genetic defects. Causes damage to organs (CNS and blood effects - Oral). May cause damage to organs (Respiratory tract - Oral). Treat symptomatically.

IF IN EYES: Obtain prompt consultation, preferably from an ophthalmologist. Following severe exposure the patient should be kept under medical review for at least 48 hours.

# **SECTION 5: FIRE-FIGHTING MEASURES**

Extinguishing media

Suitable Extinguishing Media

Unsuitable extinguishing Media

Special hazards arising from the substance or mixture

Special protective equipment and precautions for fire fighters

As appropriate for surrounding fire. Extinguish with carbon dioxide, dry chemical, foam or waterspray.

Do not use water jet. Direct water jet may spread the fire.

May decompose in a fire giving off toxic fumes. Decomposes in a fire giving off toxic fumes: Phenolics, Carbon monoxide and Carbon dioxide.

Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Do not breathe fumes. Keep containers cool by spraying with water if exposed to fire. Avoid run off to waterways and sewers.

#### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and

emergency procedures

Environmental precautions

Methods and material for containment and cleaning up

Ensure adequate ventilation. Stop leak if safe to do so. Use personal protective equipment as required. Wear appropriate personal protective equipment, avoid direct contact. Do not breathe vapour. Avoid all contact. Do not ingest. If swallowed then seek immediate medical assistance. Isolate the area and allow vapours to disperse.

Avoid release to the environment. Do not allow to enter drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be alerted to the Environment Agency or other appropriate regulatory body.

Adsorb spillages onto sand, earth or any suitable adsorbent material. Transfer to a container for disposal. Ventilate the area and wash spill site after material pick-up is complete. Dispose of this material and its container as hazardous waste

### **SECTION 7: HANDLING AND STORAGE**

Precautions for safe handling

Conditions for safe storage, including any incompatibilities
Storage temperature

Incompatible materials

Storage life

Avoid all contact. Do not breathe vapour. Ensure adequate ventilation. Wear appropriate personal protective equipment, avoid direct contact. Use personal protective equipment as required. See Section: 8. Do not eat, drink or smoke when using this product. Wash hands before breaks and after work.

Contaminated clothing should be laundered before reuse.

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Keep away from heat, sources of ignition and direct sunlight.

Ambient. Keep at temperature not exceeding (°C): 27

Stable under normal conditions.

Keep away from: Flammable liquids, Strong Oxidizing agents, Corrosive Substances, Strong Acids and strong mineral and organic bases, especially primary and secondary aliphatic amines.

14039 Page: 3 of 9

Version: 5.0

Date of First Issue: 20 March 2012



www.vishaypg.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

#### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Occupational Exposure Limits**

No OSHA permissible exposure limit (PEL).

SUBSTANCE	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m³)	STEL (ppm)	STEL (mg/m³)	Note
1,3-Benzenediol	108-46-3	10	45	20	90	NIOSH
(Resorcinol)	100-40-3	10	-	20	-	ACGIH, A4

Note: OSHA PELs 1910.1000 TABLE Z-1/ NIOSH RELs / ACGIH TLVs

A4: Not Classifiable as a Human Carcinogen: Agents which cause concern that they could be carcinogenic for humans but which cannot be assessed conclusively because of the lack of data. In vitro or animal studies do not provide indications of carcinogenicity which are sufficient to classify the agent into one of the other categories.

The other components listed in Section 3 do not have occupational exposure limits.

**Biological Exposure Indices** 

Not established

Appropriate engineering controls

Ensure adequate ventilation or use appropriate containment. Atmospheric levels should be controlled in compliance with the occupational exposure limit. A washing facility/water for eye and skin cleaning purposes should be present.

Individual protection measures, such as personal protective equipment (PPE)

General hygiene measures for the handling of chemicals are applicable. Avoid all contact. Do not breathe vapour. Wash hands before breaks and after work. Keep work clothes separately. Contaminated clothing should be laundered before reuse. Do not eat, drink or smoke at the work place.

Eye/face protection



Wear protective eye glasses for protection against liquid splashes. Wear eye protection with side protection (EN166).

#### Skin protection



#### Hand protection:

Wear impervious gloves (EN374). Gloves should be changed regularly to avoid permeation problems. Breakthrough time of the glove material: refer to the information provided by the gloves' producer.

#### **Body protection:**

Wear impervious protective clothing, including boots, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Respiratory protection



In case of inadequate ventilation wear respiratory protection. Open system(s): Wear suitable respiratory protective equipment.

# **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

### Information on basic physical and chemical properties

Appearance Odor Odor Threshold

Melting Point/Freezing Point

Clear - Amber Coloured liquid. Faint Epoxy Odour Not available. Not established.

Not available.

14039 Page: 4 of 9

Version: 5.0

Date of Issue: 07 July 2021 Date of First Issue: 20 March 2012



www.vishaypg.com

### ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Initial boiling point and boiling range

Not available.

Flash Point

Not available.

Evaporation rate (Butyl acetate = 1)

Not available.

Flammability (solid, gas)

Not applicable - Liquid

Upper/lower flammability or explosive limits

Vapour pressure

Vapour density

Relative density

Not available.

1 @ 118°C (mmHg)

>3.8 (Air = 1)

1.15 (H2O = 1)

Solubility(ies) The substance is essentially insoluble in water.

Partition coefficient: n-octanol/water Not available.

Auto-ignition temperature Not available.

Decomposition Temperature Not available.

Viscosity Not available.

# **SECTION 10: STABILITY AND REACTIVITY**

Reactivity Stable under normal conditions.

Chemical stability Stable under normal conditions. May decompose if heated.

Possibility of hazardous reactions

Hazardous polymerisation will not occur.

Conditions to avoid Keep away from heat, sources of ignition and direct sunlight. Keep at

temperature not exceeding (°C): 27

Incompatible materials Flammable liquids, Strong Oxidizing agents, Corrosive Substances, Strong

Acids and strong mineral and organic bases, especially primary and secondary

aliphatic amines.

Hazardous decomposition product(s) Decomposes in a fire giving off toxic fumes: Phenolics, Carbon monoxide and

Carbon dioxide.

# **SECTION 11: TOXICOLOGICAL INFORMATION**

#### Information on toxicological effects (Substances in preparations / mixtures)

Acute toxicity - Ingestion Based upon the available data, the classification criteria are not met.

Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 2000 mg/kg

bw/day.

Resorcinol: LD50 (oral,rat) mg/kg: 510 (OECD 401)

Acute toxicity - Inhalation Based upon the available data, the classification criteria are not met.

Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 20.0 mg/l.

Acute toxicity - Skin Contact

Based upon the available data, the classification criteria are not met.

Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 2000 mg/kg

bw/dav.

Skin corrosion/irritation Skin Corrosion/Irritation, Category 2; Causes skin irritation.

Bis-[4-(2,3-epoxipropoxi)phenyl] propane: Skin Corrosion/Irritation, Category 2; Causes skin irritation. (SCL ≥ 5%).

Slightly irritating to skin. (rabbit) (OECD 404)

Bisphenol A Diglycidyl Ether: Skin Corrosion/Irritation, Category 2; Causes skin irritation. No data. EU

classification and labelling inventory, ≥ 770 Notifiers

2,3-Epoxypropyl o-tolyl ether: Skin Corrosion/Irritation, Category 2; Causes skin irritation. Not irritating to skin

(rabbit) (OECD 404)

Resorcinol: Skin Corrosion/Irritation, Category 2; Causes skin irritation.

Test Result: Irritating to skin. (in vivo; FHSLA)

**Serious eye damage/irritation**Eye Damage, Category 1; Causes serious eye damage.

Bis-[4-(2,3-epoxipropoxi)phenyl] propane:
Eye Irritation, Category 2; Causes serious eye irritation.

(SCL ≥ 5%)

Not irritating to eyes (rabbit) (OECD 405)

Bisphenol A Diglycidyl Ether: Eye Irritation, Category 2; Causes serious eye irritation.

No data. EU classification and labelling inventory, ≥ 770 Notifiers

Resorcinol: Eye Damage, Category 1; Causes serious eye damage.

Test Result: Causes serious eye damage. (*in vivo*; FHSLA) (Flickinger, 1976) Skin Sensitisation, Category 1: May cause an allergic skin reaction.

**Respiratory or skin sensitization** Skin Sensitisation, Category 1: May cause an allergic skin reaction

14039 Page: 5 of 9

Version: 5.0

Date of Issue: 07 July 2021 Date of First Issue: 20 March 2012



www.vishaypg.com

### ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Skin Sensitisation, Category 1: May cause an allergic skin reaction. Positive -Bis-[4-(2,3-epoxipropoxi)phenyl] propane:

sensitising. (Mouse) (OECD 429)

Skin Sensitisation, Category 1: May cause an allergic skin reaction. No data. EU Bisphenol A Diglycidyl Ether:

classification and labelling inventory, ≥ 770 Notifiers

2,3-Epoxypropyl o-tolyl ether: Skin Sensitisation, Category 1: May cause an allergic skin reaction. Test Result:

Positive (OECD 406)

Resorcinol: Skin Sensitisation, Category 1: May cause an allergic skin reaction. Test Result:

Positive (OECD 429)

Germ cell mutagenicity Germ cell mutagenicity, Category 2: Suspected of causing genetic defects.

2,3-Epoxypropyl o-tolyl ether: Test Result: Positive (OECD 471)

Carcinogenicity Based upon the available data, the classification criteria are not met. Reproductive toxicity Based upon the available data, the classification criteria are not met.

STOT - single exposure Specific target organ toxicity — single exposure, Category 1; Causes damage to

organs. - oral

Specific target organ toxicity — single exposure, Category 2; May cause

damage to organs - oral.

Resorcinol: NOAEL 80 mg/kg bw/day (OECD 408)

STOT - repeated exposure Based upon the available data, the classification criteria are not met. **Aspiration hazard** Based upon the available data, the classification criteria are not met.

Information on likely routes of exposure

Inhalation Possible - accidental exposure Ingestion Unlikely - accidental exposure Skin Contact Possible - accidental exposure Eye Contact Unlikely - accidental exposure

Early onset symptoms related to exposure Causes skin irritation. May cause an allergic skin reaction. Causes serious eye

damage. Suspected of causing genetic defects. Causes damage to organs (CNS and blood effects - Oral). May cause damage to organs (Respiratory tract - Oral).

Delayed health effects from exposure Symptoms of poisoning may be delayed for several days.

Other information

Resorcinol:

NTP Report on Carcinogens All chemicals are not listed

IARC Monographs Bis-[4-(2,3-epoxipropoxi)phenyl]propane: Group 3

**OSHA** Designated Carcinogen All chemicals are not listed

# SECTION 12: ECOLOGICAL INFORMATION

**Ecotoxicity** Aquatic Chronic 3: Harmful to aquatic life with long lasting effects.

Estimated Mixture LC50 1 to ≤ 10 mg/l (Fish)

Aquatic Chronic 2; Toxic to aquatic life with long lasting effects. Bis-[4-(2,3-epoxipropoxi)phenyl] propane:

Acute: LC50 (fish) mg/l (96 hour) 1.5 (OECD 203)

Bisphenol A Diglycidyl Ether: Aquatic Chronic 2; Toxic to aquatic life with long lasting effects.

No data. EU classification and labelling inventory, ≥ 770 Notifiers

2,3-Epoxypropyl o-tolyl ether: Aquatic Chronic 2; Toxic to aquatic life with long lasting effects.

Harmonised Classification.

LC50 (fish) mg/l 2.8 - 5.1 (OECD 203)

Resorcinol: Aquatic Acute 1; Very toxic to aquatic life Harmonised Classification Aquatic Chronic 3; Harmful to aquatic life with long lasting effects.. EC50

(Daphnia magna) mg/l 1 (OECD 202)

Part of the components are poorly biodegradable. Persistence and degradability

Bis-[4-(2,3-epoxipropoxi)phenyl] propane: Not readily biodegradable

Water % Degradation: 5% (28 days) (OECD 301 F)

Bisphenol A Diglycidyl Ether: No data

2,3-Epoxypropyl o-tolyl ether: Not readily biodegradable

Water % Degradation: ~1 - ~4% (28 days) (OECD 301 B)

Readily biodegradable.

Water % Degradation: 100% (14 days) (OECD 301 C)

14039 Page: 6 of 9

Version: 5.0

Date of Issue: 07 July 2021 Date of First Issue: 20 March 2012

www.vishaypg.com

Epoxypropyl o-tolyl ether)

### ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Bisphenol A Diglycidyl Ether:

Bioaccumulative potential The product has low potential for bioaccumulation. Bis-[4-(2,3-epoxipropoxi)phenyl] propane: The substance has low potential for bioaccumulation.

Bioconcentration factor (BCF): 31 ((Q)SAR) (Unnamed publication, 2010)

No data

2,3-Epoxypropyl o-tolyl ether: No data - Can be waived on basis of: Log Koc : ≤ 3 Resorcinol: The substance has low potential for bioaccumulation.

Bioconcentration factor (BCF): 3.16 (EPA, 2000)

Mobility in soil The product is predicted to have low mobility in soil (Insoluble in water).

Bis-[4-(2,3-epoxipropoxi)phenyl] propane: The substance has moderate mobility in soil.

Log Koc: 2.65 ((Q)SAR) (Unnamed publication, 2010)

Epoxypropyl o-tolyl ether) Epoxypropyl o-tolyl ether)

Bisphenol A Diglycidyl Ether: No data

2,3-Epoxypropyl o-tolyl ether: The substance has moderate mobility in soil.

Log Koc: 2.32 (OECD 121)

Resorcinol: The substance has high mobility in soil. Log Koc: 0.98 (Schuurmann, G et al. 2006)

Other adverse effects None known.

### **SECTION 13: DISPOSAL CONSIDERATIONS**

Waste treatment methods This material and its container must be disposed of as hazardous waste. Send

after pre-treatment to a appropriate hazardous waste incinerator facility

according to legislation.

**Additional Information** Dispose of contents in accordance with local, state or national legislation.

### **SECTION 14: TRANSPORT INFORMATION**

IMDG IATA ADR/RID **UN** number UN 3082 UN 3082 UN 3082

**UN proper shipping name ENVIRONMENTALLY ENVIRONMENTALLY ENVIRONMENTALLY HAZARDOUS HAZARDOUS HAZARDOUS** SUBSTANCE, LIQUID, SUBSTANCE, LIQUID, SUBSTANCE, LIQUID, N.O.S. (Bis-[4-(2,3-N.O.S. (Bis-[4-(2,3-N.O.S. (Bis-[4-(2,3epoxipropoxi)phenyl] epoxipropoxi)phenyl] epoxipropoxi)phenyl] propane; Bisphenol A propane; Bisphenol A propane; Bisphenol A Diglycidyl Ether; 2,3-Diglycidyl Ether; 2,3-Diglycidyl Ether; 2,3-

Transport hazard class(es) 9 9 9 Packing group Ш Ш

**Environmental hazards** Classified as a Marine Environmentally Environmentally hazardous substance. Pollutant hazardous substance

See Section: 2

Transport in bulk according to Annex II of MARPOL

73/78 and the IBC Code

Special precautions for user Not applicable

### **SECTION 15: REGULATORY INFORMATION**

### Safety, health and environmental regulations/legislation specific for the substance or mixture **US Federal Regulations**

TSCA (Toxic Substance Control Act) Bis-[4-(2,3-epoxipropoxi)phenyl]propane: Subject to 25,000 lb reporting

All chemicals are not listed

All chemicals are not listed

threshold

Bisphenol A Diglycidyl Ether (MW <700): Exempt from reporting under CDR 2,3-Epoxypropyl o-tolyl ether: Subject to 25,000 lb reporting threshold

EPCRA/SARA Section 302 Extremely Hazardous

EPCRA Section 313 Toxics Release Inventory (TRI)

Substances

Program

All chemicals are not listed NIOSH Occupational Carcinogen List

14039 Page: 7 of 9

Version: 5.0

Date of Issue: 07 July 2021 Date of First Issue: 20 March 2012



www.vishaypg.com

### ACCORDING TO OSHA HCS (29 CFR 1910.1200)

OSHA List of highly hazardous chemicals, toxics and

reactives

NTP Report on Carcinogens (RoC) List

Poison Prevention Packaging Act

All chemicals are not listed
All chemicals are not listed

**US State Regulations** 

California State, Proposition 65 List

California State, Safer Consumer Products Regulations

Maine State, Toxic Chemicals in Children's Products Act

New Jersey State Worker and Community RTK Act

Pennsylvania State, Worker and Community RTK Act

Rhode Island State, Hazardous Substances RTK Act

All chemicals are not listed

Non-Regional

IARC Monographs, List of Classifications

Bis-[4-(2,3-epoxipropoxi)phenyl]propane: Group 3

# **SECTION 16: OTHER INFORMATION**

The following sections contain revisions or new statements: Updated substance / mixture classification. Updated version and date. Please review SDS with care. See below -

All chemicals are not listed

Sections indicated with the following have been revised:

Version 5.0

Revision Date 06 July 2021 Date of First Issue 20 March 2012

#### References:

Existing Safety Data Sheet (SDS), EU Data: Harmonised Classification(s) for Bis-[4-(2,3-epoxipropoxi)phenyl]propane (CAS No. 1675-54-3), 2,3-Epoxypropyl o-tolyl ether (CAS No. 2210-79-9) and Resorcinol (CAS No. 108-46-3). Existing ECHA registration(s) for 2,3-Epoxypropyl o-tolyl ether (CAS No. 2210-79-9) and Resorcinol (CAS No. 108-46-3), and the Classification and Labelling Inventory for Bisphenol A Diglycidyl Ether (CAS No. 25085-99-8).

GHS Classification of the substance or mixture	Classification Procedure		
Skin Corrosion/Irritation, Category 2	Threshold Calculation		
Skin Sensitisation, Category 1	Threshold Calculation		
Eye Damage, Category 1	Threshold Calculation		
Germ cell mutagenicity, Category 2	Threshold Calculation		
Specific target organ toxicity — single exposure, Category 1	Threshold Calculation		
Specific target organ toxicity — single exposure, Category 2	Threshold Calculation		
Hazardous to the aquatic environment, Chronic, Category 2	Summation Calculation		

#### **LEGEND**

ADR European Agreement concerning the International Carriage of Dangerous Goods by Road

CAS Chemical Abstracts Service

CERCLA Comprehensive Environmental Response Compensation and Liability Act

CWA Clean Water Act
EC European Community
ECHA European Chemicals Agency

EU European Union

IATA International Air Transport Association
IARC International Agency for Research on Cancer
ICAO International Civil Aviation Organization
IMDG International Maritime Dangerous Goods

LC50 Lethal concentration at which 50% of the population is killed

LD50 Lethal dose at which 50% of the population is killed

LTEL Long term exposure limit

NOEC No Observed Effect Concentration

14039 Page: 8 of 9

Version: 5.0

Date of Issue: 07 July 2021 Date of First Issue: 20 March 2012



www.vishaypg.com

### ACCORDING TO OSHA HCS (29 CFR 1910.1200)

NTP National Toxicology Program

OECD Organisation for Economic Cooperation and Development

OSHA The Occupational Safety & Health Administration

RID Regulations concerning the International Carriage of Dangerous Goods by Rail

STEL Short term exposure limit
TSCA Toxic Substance Control Act
TWA Time Weighted Average

UN United Nations

Training advice: Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required.

#### **Disclaimers**

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Vishay Precision Group gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Vishay Precision Group accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

14039 Page: 9 of 9



# **Legal Disclaimer Notice**

Vishay Precision Group, Inc.

# **Disclaimer**

ALL PRODUCTS. PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "VPG"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify VPG's terms and conditions of purchase, including but not limited to, the warranty expressed therein.

VPG makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. To the maximum extent permitted by applicable law, VPG disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on VPG's knowledge of typical requirements that are often placed on VPG products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. You should ensure you have the current version of the relevant information by contacting VPG prior to performing installation or use of the product, such as on our website at vpgsensors.com.

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of VPG.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling VPG products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify VPG for any damages arising or resulting from such use or sale. Please contact authorized VPG personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Copyright Vishay Precision Group, Inc., 2014. All rights reserved.

Document No.: 63999 Revision: 15-Jul-2014