### Revision: 1.1 Date: 26.08.2015

# ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830

# 

www.vishaypg.com

4		
.1	Product identifier	
	Product Name	PLM-9
	Chemical Name	Mixture
	CAS No.	Mixture
	EINECS No.	Mixture
	REACH Registration No.	None assigned.
.2	Relevant identified uses of the substance or mixture	None assigned.
.2	and uses advised against	
	-	
	Identified use(s)	Photostress® measurements.
•	Uses advised against	None known.
.3	Details of the supplier of the safety data sheet	
	Company Identification	VISHAY MEASUREMENTS GROUP, INC.
		Post Office Box 27777
		Raleigh, NC 27611
		USA
	Telephone	919-365-3800
	Fax	919-365-3945
	E-Mail (competent person)	mm.us@vishaypg.com
.4	Emergency telephone number	1-800-424-9300
		CHEMTREC
		UNEWITIED .
	SECTION 2: HAZARDS IDENTIFICATION	
.1	Classification of the substance or mixture	
1.1	GHS Classification	Skin Irrit. 2; H315
		Skin Sens. 1; H317
		Eye Irrit. 2; H319
		Muta. 2; H341
		Carc. 2; H351
		Aquatic Chronic 2; H411
2.2	Label elements	GHS Classification
	Product Name	PLM-9
	Product Name Hazard pictogram(s)	
		Varning
	Hazard pictogram(s)	
	Hazard pictogram(s) Signal word(s) Contains:	Warning   Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700), N-Butyl Glycidyl Ether, p-tert-butylphenyl 1-(2,3-epoxy)propyl ether.
	Hazard pictogram(s) Signal word(s)	Warning   Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700), N-Butyl Glycidyl Ether, p-tert-butylphenyl 1-(2,3-epoxy)propyl ether.   H315: Causes skin irritation.
	Hazard pictogram(s) Signal word(s) Contains:	Warning   Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700), N-Butyl Glycidyl Ether, p-tert-butylphenyl 1-(2,3-epoxy)propyl ether.   H315: Causes skin irritation.   H315: Causes an allergic skin reaction.
	Hazard pictogram(s) Signal word(s) Contains:	Warning   Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700), N-Butyl Glycidyl Ether, p-tert-butylphenyl 1-(2,3-epoxy)propyl ether.   H315: Causes skin irritation.   H315: Causes skin irritation.   H317: May cause an allergic skin reaction.   H319: Causes serious eye irritation.
	Hazard pictogram(s) Signal word(s) Contains:	Warning   Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700), N-Butyl Glycidyl Ether, p-tert-butylphenyl 1-(2,3-epoxy)propyl ether.   H315: Causes skin irritation.   H315: Causes skin irritation.   H317: May cause an allergic skin reaction.   H319: Causes serious eye irritation.   H311: Suspected of causing genetic defects.
	Hazard pictogram(s) Signal word(s) Contains:	Warning   Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700), N-Butyl Glycidyl Ether, p-tert-butylphenyl 1-(2,3-epoxy)propyl ether.   H315: Causes skin irritation.   H315: Causes skin irritation.   H315: Causes skin irritation.   H317: May cause an allergic skin reaction.   H319: Causes serious eye irritation.   H311: Suspected of causing genetic defects.   H351: Suspected of causing cancer.
	Hazard pictogram(s) Signal word(s) Contains:	Warning   Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700), N-Butyl Glycidyl Ether, p-tert-butylphenyl 1-(2,3-epoxy)propyl ether.   H315: Causes skin irritation.   H315: Causes skin irritation.   H317: May cause an allergic skin reaction.   H319: Causes serious eye irritation.   H311: Suspected of causing genetic defects.
	Hazard pictogram(s) Signal word(s) Contains:	Warning   Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700), N-Butyl Glycidyl Ether, p-tert-butylphenyl 1-(2,3-epoxy)propyl ether.   H315: Causes skin irritation.   H315: Causes skin irritation.   H315: Causes skin irritation.   H317: May cause an allergic skin reaction.   H319: Causes serious eye irritation.   H311: Suspected of causing genetic defects.   H351: Suspected of causing cancer.

### Revision: 1.1 Date: 26.08.2015

# ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830

P302+P352: VID HUDKONTAKT: Tvätta med mycket vatten. P333+P313: Vid hudirritation eller utslag: Sök läkarhjälp. P305+P351+P338: VID KONTAKT MED ÖGONEN: Skölj försiktigt med vatten i flera minuter. Ta ur eventuella kontaktlinser om det går lätt. Fortsätt att skölja. P308+P313: Vid exponering eller misstanke om exponering Sök läkarhjälp.

#### 2.3 Other hazards

None

## 3. SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1 Substances Not applicable

#### 3.2 Mixtures

**GHS** Classification

Chemical identity of the substance	%W/W	CAS No.	EC No.	Hazard statement(s)
Reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)	<100	25068-38-6	500-033-5	Skin Irrit. 2; H315 (SCL: ≥ 5%) Skin Sens. 1; H317 Eye Irrit. 2; H319 (SCL: ≥ 5%) Aquatic Chronic 2; H411
p-Tert-butylphenyl 1-(2,3- epoxy)propyl ether	< 10	3101-60-8	221-453-2	Skin Irrit. 2; H315 Skin Sens. 1; H317 Aquatic Chronic 2; H411
N-Butyl Glycidyl Ether 2 – 5		2426-08-6	219-376-4	Flam. Liq. 3; H226 Acute Tox. 4; H302 & H332 Skin Sens. 1; H317 STOT SE 3; H335 Muta. 2; H341 Carc. 2; H351 Aquatic Chronic 3; H412

H226: Flammable liquid and vapour. H302+H332: Harmful if swallowed or if inhaled. H315: Causes skin irritation. H317: May cause an allergic skin reaction. H319: Causes serious eye irritation. H335: May cause respiratory irritation. H341: Suspected of causing genetic defects. H351: Suspected of causing cancer. H411: Toxic to aquatic life with long lasting effects. H412: Harmful to aquatic life with long lasting effects. SCL: Specific Concentration Limit.

### 4. SECTION 4: FIRST AID MEASURES



Description of first aid measures				
Self-protection of the first aider	Do not breathe vapour. Wear suitable respiratory protective equipment if exposure to high levels of material are likely. Wear suitable protective clothing.			
	Do not use mouth-to-mouth resuscitation.			
Inhalation	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Apply artificial respiration if necessary (do not			
	employ mouth-to-mouth method). IF exposed or concerned: Get medical advice/attention.			
Skin Contact	IF ON SKIN: Remove contaminated clothing and wash affected skin with water. Contaminated clothing should be thoroughly cleaned. If skin irritation or rash occurs: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention.			
Eye Contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get			
	Self-protection of the first aider Inhalation Skin Contact			



## Revision: 1.1 Date: 26.08.2015

# ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830

Most important symptoms and effects, both acute

Indication of any immediate medical attention and

MENTS

#### Ingestion

and delayed

special treatment needed

4.2

4.3

medical advice/attention.

IF SWALLOWED: Get medical advice/attention if you feel unwell. Do not induce vomiting. Do not give anything by mouth to an unconscious person. May cause an allergic skin reaction. Causes skin irritation. Causes serious eye irritation. Suspected of causing genetic defects. Suspected of causing cancer. Treat symptomatically.

5.	SECTION 5: FIRE-FIGHTING MEASURES	
5.1	Extinguishing media	
	Suitable Extinguishing Media	Extinguish with carbon dioxide, dry chemical, foam or waterspray. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.
	Unsuitable Extinguishing Media	Do not use water jet. May spread fire.
5.2	Special hazards arising from the substance or	May decompose in a fire giving off toxic fumes. Phenolics, Carbon monoxide,
	mixture	Carbon dioxide, Acids and Aldehydes. Container may rupture from gas generation in a fire situation. Dense smoke is emitted when burned without sufficient oxygen.
5.3	Advice for fire-fighters	Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Do not breathe fumes. Keep containers cool by spraying with water if exposed to fire. Avoid run off to waterways and sewers.

### 6. SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1	Personal precautions, protective equipment and emergency procedures	Stop leak if safe to do so. Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Do not breathe vapour. Avoid contact with skin, eyes or clothing. Wear suitable respiratory protection. Use personal protective equipment as required. See Section: 8.
6.2	Environmental precautions	Do not allow to enter drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be alerted to the Environment Agency or other appropriate regulatory body.
6.3	Methods and material for containment and cleaning up	Ensure suitable personal protection during removal of spillages. Adsorb spillages onto sand, earth or any suitable adsorbent material. Transfer to a container for disposal. Dispose of this material and its container as hazardous waste. To clean the floor and all objects contaminated by this material use soap and water.
6.4	Reference to other sections	See Section: 8, 13

### 7. SECTION 7: HANDLING AND STORAGE

7.1	Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe vapour. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. See Section: 8. Do not eat, drink or smoke when using this product. Wash hands before breaks and after work.
7.2	Conditions for safe storage, including any incompatibilities	Keep in a cool, dry, well ventilated place. Keep away from heat and direct sunlight.
	Storage Temperature	Ambient.
	Storage Life	Stable under normal conditions.
	Incompatible materials	Keep away from: Oxidizing agents, unintended contact with amines, Strong
		Acids, mercaptans and Alkalis.
7.3	Specific end use(s)	Photostress® measurements.

# ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830

### 8. SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters

#### 8.1.1 Occupational exposure limits

SUBSTANCE	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m³)	STEL (ppm)	STEL (mg/m <sup>3</sup> )	Note
N-Butyl Glycidyl Ether	2426-08-6	-	-	5.6*	30*	NIOSH
N-Butyl Glycidyl Ether	2426-08-6	50	270	-	-	OSHA

Note: OSHA 1910.1000 TABLE Z-1 / \*NIOSH 15 minute value

8.1.2	Biological limit value	Not established.
8.1.3	PNECs and DNELs	Not established.
8.2	Exposure controls	
8.2.1	Appropriate engineering controls	Ensure adequate ventilation or use appropriate containment. Use with local exhaust ventilation. Atmospheric levels should be controlled in compliance with the occupational exposure limit. Guarantee that the eye flushing systems and safety showers are located close to the working place.
8.2.2	Individual protection measures, such as personal protective equipment (PPE)	General hygiene measures for the handling of chemicals are applicable. Use personal protective equipment as required. Keep work clothes separately. Contaminated clothing should be thoroughly cleaned. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke during work.
	Eye/face protection	Wear protective eye glasses for protection against liquid splashes. Wear eye protection with side protection (EN166).
	Skin protection	Hand protection: Wear impervious gloves (EN374). Breakthrough time of the glove material: refer to the information provided by the gloves' producer. The gloves type used must be chosen based on the work activity and duration as well as concentration/quantity of material being handled. Recommended: Butyl rubber, Nitrile rubber, Neoprene, PVC.
		Body protection: Wear impervious protective clothing, including boots, lab coat, apron or coveralls, as appropriate, to prevent skin contact.
	Respiratory protection	In case of inadequate ventilation wear respiratory protection. Open system(s): Wear suitable respiratory protective equipment.
	Thermal hazards	Not applicable.
8.2.3	Environmental Exposure Controls	Avoid release to the environment.
9	SECTION 9' PHYSICAL AND CHEMICAL PR	OPERTIES

### 9. SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties

Appearance Odour Odour Threshold pH Melting Point/Freezing Point Clear - Light Coloured liquid Faint Odour Not available. Not established. -16 ℃ (CAS No. 25068-38-6)



#### Revision: 1.1 Date: 26.08.2015

# ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830

Initial boiling point and boiling range Flash point Evaporation rate Flammability (solid, gas) Upper/lower flammability or explosive limits Vapour pressure Vapour density Relative density Solubility(ies) Partition coefficient: n-octanol/water Auto-ignition temperature Decomposition Temperature Viscosity Explosive properties Oxidising properties  $\label{eq:constraint} \begin{array}{l} \sim 320\,^\circ \mbox{C} \ (\mbox{CAS No. } 25068-38-6) \\ \geq 264 \leq 268\,^\circ \mbox{C} \ (\mbox{CAS No. } 25068-38-6) \\ \mbox{Not available.} \\ \mbox{Not applicable.} \\ 1 \ \mbox{mm Hg} \\ >1 \ (\mbox{Air = 1}) \\ 1.14 \ (\mbox{H2O = 1}) \\ \mbox{Partly soluble in water.} \\ \geq 2.64 \leq 3.78 \ \mbox{log Pow} \ (25\,^\circ \mbox{C}) \ (\mbox{CAS No. } 25068-38-6) \\ \mbox{Not applicable.} \\ >350\,^\circ \mbox{C} \ (\mbox{CAS No. } 25068-38-6) \\ \mbox{Not available.} \\ \mbox{Not available.} \\ \mbox{Not explosive.} \\ \mbox{Not oxidising.} \end{array}$ 

Decomposes in a fire giving off toxic fumes: Phenolics, Carbon monoxide,

Carbon dioxide, Acids and Aldehydes.

#### 9.2 Other information

None.

#### 10. SECTION 10: STABILITY AND REACTIVITY 10.1 Reactivity Stable under normal conditions. 10.2 Chemical stability Stable under normal conditions. 10.3 Possibility of hazardous reactions Reaction with some curing agents may produce considerable heat. Reacts with amines. Polymerization may occur. Contact with aliphatic amines will cause irreversible polymerization with considerable heat build-up. 10.4 Conditions to avoid Avoid contact with heat and ignition sources and oxidizers. The product may decompose if heated to temperatures above (°C): 300 10.5 Incompatible materials Keep away from: Oxidizing agents, unintended contact with amines, Strong Acids mercaptans and alkalis. Polymerization may occur.

10.6 Hazardous Decomposition Product(s)

## 11. SECTION 11: TOXICOLOGICAL INFORMATION

11.1	Information on toxicological effects (Substances in Acute toxicity	preparations / mixtures)
	Ingestion	Based upon the available data, the classification criteria are not met. LC50 > 2000 mg/kg bw/day
	Inhalation	Based upon the available data, the classification criteria are not met. LC50 > 20 mg/kg bw/day
	Dermal	Based upon the available data, the classification criteria are not met. LC50 > 2000 mg/kg bw/day
	Skin corrosion/irritation	Skin Irrit. 2: Causes skin irritation.
	Serious eye damage/irritation	Eye Irrit. 2: Causes serious eye irritation.
	Respiratory or skin sensitization	Skin Sens. 1: May cause an allergic skin reaction.
	Germ cell mutagenicity	Muta. 2: May cause genetic defects.
	Carcinogenicity	Carc. 2: Suspected of causing cancer.
	Reproductive toxicity	Based upon the available data, the classification criteria are not met.
	STOT - single exposure	Based upon the available data, the classification criteria are not met.
	STOT - repeated exposure	Based upon the available data, the classification criteria are not met.
	Aspiration hazard	Based upon the available data, the classification criteria are not met.
11.2	Other information	
	NTP Report on Carcinogens	Not listed.
	IARC Monographs	Not listed.



#### www.vishaypg.com

Toxicity

Mobility in soil

12.

12.1

12.2

12.3

12.4

12.5

12.6

13.

13.1

13.2

14.

14.1

14.2

14.3 14.4

14.5

14.6

14.7

14.8

15. 15.1

15.1.1

15.1.2

Revision: 1.1 Date: 26.08.2015

# ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),

**SECTION 12: ECOLOGICAL INFORMATION** 

# Αı Sı W 15.2 CI 16. SE The follow References (number av Classification

Other adverse effects	Not classified as PBT or VPVB. None known.
SECTION 13: DISPOSAL CONSIDERATION	S
Waste treatment methods Additional Information	This material and its container must be disposed of as hazardous waste (2008/98/EEC). Dispose of contents in accordance with local, state or national legislation. Containers of this material may be hazardous when empty since they retain product residue. Do not allow to enter drains, sewers or watercourses. Dispose of contents in accordance with local, state or national legislation.
SECTION 14: TRANSPORT INFORMATION	
UN number UN Proper Shipping Name	ADR/RID / IMDG / IATA UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700) and p-Tert-butylphenyl 1-(2,3-epoxy)propyl ether)
Transport hazard class(es)	9
Packing Group Environmental hazards	III Marine Pollutant / Environmentally hazardous substance
Special precautions for user	See Section: 2
Transport in bulk according to Annex II of	Not applicable.
MARPOL73/78 and the IBC Code	
Additional information	None.
SECTION 15: REGULATORY INFORMATION	
Safety, health and environmental regulations/legislation specific for the substance or mixture National regulations	
OSHA Occupational Safety and Health Standards European regulations	None.
Authorisations and/or restrictions on use	None.
Substance(s) of Very High Concern (SVHCs)	None. Water hazard class: 2
Wassergefährdungsklasse (Germany) Chemical Safety Assessment	Not available.
SECTION 16: OTHER INFORMATION	
ollowing sections contain revisions or new statements:	1-16.
	gistration(s) for Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin P-Tert-butylphenyl 1-(2,3-epoxy)propyl ether (CAS# 3101-60-8), and Harmonised

Aquatic Chronic 2 Toxic to aquatic life with long lasting effects.

The product is predicted to have low mobility in soil. (Partly soluble in water).

Part of the components are poorly biodegradable.

The product has low potential for bioaccumulation.

Estimated LC50 (Fish) > 1 ≤10 mg/l

Not classified as PBT or vPvB.

Persistence and degradability

Results of PBT and vPvB assessment

**Bioaccumulative potential** 

1272/2008 (CLP) & 2015/830

www.vishaypg.com



# ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830

GHS Classification of the substance or mixture	Classification Procedure
Skin Irrit. 2; H315	Threshold Calculation
Skin Sens. 1; H317	Threshold Calculation
Eye Irrit. 2; H319	Threshold Calculation
Muta. 2; H341	Harmonised Classification
Carc. 2; H351	Harmonised Classification
Aquatic Chronic 2; H411	Summation Calculation

#### LEGEND

LTEL	Long Term Exposure Limit
STEL	Short Term Exposure Limit
DNEL	Derived No Effect Level
PNEC	Predicted No Effect Concentration
PBT	PBT: Persistent, Bioaccumulative and Toxic
vPvB	vPvT: very Persistent and very Toxic
NTP	National Toxicology Program
IARC	International Agency for Research on Cancer
OSHA	The Occupational Safety & Health Administration
NIOSH	National Institute for Occupational Safety and Health

Training advice: Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required.

#### Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Vishay Precision Group gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Vishay Precision Group accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

#### Annex to the extended Safety Data Sheet (eSDS)

No information available.



# Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "VPG"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify VPG's terms and conditions of purchase, including but not limited to, the warranty expressed therein.

VPG makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. To the maximum extent permitted by applicable law, VPG disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on VPG's knowledge of typical requirements that are often placed on VPG products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. You should ensure you have the current version of the relevant information by contacting VPG prior to performing installation or use of the product, such as on our website at vpgsensors.com.

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of VPG.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling VPG products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify VPG for any damages arising or resulting from such use or sale. Please contact authorized VPG personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Copyright Vishay Precision Group, Inc., 2014. All rights reserved.