Revision: 2.0 Date: 21.08.2015



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),

1272/2008 (CLP) & 2015/830

www.vishaypg.com

1. SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product Name M-Bond GA-100 Cement

Chemical Name Mixture
CAS No. Mixture
EINECS No. Mixture
REACH Registration No. None assigned.

1.2 Relevant identified uses of the substance or mixture

and uses advised against

Identified Use(s) Adhesives.

Uses Advised Against For professional users only.

1.3 Details of the supplier of the safety data sheet

Company Identification VISHAY MEASUREMENTS GROUP UK LTD

Stroudley Road Basingstoke Hampshire United Kingdom RG24 8FW

 Telephone
 +44 (0) 1256 462131

 Fax
 +44 (0) 1256 471441

 E-Mail (competent person)
 mm.uk@vishaypg.com

1.4 Emergency telephone number (00-1) 703-527-3887

CHEMTREC

2. SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

2.1.1

Regulation (EC) No. 1272/2008 (CLP)

Skin Irrit. 2; H315

Skin Sens. 1; H317

Eye Dam. 1; H318

Acute Tox. 4; H332

Resp. Sens. 1; H334

STOT SE 3; H335

Muta. 1B; H340 Carc. 1A; H350 STOT RE 1; H372 Aquatic Chronic 2; H411

2.2 Label elements According to Regulation (EC) No. 1272/2008 (CLP)

Product Name M-Bond GA-100 Cement

Hazard Pictogram(s)









Signal Word(s)

Danger

Contains: Quartz (SiO2), Aluminium tris(dihydrogen phosphate)and Chromium (VI)

trioxide.

Hazard Statement(s) H315: Causes skin irritation.

H317: May cause an allergic skin reaction. H318: Causes serious eye damage.

H332: Harmful if inhaled.

Revision: 2.0 Date: 21.08.2015



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),

1272/2008 (CLP) & 2015/830

www.vishaypq.com

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335: May cause respiratory irritation. H340: May cause genetic defects.

H350: May cause cancer.

H372: Causes damage to organs through prolonged or repeated exposure.

H411: Toxic to aquatic life with long lasting effects.

Precautionary Statement(s) P201: Obtain special instructions before use.

P280: Wear protective gloves/protective clothing/eye protection/face protection. P304+P341: IF INHALED: If breathing is difficult, remove victim to fresh air and

keep at rest in a position comfortable for breathing.

P342 + P311: If experiencing respiratory symptoms: Call a POISON

CENTER/doctor.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P310: Immediately call a POISON CENTER/doctor.

Additional Information None.

2.3 Other hazards None.

3. SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances Not applicable

3.2 Mixtures

EC Classification Regulation (EC) No. 1272/2008 (CLP)

Chemical identity of the	%W/W	CAS No.	EC No.	REACH Registration	Hazard Statement(s)		
substance				No.			
Quartz (SiO2)	30 - 40	14808-60-7	238-878-4	None assigned	STOT RE 1; H372		
Distilled Water	< 30	7732-18-5	231-791-2	None assigned	Not classified		
Silicon Dioxide	15 - 20	7631-86-9	231-791-2	None assigned	Not classified		
Aluminium tris(dihydrogen phosphate)	10 - 15	13530-50-2	236-875-2	None assigned	Eye Dam. 1; H318		
Chromium (VI) Trioxide	۷ 8	1333-82-0	215-607-8	None assigned	Ox. Sol. 1; H271 Acute Tox. 3; H301 Acute Tox. 3; H311 Skin Corr. 1A; H314 Skin Sens. 1; H317 Acute Tox. 2; H330 Resp. Sens. 1; H334 STOT SE 3; H335 (SCL: ≥ 1%) Muta. 1B; H340 Carc. 1A; H350 Repr. 2; H361f STOT RE 1; H372 Aquatic Acute 1; H400 Aquatic Chronic 1; H410		
Phosphoric Acid	< 1	7664-38-2	231-633-2 /616-646-7	None assigned Met. Corr. 1; H290 Skin Corr. 1B; H314 (SCL: > 25%)			
Gum tragacanth	< 1	9000-65-1	232-552-5	None assigned Not classified			

H271: May cause fire or explosion; strong oxidiser. H290: May be corrosive to metals. H301: Toxic if swallowed. H311: Toxic in contact with skin. H314: Causes severe skin burns and eye damage. H317: May cause an allergic skin reaction. H330: Fatal if inhaled. H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335: May cause respiratory irritation. H340: May cause genetic defects. H350: May cause cancer. H372: Causes damage to organs through prolonged or repeated exposure. H400: Very toxic to aquatic life. H410: Very toxic to aquatic life with long lasting effects. SCL: Specific Concentration Limit.

Revision: 2.0 Date: 21.08.2015



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),

1272/2008 (CLP) & 2015/830

www.vishaypg.com

4. **SECTION 4: FIRST AID MEASURES**



Description of first aid measures

Self-protection of the first aider

Inhalation

Skin Contact

Eve Contact

Ingestion

4.2 Most important symptoms and effects, both acute and delayed

Indication of any immediate medical attention and 4.3 special treatment needed

Wear suitable respiratory protective equipment if exposure to high levels of material are likely. Wear suitable protective clothing. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Avoid all contact. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician. IF exposed or concerned: Get medical advice/attention. If unconscious, place in recovery position and get medical attention immediately. Apply artificial respiration if necessary.

IF ON SKIN: Remove contaminated clothing and wash all affected areas with plenty of water. Contaminated clothing should be thoroughly cleaned. If skin irritation or rash occurs: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if eye irritation develops or persists. Obtain prompt consultation, preferably from an ophthalmologist.

IF SWALLOWED: Rinse mouth. Drink two glasses of water. Do not induce vomiting. Do not give anything by mouth to an unconscious person. Obtain medical attention.

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. May cause genetic defects. May cause cancer. Causes damage to organs through prolonged or repeated exposure.

IF IN EYES: Get immediate medical advice/attention. Chemical eye burns may require extended irrigation.

IF INHALED: Do not employ mouth-to-mouth method.

IF SWALLOWED: Get medical attention immediately. Allow the patient to drink 5 - 10 g ascorbic acid (not effervescent tablets) dissolved in water. This dose can be repeated several times.

5. **SECTION 5: FIREFIGHTING MEASURES**

5.1 **Extinguishing media**

5.2

5.3

Suitable Extinguishing media

Advice for fire-fighters

dioxide or dry chemical. Do not use water jet. Direct water jet may spread the fire.

Unsuitable extinguishing media Special hazards arising from the substance or mixture

May decompose in a fire giving off toxic fumes. May decompose in a fire giving

off toxic fumes. Carbon monoxide, Carbon dioxide, silicon and possibly

As appropriate for surrounding fire. Extinguish preferably with foam, carbon

chromium. Sealed containers may rupture explosively if hot.

Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Do not breathe fumes. Keep containers cool by spraying with water if exposed to fire. Avoid run off to waterways and sewers.

6. SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Do not breathe vapour. Avoid all contact. Wear suitable respiratory protection. Use personal protective equipment as required. See Section: 8. Stop leak if safe to do so. Eliminate all ignition sources if safe to do so. Keep away from heat, hot surfaces, sparks, open flames and other

Revision: 2.0 Date: 21.08.2015

Environmental precautions



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),

1272/2008 (CLP) & 2015/830

www.vishaypg.com

ignition sources. No smoking.

Avoid release to the environment. Do NOT wash away into sewer. Spillages or

uncontrolled discharges into watercourses must be alerted to the Environment

Agency or other appropriate regulatory body.

6.3 Methods and material for containment and cleaning

6.2

Ensure full personal protection (including respiratory protection) during removal of spillages. Adsorb spillages onto sand, earth or any suitable adsorbent material. Neutralize with: slaked lime (calcium hydroxide), sodium carbonate, calcium carbonate or sodium bicarbonate. Use only non-sparking tools. Transfer to a container for disposal. Dispose of this material and its container as

hazardous waste (2008/98/EEC).

6.4 Reference to other sections See Section: 8, 13

SECTION 7: HANDLING AND STORAGE 7.

7.1 Precautions for safe handling Obtain special instructions before use. Do not handle until all safety precautions

> have been read and understood. Ensure adequate ventilation. Avoid all contact. Do not breathe vapour. Use personal protective equipment as required. See Section: 8. Do not eat, drink or smoke when using this product. Wash hands

before breaks and after work.

7.2 Store in a well-ventilated place. Keep container tightly closed. Keep away from Conditions for safe storage, including any incompatibilities

heat, sources of ignition and direct sunlight. Do not allow product to dry out. Add

water as necessary.

Storage temperature Ambient. Store at temperatures not exceeding (°C): 27

Storage life Stable under normal conditions.

Incompatible materials Keep away from: Combustible materials, Reducing agent, Oxidizing agents,

Acids and Alkalis.

7.3 Specific end use(s) PC14 Metal surface treatment products, including galvanic and electroplating

products.

8. SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Occupational Exposure Limits 8.1.1

SUBSTANCE	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m³)	STEL (ppm)	STEL (mg/m³)	Note
Quartz (SiO2)	14808-60-7	-	0.1 (1)	-	-	WEL
Silicon Dioxide	7631-86-9		6 (2) 2.4 (3)			WEL
Phosphoric Acid	7664-38-2	-	1	-	2	WEL

Note: WEL: Workplace Exposure Limit (UK HSE EH40)

(1): Respirable crystalline

(2): Inhalable aerosol

(3): Respirable aerosol

8.1.2 Biological limit value Not established.

8.1.3 PNECs and DNELs Not established.

8.2 **Exposure controls**

Appropriate engineering controls 8.2.1 Ensure adequate ventilation or use appropriate containment. Atmospheric levels

> should be controlled in compliance with the occupational exposure limit. Guarantee that the eye flushing systems and safety showers are located close

to the working place. Wash thoroughly after handling.

8.2.2 Individual protection measures, such as personal protective equipment (PPE)

General hygiene measures for the handling of chemicals are applicable. Avoid all contact. Do not breathe vapour. Wash hands before breaks and after work.

Revision: 2.0 Date: 21.08.2015



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),

1272/2008 (CLP) & 2015/830

Eye/ face protection

www.vishaypg.com

Keep work clothes separately. Contaminated clothing should be thoroughly cleaned. Do not eat, drink or smoke at the work place.

Wear eve protection with side protection (EN166). Recommended: Full face

shield.

Hand protection: Wear impervious gloves (EN374). Gloves should be changed Skin protection regularly to avoid permeation problems. Breakthrough time of the glove material:

refer to the information provided by the gloves' producer. Recommended:

Neoprene.

Body protection: Wear impervious protective clothing, including boots, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Recommended:

Neoprene.

Respiratory protection Do not use in areas without adequate ventilation. In case of inadequate

ventilation wear respiratory protection. Have available emergency self-contained

breathing apparatus or full-face airline respirator when using this chemical.

Not applicable. Thermal hazards

8.2.3 **Environmental Exposure Controls** Avoid release to the environment.

9. **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

9.1 Information on basic physical and chemical properties

Appearance Material separates into dark amber liquid and yellow paste.

Odour Acidic Odour Odour threshold Not available. рΗ Not established. Melting point/freezing point Not available.

100℃ Initial boiling point and boiling range Flash point Not applicable. Evaporation rate Slight

Flammability (solid, gas) Not applicable - Liquid.

Upper/lower flammability or explosive limits Not available. Vapour pressure <1 (mmHg) Vapour density >1 (Air = 1) Relative density Not available. Solubility(ies) Slight (Water) Partition coefficient: n-octanol/water Not available. Auto-ignition temperature Not available. **Decomposition Temperature** Not available. Viscosity Not available. Not explosive

Explosive properties Oxidising properties Not oxidising.

9.2 Other information Volatile Organic Compound Content: < 10 g/l

SECTION 10: STABILITY AND REACTIVITY 10.

10.1 Stability and reactivity

10.2 Chemical stability

10.3 Possibility of hazardous reactions

10.4 Conditions to avoid Stable under normal conditions.

Hazardous polymerisation will not occur.

Keep away from heat, sources of ignition and direct sunlight. Do not allow

product to dry out. Add water as necessary.

Revision: 2.0 Date: 21.08.2015



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),

1272/2008 (CLP) & 2015/830

www.vishaypg.com

10.5 Incompatible materials Keep away from: Combustible materials, Reducing agent, Oxidizing agents,

Acids and Alkalis.

10.6 Hazardous decomposition product(s) May decompose in a fire giving off toxic fumes. Carbon monoxide, Carbon

dioxide, silicon and possibly chromium.

11. SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects (Substances in preparations / mixtures)

Acute toxicity

Ingestion Based upon the available data, the classification criteria are not met.

Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 2000 mg/kg

bw/day.

Inhalation Acute Tox. 4: Harmful if inhaled.

Acute Toxicity Estimate Mixture Calculation: Estimated LC50 17.2 mg/l.

Skin Contact Based upon the available data, the classification criteria are not met.

Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 2000 mg/kg

bw/day.

Skin corrosion/irritation Skin Irrit. 2; Causes skin irritation.

Serious eye damage/irritationEye Dam. 1: Causes serious eye damage.Respiratory or skin sensitizationSkin Sens. 1: May cause an allergic skin reaction.

Resp. Sens. 1: May cause allergy or asthma symptoms or breathing difficulties if

inhaled.

Germ cell mutagenicity Muta. 1B: May cause genetic defects.

Carcinogenicity Carc. 1A: May cause cancer.

Reproductive toxicity Based upon the available data, the classification criteria are not met.

STOT - single exposure STOT SE 3: May cause respiratory irritation.

STOT - repeated exposure STOT RE 1: Causes damage to organs through prolonged or repeated

exposure.

Aspiration hazard Based upon the available data, the classification criteria are not met.

11.2 Other information None.

12. SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity Aquatic Chronic 2: Toxic to aquatic life with long lasting effects.

Estimated Mixture LC50 > 1 ≤ 10 mg/l (Fish)

12.2 Persistence and degradability The methods for determining the biological degradability are not applicable to

inorganic substances.

12.3 Bioaccumulative potential No data for the mixture as a whole.

12.4 Mobility in soil The product is predicted to have moderate mobility in soil.

12.5 Results of PBT and vPvB assessment Not classified as PBT or vPvB.

12.6 Other adverse effects None known.

13. SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods Do not release undiluted and unneutralised to the sewer. This material and its

container must be disposed of as hazardous waste (2008/98/EEC). Containers must be decontaminated in accordance with all applicable regulations.

13.2 Additional Information Dispose of contents in accordance with local, state or national legislation.

14. SECTION 14: TRANSPORT INFORMATION

ADR/RID / IMDG / IATA

14.1 UN number UN 3082

14.2 UN proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Chromium

(VI) trioxide) 9

14.3 Transport hazard class(es)14.4 Packing group

14.5 Environmental hazards Classified as a Marine Pollutant/ Environmentally hazardous substance

Revision: 2.0 Date: 21.08.2015



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),

1272/2008 (CLP) & 2015/830

www.vishaypg.com

14.6 Special precautions for user

Transport in bulk according to Annex II of MARPOL

73/78 and the IBC Code

14.8 **Additional Information**

14.7

15.2

See Section: 2 Not applicable.

None.

15. **SECTION 15: REGULATORY INFORMATION**

15.1 Safety, health and environmental

> regulations/legislation specific for the substance or mixture

15.1.1 **EU** regulations

Authorisations and/or Restrictions On Use

manufacture, placing on the market and use of certain dangerous substances, preparations and articles. Chromium (VI) trioxide (CAS# 1333-82-0) Entry

For professional users only. REACH: ANNEX XVII restrictions on the

number: 28, 29 and 47.

Substance(s) of Very High Concern (SVHCs)

Chromium (VI) trioxide (CAS# 1333-82-0) - CMR effects (carcinogenity,

mutagenicity and toxicity for reproduction).

15.1.2 **National regulations**

Wassergefährdungsklasse (Germany)

Chemical Safety Assessment

Water hazard class: 3

Not available.

SECTION 16: OTHER INFORMATION 16.

The following sections contain revisions or new statements: 1-16.

References: Existing Safety Data Sheet (SDS), Harmonised Classification(s) for Phosphoric Acid (CAS# 7664-38-2) and Chromium (VI) trioxide (CAS# 1333-82-0), Existing ECHA registration(s) for Silicon Dioxide (CAS# 7631-86-9), Aluminium tris(dihydrogen phosphate) (CAS# 13530-50-2) and Phosphoric Acid (CAS# 7664-38-2), and the Classification and Labelling Inventory for Quartz (CAS# 14808-60-7), Distilled water (CAS# 7732-18-5) and Gum tragacanth (CAS# 9000-65-1).

Classification of the substance or mixture According to Regulation (EC) No. 1272/2008 (CLP)	Classification Procedure
Skin Irrit. 2; H315	Threshold Calculation
Skin Sens. 1; H317	Threshold Calculation
Eye Dam. 1; H318	Threshold Calculation
Acute Tox. 4; H332	Acute Toxicity Estimate Mixture Calculation
Resp. Sens. 1; H334	Threshold Calculation
STOT SE 3; H335	Threshold Calculation (SCL)
Muta. 1B; H340	Threshold Calculation
Carc. 1A; H350	Threshold Calculation
STOT RE 1; H372	Threshold Calculation
Aquatic Chronic 2; H411	Summation Calculation

LEGEND

I TFI Long Term Exposure Limit Short Term Exposure Limit STEL **DNEL** Derived No Effect Level

PNEC Predicted No Effect Concentration

PBT PBT: Persistent, Bioaccumulative and Toxic vPvB very Persistent and very Bioaccumulative

Training advice: Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required.

Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Vishay Precision Group gives no warranty as to the fitness of

Revision: 2.0 Date: 21.08.2015



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),

1272/2008 (CLP) & 2015/830

www.vishaypg.com

the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Vishay Precision Group accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

Annex to the extended Safety Data Sheet (eSDS)

No information available.



Legal Disclaimer Notice

Vishay Precision Group, Inc.

Disclaimer

ALL PRODUCTS. PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "VPG"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify VPG's terms and conditions of purchase, including but not limited to, the warranty expressed therein.

VPG makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. To the maximum extent permitted by applicable law, VPG disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on VPG's knowledge of typical requirements that are often placed on VPG products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. You should ensure you have the current version of the relevant information by contacting VPG prior to performing installation or use of the product, such as on our website at vpgsensors.com.

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of VPG.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling VPG products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify VPG for any damages arising or resulting from such use or sale. Please contact authorized VPG personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Copyright Vishay Precision Group, Inc., 2014. All rights reserved.

Document No.: 63999 Revision: 15-Jul-2014