Revision: 1.1 Date: 17/02/2016



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),

1272/2008 (CLP) & 2015/830

www.vpgsensors.com

### 1. SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product Name White Mineral Oil

Chemical Name White mineral oil (petroleum)

CAS No. 8042-47-5
EINECS No. 232-455-8
REACH Registration No. None assigned.

1.2 Relevant identified uses of the substance or mixture

and uses advised against

Identified Use(s)
Uses Advised Against
Release Agent
None.

1.3 Details of the supplier of the safety data sheet

Company Identification VISHAY MEASUREMENTS GROUP UK LTD

Stroudley Road Basingstoke Hampshire United Kingdom RG24 8FW

 Telephone
 +44 (0) 1256 462131

 Fax
 +44 (0) 1256 471441

 E-Mail (competent person)
 mm.uk@vishaypg.com

**1.4 Emergency telephone number** (00-1) 703-527-3887

CHEMTREC

## 2. SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

2.1.1 Regulation (EC) No. 1272/2008 (CLP) Not classified.

2.2 Label elements According to Regulation (EC) No. 1272/2008 (CLP)

Product Name White Mineral Oil

Hazard Pictogram(s)

None assigned.

Signal Word(s) None assigned.

Contains: Not applicable.

Hazard Statement(s)

None assigned.

Precautionary Statement(s) P103: Read label before use.

P101: If medical advice is needed, have product container or label at hand.

2.3 Other hazards None.

## 3. SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1 Substances

EC Classification Regulation (EC) No. 1272/2008 (CLP)

Chemical identity of the substance	%W/W	CAS No.	EC No.	Hazard classification
White mineral oil (petroleum)	100	8042-47-5	232-455-8	Not classified

Revision: 1.1 Date: 17/02/2016



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),

1272/2008 (CLP) & 2015/830

www.vpgsensors.com

#### 3.2 Mixtures Not applicable

### **SECTION 4: FIRST AID MEASURES**



4.

#### Description of first aid measures 4.1

Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position

> comfortable for breathing. Unlikely to be hazardous by inhalation because of the low vapour pressure of the material at ambient temperature. Get medical

advice/attention if you feel unwell.

Skin Contact IF ON SKIN: Wash affected skin with soap and water. If irritation develops and

persists, get medical attention. Wash contaminated clothing before reuse. Hot/molten product: In case of burns immediately cool affected skin as long as

possible with cold water.

Eye Contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get

medical advice/attention.

If hot product is splashed into the eye, it should be cooled immediately to

dissipate heat, under cold running water.

Ingestion IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Do not give milk or

> alcoholic beverages. If vomiting occurs spontaneously, keep head below hips to prevent aspiration into the lungs. Obtain medical attention if symptoms appear or if large quantities have been ingested. If aspiration is suspected obtain

immediate medical attention.

4.2 Most important symptoms and effects, both acute and

delayed

Repeated or prolonged contact may cause defatting of the skin resulting in dryness, cracking and dermatitis. Laxative. May cause irritation: Gastrointestinal

4.3 Indication of any immediate medical attention and

special treatment needed

Remove from exposure. Treat symptomatically.

#### 5. **SECTION 5: FIRE-FIGHTING MEASURES**

#### 5.1 Extinguishing media

Suitable Extinguishing Media

As appropriate for surrounding fire. Extinguish preferably with foam, carbon dioxide or dry chemical.

Unsuitable extinguishing Media

Do not use water jet. Direct water jet may spread the fire. Water extinguishers may cause frothing.

5.2 Special hazards arising from the substance or mixture

Combustion will evolve toxic, irritant and flammable vapours. Thermal

5.3 Advice for fire-fighters Acrid smoke. Will float and can be reignited on surface water. Fire fighters should wear complete protective clothing including self-contained

decomposition will evolve toxic and flammable vapours. Oxides of carbon and

breathing apparatus. Do not breathe fumes. Keep containers cool by spraying with water if exposed to fire. Do not allow run-off from fire fighting to enter drains or water courses.

#### **SECTION 6: ACCIDENTAL RELEASE MEASURES** 6.

6.1 Personal precautions, protective equipment and emergency procedures

Evacuate area. Shut off leaks if without risk. Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Avoid breathing mist/vapours/spray. Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. See Section: 8. Ensure adequate ventilation. Caution - spillages may

6.2 **Environmental precautions** 

Avoid release to the environment. Do not allow to enter drains, sewers or watercourses. Will float and can be reignited on surface water.

6.3 Methods and material for containment and cleaning Contain spillages. Adsorb spillages onto sand, earth or any suitable adsorbent

be slippery.

Revision: 1.1 Date: 17/02/2016



www.vpgsensors.com

# ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),

1272/2008 (CLP) & 2015/830

up

material. Transfer to a lidded container for disposal or recovery. Ventilate the

area and wash spill site after material pick-up is complete.

Reference to other sections 6.4

See Section: 8, 13

#### 7. **SECTION 7: HANDLING AND STORAGE**

7.1 Precautions for safe handling

Ensure adequate ventilation. Avoid breathing mist/vapours/spray. In case of inadequate ventilation wear respiratory protection. Use personal protective equipment as required. See Section: 8. Avoid contact with skin, eyes or clothing. Avoid splashing. Avoid generation of mist (May be flammable). Do not eat, drink or smoke when using this product. Wash hands before breaks and after work. Keep container tightly closed, in a cool, well ventilated place. Keep away from heat, sources of ignition and direct sunlight.

7.2 Conditions for safe storage, including any incompatibilities

Storage temperature

Storage life

Incompatible materials

Stable under normal conditions. Avoid contact with: Strong oxidising agents (e.g. liquid chlorine and oxygen),

Strong Acids and Alkalis.

Store at temperatures not exceeding (°C): 49

7.3 Specific end use(s) Release Agent

#### 8. SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

8.1.1 **Occupational Exposure Limits**  Not established.

8.1.2 **Biological limit value**  Not established.

**PNECs and DNELs** 8.1.3

Not established.

8.2 **Exposure controls** 

8.2.1 Appropriate engineering controls

Ensure adequate ventilation or use appropriate containment. Atmospheric levels should be controlled in compliance with the occupational exposure limit. Guarantee that the eye flushing systems and safety showers are located close to the working place.

8.2.2 Individual protection measures, such as personal protective equipment (PPE)

General hygiene measures for the handling of chemicals are applicable. Avoid contact with skin, eyes or clothing. Avoid breathing mist/vapours/spray. Wash hands before breaks and after work. Keep work clothes separately. Contaminated clothing should be thoroughly cleaned. Do not eat, drink or smoke

at the work place.

Eye/face protection



Wear protective eye glasses for protection against liquid splashes. Wear eye protection with side protection (EN166).

Skin protection



Hand protection: Prolonged exposure - Wear impervious gloves (EN374). Breakthrough time of the glove material: refer to the information provided by the gloves' producer.

Body protection: Wear work clothes with long sleeves.

When dealing with heated material: Heat resistant coveralls (with trousers legs over boots and sleeves over cuffs of gloves), heat resistant heavy duty antiskid boots.

Respiratory protection

Respiratory protection is not necessary if room is well ventilated. In case of inadequate ventilation wear respiratory protection. Open system(s): Wear suitable respiratory protective equipment.

Revision: 1.1 Date: 17/02/2016



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),

1272/2008 (CLP) & 2015/830



www.vpgsensors.com

Thermal hazards

When dealing with heated material: Heat resistant coveralls (with trousers legs

over boots and sleeves over cuffs of gloves), heat resistant heavy duty antiskid

boots. Avoid splashing.

8.2.3 **Environmental Exposure Controls** Avoid release to the environment.

#### 9. **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

#### 9.1 Information on basic physical and chemical properties

Colourless liquid **Appearance** Odour Odourless Odour Threshold Not available. Not established. На Melting Point/Freezing Point -9 ℃ 302 - 427 ℃ Initial boiling point and boiling range

Flash point 185 ℃ **Evaporation Rate** Not available. Flammability (solid, gas) Non-flammable.

Upper/lower flammability or explosive limits Flammable Limits (Upper) (%v/v): 1.0 Flammable Limits (Lower) (%v/v): 7.0

Vapour pressure < 0.1 mm Hg @ 21.1 °C

Vapour density > 10 (Air = 1)Relative density  $0.85 (H_2O = 1)$ Solubility(ies) Negligible (Water) Not established. Partition coefficient: n-octanol/water Not established. Auto-ignition temperature **Decomposition Temperature** Not established.

350 SUS @ 37.8°C (≈ 75 mm²/s) Viscosity

Explosive properties Not explosive. Oxidising properties Not oxidising.

Other information 9.2 Volatile Organic Compound Content: 0%

#### **SECTION 10: STABILITY AND REACTIVITY** 10.

10.1 Reactivity Stable under normal conditions. 10.2 Chemical stability Stable under normal conditions.

10.3 Possibility of hazardous reactions Combustion or thermal decomposition will evolve toxic and irritant vapours.

Store at temperatures not exceeding (°C): 49. Keep away from heat, sources of 10.4 Conditions to avoid

ignition and direct sunlight. Avoid splashing. Avoid generation of mist (May be

flammable).

Incompatible materials Avoid contact with: Strong oxidising agents (e.g. liquid chlorine and oxygen), 10.5

Strong Acids and Alkalis.

10.6 Hazardous decomposition product(s) Thermal decomposition will evolve toxic and flammable vapours. Carbon

monoxide, Carbon dioxide and Acrid smoke.

#### **SECTION 11: TOXICOLOGICAL INFORMATION** 11.

#### 11.1 Information on toxicological effects

**Acute toxicity** 

Ingestion Based on available data, the classification criteria are not met. Acute Toxicity Estimate Mixture Calculation: > 2000 mg/kg bw/day

Inhalation Based on available data, the classification criteria are not met.

Acute Toxicity Estimate Mixture Calculation: > 20 mg/l

Skin Contact Based on available data, the classification criteria are not met.

DOCUMENT NO. 14259 Page: 4 of 6 **REVISION I** 

Revision: 1.1 Date: 17/02/2016



www.vpgsensors.com

# ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),

1272/2008 (CLP) & 2015/830

Acute Toxicity Estimate Mixture Calculation: > 2000 mg/kg bw/day Skin corrosion/irritation Based on available data, the classification criteria are not met. Serious eve damage/irritation Based on available data, the classification criteria are not met. Respiratory or skin sensitization Based on available data, the classification criteria are not met. Germ cell mutagenicity Based on available data, the classification criteria are not met. Carcinogenicity Based on available data, the classification criteria are not met. Reproductive toxicity Based on available data, the classification criteria are not met. STOT - single exposure Based on available data, the classification criteria are not met. STOT - repeated exposure Based on available data, the classification criteria are not met.

**Aspiration hazard** 

Other information 11.2 None.

#### **SECTION 12: ECOLOGICAL INFORMATION** 12.

12.1 Based on available data, the classification criteria are not met. **Toxicity** 

Estimated LC50 (96 hour) > 100 mg/l (Fish)

12.2 Persistence and degradability Inherently biodegradable.

12.3 Bioaccumulative potential No data.

12.4 Mobility in soil The substance has low mobility in soil. Poorly water soluble product.

Results of PBT and VPVB assessment 12.5 Not classified as PBT or vPvB.

Other adverse effects 12.6 None known.

#### **SECTION 13: DISPOSAL CONSIDERATIONS** 13.

13.1 Waste treatment methods Avoid release to the environment. Dispose of this material and its container as

hazardous waste (2008/98/EEC). Containers of this material may be hazardous

when empty since they retain product residue.

13.2 **Additional Information** Dispose of contents in accordance with local, state or national legislation.

#### 14. **SECTION 14: TRANSPORT INFORMATION**

### ADR/RID / IMDG / IATA/ICAO

14.1 **UN number** None assigned. 14.2 **UN proper shipping name** Not applicable. 14.3 Transport hazard class(es) Not applicable.

14.4 Packing group Not applicable.

14.5 **Environmental hazards** Not classified as a Marine Pollutant.

14.6 Special precautions for user See Section: 2 14.7 Transport in bulk according to Annex II of Not applicable.

MARPOL73/78 and the IBC Code

14.8 **Additional Information** None.

#### **SECTION 15: REGULATORY INFORMATION** 15.

Safety, health and environmental 15.1

regulations/legislation specific for the substance or

mixture

EU regulations 15.1.1

Substance(s) of Very High Concern (SVHCs) None Authorisations and/or Restrictions On Use None

15.1.2 National regulations

> Wassergefährdungsklasse (Germany) Water hazard class: 1

**Chemical Safety Assessment** 15.2 Not available.

Revision: 1.1 Date: 17/02/2016



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),

1272/2008 (CLP) & 2015/830

www.vpgsensors.com

## 16. SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16.

References: Existing Safety Data Sheet (SDS), Existing ECHA registration(s) for White Mineral Oil (CAS# 8042-47-5).

Classification of the substance or mixture According to Regulation (EC) No. 1272/2008 (CLP)	Classification Procedure
Not classified	Existing ECHA registration for White Mineral Oil

### **LEGEND**

LTEL Long Term Exposure Limit
STEL Short Term Exposure Limit
DNEL Derived No Effect Level

PNEC Predicted No Effect Concentration

PBT PBT: Persistent, Bioaccumulative and Toxic PvB PBT: very Persistent and very Toxic

Training advice: Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required.

### **Disclaimers**

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Vishay Precision Group gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Vishay Precision Group accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

### Annex to the extended Safety Data Sheet (eSDS)

No information available.



# **Legal Disclaimer Notice**

Vishay Precision Group, Inc.

# Disclaimer

ALL PRODUCTS. PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "VPG"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify VPG's terms and conditions of purchase, including but not limited to, the warranty expressed therein.

VPG makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. To the maximum extent permitted by applicable law, VPG disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on VPG's knowledge of typical requirements that are often placed on VPG products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. You should ensure you have the current version of the relevant information by contacting VPG prior to performing installation or use of the product, such as on our website at vpgsensors.com.

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of VPG.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling VPG products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify VPG for any damages arising or resulting from such use or sale. Please contact authorized VPG personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Copyright Vishay Precision Group, Inc., 2014. All rights reserved.

Document No.: 63999 Revision: 15-Jul-2014