

SAFETY DATA SHEET

M-Bond 450 LVOC Part B

www.vpgsensors.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Date of Issue: 27 January 2023
Date of First Issue: 27 January 2023
Version: 1.0

SECTION 1: IDENTIFICATION

Product identifier

Product Name M-Bond 450 LVOC Part B

Other Means of Identification

None known.

Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s) Adhesive
Uses Advised Against Anything other than the above.

Details of the supplier of the safety data sheet

Supplier VISHAY MEASUREMENTS GROUP, INC.
Post Office Box 27777
Raleigh, NC 27611
USA
Telephone 919-365-3800
Fax 919-365-3945
E-Mail (competent person) mm.us@vpgsensors.com

Emergency telephone number

Emergency Phone No. +1 800-262-8200 (for spills and releases) CHEMTREC (24 hours)
Languages spoken English

SECTION 2: HAZARD(S) IDENTIFICATION

Classification of the substance or mixture in accordance with paragraph (d) of 29 CFR 1910.1200

Physical hazards Flammable Liquid, Category 2
Health hazards Serious eye damage/irritation, Category 2
Specific target organ toxicity — single exposure, Category 3 (Narcotic effects)
Reproductive toxicant, Category 1B
Specific target organ toxicity — single exposure, Category 2
Specific target organ toxicity - Repeated exposure, Category 1
Environmental hazards Hazardous to the aquatic environment (Chronic), Category 3

Label elements

Hazard Pictogram(s)



Signal Word(s)

DANGER

Hazard Statement(s)

Highly flammable liquid and vapour.
Causes serious eye irritation.
May cause drowsiness or dizziness.
May damage fertility. May damage the unborn child.
May cause damage to organs.
Causes damage to organs through prolonged or repeated exposure.
Harmful to aquatic life with long lasting effects.
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Keep container tightly closed.
Ground and bond container and receiving equipment.

Precautionary Statement(s)

SAFETY DATA SHEET

M-Bond 450 LVOC Part B

www.vpgsensors.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Date of Issue: 27 January 2023
Date of First Issue: 27 January 2023
Version: 1.0

Use explosion proof electrical equipment.
Use non-sparking tools.
Take action to prevent static discharges.
Do not breathe mist/vapours/spray.
Wash hands and exposed skin thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Avoid release to the environment.
Wear protective gloves/eye protection/face protection.
IF ON SKIN or hair: Take off immediately all contaminated clothing. Rinse skin with water.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed or concerned: Call a POISON CENTER/doctor.
In case of fire: Use foam to extinguish.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents in accordance with local, state or national legislation.

Other hazards

Vapours can form explosive mixtures with air.

Percent of the mixture consists of ingredient(s) of unknown acute toxicity:

0% of the mixture consists of ingredients of unknown acute inhaled toxicity.
0% of the mixture consists of ingredients of unknown acute oral toxicity.
0% of the mixture consists of ingredients of unknown acute dermal toxicity.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Substances
not applicable

Mixtures Substances in preparations / mixtures

Classification: OSHA HCS (29 CFR 1910.1200)

| Chemical identity of the substance | %W/W | CAS No. | EC No. | Hazard classification |
|------------------------------------|---------|----------|-----------|---|
| Acetone | 40 - 60 | 67-64-1 | 200-662-2 | Flammable liquid, Category 3 Serious eye damage/irritation, Category 2 Specific Target Organ Toxicity — Single Exposure, Category 3 |
| Dimethyl carbonate | 20 – 30 | 616-38-6 | 210-478-4 | Flammable liquid, Category 2 |
| 2-Ethoxyethanol | 20 - 30 | 110-80-5 | 203-804-1 | Flammable liquid, Category 3 Acute Toxicity, Category 4 - oral Acute Toxicity, Category 4 - inhalation Reproductive toxicant, Category 1B |
| 4,4'-Sulfonyldianiline | 15 – 20 | 80-08-0 | 201-248-4 | Acute Toxicity, Category 4 - oral Specific Target Organ Toxicity — Single Exposure, Category 2 (blood) Specific target organ toxicity - Repeated exposure, Category 1 (Testes, epididymis) Specific target organ toxicity - Repeated exposure, Category 2 (blood, spleen, liver) |

SAFETY DATA SHEET

M-Bond 450 LVOC Part B

www.vpgsensors.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Date of Issue: 27 January 2023
Date of First Issue: 27 January 2023
Version: 1.0

| | | | | |
|--------------------------------------|-----------|-----------|-----------|---|
| | | | | Hazardous to the aquatic environment, Chronic, Category 2 |
| Xylene | 1 - 10 | 1330-20-7 | 215-535-7 | Flammable liquid, Category 3 Aspiration toxicity, Category 1 Acute Toxicity, Category 4 Skin corrosion/irritation, Category 2 Serious eye damage/irritation, Category 2 Acute Toxicity, Category 4 - inhalation Specific Target Organ Toxicity — Single Exposure, Category 3 Specific target organ toxicity - Repeated exposure, Category 2 Hazardous to the aquatic environment, Chronic, Category 3 |
| Boron trifluoride ethylamine complex | 0.1 - 0.5 | 0.1 - 0.5 | 75-23-0 | Acute Toxicity, Category 4 - oral Skin corrosion/irritation, Category 2 Serious eye damage/irritation, Category 2 Specific Target Organ Toxicity — Single Exposure, Category 3 |

SECTION 4: FIRST AID MEASURES



Description of first aid measures

Self-protection of the first aider

Inhalation

Skin Contact

Eye Contact

Ingestion

Most important symptoms and effects, both acute and delayed

Indication of any immediate medical attention and special treatment needed

Avoid breathing mist/vapours/spray. Ensure adequate ventilation. Wear suitable protective clothing. Wear suitable respiratory protective equipment if exposure to high levels of material are likely. Avoid contact with skin. Contaminated clothing should be laundered before reuse. Do not use mouth-to-mouth resuscitation. Eyewash facilities should be stationed close to workplace where possible.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

IF ON SKIN: Gently wash with plenty of soap and water. Remove contaminated clothing and wash clothing before reuse. If irritation (redness, rash, blistering) develops, get medical attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

IF SWALLOWED: Rinse mouth. Do not give anything by mouth to an unconscious person. Do NOT induce vomiting. If symptoms occur obtain medical attention.

May be harmful if swallowed. Causes serious eye irritation. May cause drowsiness or dizziness. May damage fertility. May damage the unborn child. May cause damage to organs. May cause damage to organs through prolonged or repeated exposure.

Treat symptomatically.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing media

SAFETY DATA SHEET

M-Bond 450 LVOC Part B

www.vpgsensors.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Date of Issue: 27 January 2023
Date of First Issue: 27 January 2023
Version: 1.0

Suitable Extinguishing Media

As appropriate for surrounding fire. Extinguish preferably with foam, carbon dioxide or dry chemical.

Unsuitable extinguishing Media

Do not use water jet. Direct water jet may spread the fire.

Special hazards arising from the substance or mixture

Highly flammable liquid and vapour. Vapours can form explosive mixtures with air. Containers may explode when involved in a fire. Keep container(s) exposed to fire cool, by spraying with water. Thermal decomposition will evolve toxic and corrosive vapours: Carbon dioxide, Carbon monoxide Vapours are heavier than air and may travel considerable distances to a source of ignition and flashback. Sealed containers may rupture explosively if hot.

Advice for fire-fighters

Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Do not breathe fumes. Keep containers cool by spraying with water if exposed to fire. Avoid run off to waterways and sewers.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Stop leak if safe to do so. Eliminate all ignition sources if safe to do so. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing mist/vapours/spray. Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. See Section: 8. The vapour is heavier than air; beware of pits and confined spaces.

Methods and material for containment and cleaning up

Ensure suitable personal protection during removal of spillages. Use non-sparking equipment when picking up flammable spill. Adsorb spillages onto sand, earth or any suitable adsorbent material. Do NOT absorb in saw-dust or other combustible absorbents. Transfer to a lidded container for disposal or recovery. Ventilate the area and wash spill site after material pick-up is complete. Dispose of this material and its container as hazardous waste. Allow small spillages to evaporate provided there is adequate ventilation.

Large spillages:

Evacuate the area and keep personnel upwind. Notify police and fire brigade as soon as possible.

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling

Ensure adequate ventilation. Avoid breathing mist/vapours/spray. Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. See Section: 8. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Do not use sparking tools. Do not spray on an open flame or other ignition source. Do not eat, drink or smoke when using this product. Wash hands before breaks and after work. Ground/bond container and receiving equipment.

Conditions for safe storage, including any incompatibilities

Store in a cool/low-temperature, well-ventilated (dry) place away from heat and ignition sources. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep away from direct sunlight. Do not reuse empty containers.

Storage temperature

Store in a cool/low temperature.

Incompatible materials

Keep away from: Strong oxidising agents, Strong acids and alkali.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

| SUBSTANCE | CAS No. | ppm (a) ¹ | mg/m3(b) ¹ | Skin designation | Source |
|------------------------------|-----------|----------------------|-----------------------|------------------|--------|
| Acetone | 67-64-1 | 1000 | 2400 | - | OSHA |
| 2-Ethoxyethanol (Cellosolve) | 110-80-5 | 200 | 740 | X | OSHA |
| Xylenes (o-, m-, p-isomers) | 1330-20-7 | 100 | 435 | - | OSHA |

SAFETY DATA SHEET

M-Bond 450 LVOC Part B

www.vpgsensors.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Date of Issue: 27 January 2023
Date of First Issue: 27 January 2023
Version: 1.0

Source:

OSHA: Occupational Health and Safety Act - Permissible Exposure Limit (PEL), 1910.1000 TABLE Z-1

Biological exposure indices

| SUBSTANCE | CAS No. | Determinant | Biological Exposure Indices | Sampling Time | Note |
|---------------------------------|----------|------------------------------|-----------------------------|---------------------------------|------|
| Acetone | 67-64-1 | Acetone in urine | 25mg/L | End of Shift | Ns |
| 2-Ethoxyethanol (Cellosolve) | 110-80-5 | 2-Ethoxyacetic acid in urine | 2mg/L creatinine | End of shift at end of workweek | - |

Source:

2015 ACGIH Biological Exposure Indices (BEIs)

Notes:

Nonspecific - The determinant is nonspecific, since it is also observed after exposure to other chemicals.

Appropriate engineering controls

Ensure adequate ventilation or use appropriate containment. Atmospheric levels should be controlled in compliance with the occupational exposure limit. Local exhaust recommended. Use non-sparking ventilation systems, approved explosion-proof equipment, and intrinsically safe electrical systems. Eyewash facilities should be stationed close to workplace where possible.

Individual protection measures, such as personal protective equipment (PPE)

General hygiene measures for the handling of chemicals are applicable. Avoid contact with skin, eyes or clothing. Avoid breathing mist/vapours/spray. Wash hands before breaks and after work. Keep work clothes separately. Contaminated clothing should be thoroughly cleaned. Do not eat, drink or smoke at the work place.

Protective clothing should be selected specifically for the working place, depending on concentration and quantity of the hazardous substances handled. The resistance of the protective clothing to chemicals should be ascertained with the respective supplier.

Eye/face protection



Wear protective eye glasses for protection against liquid splashes. Wear eye protection with side protection (EN166).

Skin protection



Hand protection:

Wear impervious gloves (EN374). Gloves should be changed regularly to avoid permeation problems. Breakthrough time of the glove material: refer to the information provided by the gloves' producer. Recommended: PVC / Nitrile rubber.

During full contact:

Protective index 6, corresponding > 480 minutes of permeation time according to EN 374.

Nitrile rubber (Minimum thickness: 0.33 mm)

Butyl rubber (Minimum thickness: 0.5 mm)

During splash contact:

At least protective index 5, corresponding > 240 minutes of permeation time according to EN 374

Polychloroprene - CR (Minimum thickness: 0.5 mm)

Unsuitable gloves materials:

Natural rubber/natural latex, Polyvinyl chloride - PVC.

SAFETY DATA SHEET

M-Bond 450 LVOC Part B

www.vpgsensors.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Date of Issue: 27 January 2023
Date of First Issue: 27 January 2023
Version: 1.0

Respiratory protection



Body protection:

Wear dustproof working clothes. Wear impervious protective clothing, including boots, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Use only in well-ventilated areas. In case of inadequate ventilation wear respiratory protection. A suitable mask with filter type A (EN141 or EN405) may be appropriate.

High concentrations: Wear suitable respiratory equipment. Recommended: Self-contained breathing apparatus (DIN EN 137)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

| | |
|--|--------------------------|
| Appearance | Liquid |
| Odor | Not established. |
| Odor Threshold | Not established. |
| pH | Not established. |
| Melting Point/Freezing Point | Not established. |
| Initial boiling point and boiling range | Not established. |
| Flash Point | Not established. |
| Evaporation Rate | Not established. |
| Flammability (solid, gas) | Not established. |
| Upper/lower flammability or explosive limits | Not established. |
| Vapour pressure | Not established. |
| Vapour density | Not established. |
| Relative density | Not established. |
| Solubility(ies) | Not established. |
| Partition coefficient: n-octanol/water | not applicable - Mixture |
| Auto-ignition temperature | Not established. |
| Decomposition Temperature | Not established. |
| Viscosity | Not established. |

SECTION 10: STABILITY AND REACTIVITY

| | |
|---|--|
| Reactivity | Stable under normal conditions. |
| Chemical stability | Stable under normal conditions. Hazardous polymerisation will not occur. |
| Possibility of hazardous reactions | Vapour is explosive in air at temperatures higher than the flash point. Vapours are heavier than air and may travel considerable distances to a source of ignition and flashback. |
| Conditions to avoid | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep from direct sunlight. Do not spray on an open flame or other ignition source. Take precautionary measures against static discharge. |
| Incompatible materials | Strong oxidising agents, Strong acids and alkali. |
| Hazardous decomposition product(s) | Highly flammable liquid and vapour. May decompose in a fire giving off toxic fumes. Vapours are heavier than air and may travel considerable distances to a source of ignition and flashback. In confined spaces, sewers, etc., the vapours may collect to form explosive mixtures with air. When heated to soldering temperatures, the solvents are evaporated and rosin may be thermally degraded. Decomposition products: Carbon monoxide, Carbon dioxide, aliphatic aldehydes, aromatic aldehydes, acids and terpenes. |

SECTION 11: TOXICOLOGICAL INFORMATION

Information on toxicological effects

Acute toxicity - Ingestion

Mixture: Based upon the available data, the classification criteria are not met. Calculated acute toxicity estimate (ATE) >2,000 mg/kg.

Acute toxicity - Skin Contact

Mixture: Based upon the available data, the classification criteria are not met. Calculated acute toxicity estimate (ATE) >2,000 mg/kg.

SAFETY DATA SHEET

M-Bond 450 LVOC Part B

www.vpgsensors.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Date of Issue: 27 January 2023
Date of First Issue: 27 January 2023
Version: 1.0

| | |
|---|---|
| Acute toxicity - Inhalation | Mixture: Based upon the available data, the classification criteria are not met. Acute Toxicity Estimate Mixture Calculation: Estimated LC50 >20mg/l. (Vapour) |
| Skin corrosion/irritation | Mixture: Based upon the available data, the classification criteria are not met. |
| Serious eye damage/irritation | Mixture: Serious eye damage/irritation, Category 2: Causes serious eye irritation |
| Acetone | Serious eye damage/irritation, Category 2; H319: Causes serious eye irritation. Test Result: Irritating to eyes. (OECD 405) EU Data: Harmonised Classification/ ECHA registration dossier |
| Xylene | Serious eye damage/irritation, Category 2; H319: Causes serious eye irritation. Test Result: Irritating to eyes.(rabbit) (EU Method B.4) EU Data: Harmonised Classification/ ECHA registration dossier |
| Boron trifluoride ethylamine complex | Serious eye damage/irritation, Category 2; H319: Causes serious eye irritation. Test Result: Irritating to eyes. (rabbit) (Unnamed publication, 1979) EU Data: ECHA registration dossier |
| Respiratory or skin sensitization | Mixture: Based upon the available data, the classification criteria are not met. |
| Germ cell mutagenicity | Mixture: Based upon the available data, the classification criteria are not met. |
| Carcinogenicity | Mixture: Based upon the available data, the classification criteria are not met. |
| Reproductive toxicity | Mixture: Reproductive toxicant, Category 1B; May damage fertility. May damage the unborn child. |
| 2-Ethoxyethanol | Reproductive toxicant, Category 1B; H360FD: May damage fertility. May damage the unborn child. Developmental toxicity NOAEL: 23 mg/kg/day (oral) Developmental toxicity LOAEC: 37.4 mg/kg/day (inhalation) EU Data: Harmonised Classification/ ECHA registration dossier |
| STOT - single exposure | Mixture: Based upon the available data, the classification criteria are not met. |
| Acetone | Specific target organ toxicity — single exposure, Category 3 (Narcotic effects); May cause drowsiness or dizziness. EU Data: Harmonised Classification/ ECHA registration dossier |
| 4'-Sulfonyldianiline | Specific target organ toxicity — single exposure, Category 2; May cause damage to organs: blood EU Data: Harmonised Classification/ ECHA registration dossier |
| Xylene | Specific target organ toxicity — single exposure, Category 3; May cause respiratory irritation. EU Data: ECHA registration dossier |
| Boron trifluoride ethylamine complex | Specific target organ toxicity — single exposure, Category 3; May cause respiratory irritation. ECHA registration dossier |
| STOT - repeated exposure | Mixture: Specific target organ toxicity - Repeated exposure, Category 1; H372: Causes damage to organs through prolonged or repeated exposure. |
| 4,4'-Sulfonyldianiline 4,4'-磺酰基双苯胺 | Specific target organ toxicity - Repeated exposure, Category 1; H372: Causes damage to organs through prolonged or repeated exposure.(Testes, epididymis) Specific target organ toxicity - Repeated exposure, Category 2; H373: May cause damage to organs through prolonged or repeated exposure. (blood, spleen, liver) EU Data: Harmonised Classification/ ECHA registration dossier |
| Aspiration hazard | Mixture: Based upon the available data, the classification criteria are not met. |
| Information on likely routes of exposure | |
| Inhalation | Possible – accidental exposure |
| Ingestion | Possible – accidental exposure |
| Skin Contact | Possible – accidental exposure |
| Eye Contact | Unlikely – accidental exposure |
| Early onset symptoms related to exposure | Causes serious eye irritation. Harmful if inhaled. May cause drowsiness or dizziness. May damage fertility. May damage the unborn child. May cause damage to organs. May cause damage to organs through prolonged or repeated exposure. |

SAFETY DATA SHEET

M-Bond 450 LVOC Part B

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Date of Issue: 27 January 2023
Date of First Issue: 27 January 2023
Version: 1.0

| | |
|---|---|
| Delayed health effects from exposure | None Known |
| Exposure levels and health effects | See Section: 8 |
| Interactive effects | |
| Other information | |
| OSHA Designated Carcinogen | No components of the mixture are listed |
| NIOSH Occupational Carcinogen List | No components of the mixture are listed |
| NTP Report on Carcinogens | No components of the mixture are listed |
| IARC Monographs | No components of the mixture are listed |

SECTION 12: ECOLOGICAL INFORMATION

| | |
|--------------------------------------|--|
| Ecotoxicity | Mixture: Hazardous to the aquatic environment (Chronic), Category 3; Harmful to aquatic life with long lasting effects. Estimated Mixture LC50(96 hour) >10 - <100 mg/l (Fish) 4,4'-Sulfonyldianiline Aquatic Chronic 2; H411: Toxic to aquatic life with long lasting effects. Harmonised Classification/ ECHA registration dossier Aquatic Chronic 3; H412: Harmful to aquatic life with long lasting effects. NOEC: 0.714 mg/l Xylene LOEC: 1.29 mg/l (OECD 210) Harmonised Classification/ ECHA registration dossier |
| Persistence and degradability | No data for the mixture as a whole. 2-Ethoxyethanol Readily biodegradable (according to OECD criteria). Dimethyl carbonate Readily biodegradable (according to OECD criteria). Degradation rate (%): 86 (28 days) Acetone Readily biodegradable (according to OECD criteria). Degradation rate (%): 90.9±2.2 (28 days) OECD 301B 4,4'-Sulfonyldianiline Not biodegradable Xylene Readily biodegradable (according to OECD criteria). Boron trifluoride ethylamine complex Degrades by hydrolysis. Degradation products: flourborn-complexes and ethylamine (Readily biodegradable.) |
| Bioaccumulative potential | No data for the mixture as a whole. Log Pow: -0.32 - -0.43 2-Ethoxyethanol Bioconcentration factor (BCF): 0.28 -0.34 Low bioaccumulative potential Log KOW : <3 Dimethyl carbonate Low bioaccumulative potential Acetone Bioconcentration factor (BCF): 3 (calculated) Log KOW= -0.24 Bioaccumulation will not occur 4,4'-Sulfonyldianiline Log KOW : <3 Low bioaccumulative potential Xylene Log KOW : 3.1 – 3.2 Low bioaccumulative potential Boron trifluoride ethylamine complex No data available |
| Mobility in soil | No data for the mixture as a whole. 2-Ethoxyethanol Adsorption to solid soil phase is not expected. Log Koc: 2.99 – 6.65 (OECD 121) Dimethyl carbonate Low partition coefficient n-octanol/water. Completely soluble in water. Adsorption to solid soil phase is not expected. Acetone The substance is predicted to have high mobility in soil. Kd= 1.5 L/kg@ 20 °C 4,4'-Sulfonyldianiline Adsorption to solid soil phase is not expected. Log Koc: 2.73 (OECD 121) Xylene Adsorption to solid soil phase is not expected. Boron trifluoride ethylamine complex No data available |

SAFETY DATA SHEET

M-Bond 450 LVOC Part B

www.vpgsensors.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Date of Issue: 27 January 2023
Date of First Issue: 27 January 2023
Version: 1.0

Other adverse effects

None known

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

This material and its container must be disposed of as hazardous waste. Dispose of wastes in an approved waste disposal facility. Dispose of contents in accordance with local, state or national legislation.

SECTION 14: TRANSPORT INFORMATION

| | Road/Rail (ADR/RID) | Sea transport (IMDG) | Air (ICAO/IATA) |
|--|---------------------------------------|---------------------------------------|---------------------------------------|
| UN number | UN 1133 | UN 1133 | UN 1133 |
| UN proper shipping name | ADHESIVES containing flammable liquid | ADHESIVES containing flammable liquid | ADHESIVES containing flammable liquid |
| Transport hazard class(es) | 3 | 3 | 3 |
| Packing group | II | II | II |
| Environmental hazards | Not applicable | Not classified as a Marine Pollutant. | Not applicable |
| Special precautions for user | See Section: 2 | | |
| Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code | Not applicable | | |
| Additional Information | None | | |

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

US Federal Regulations

| | |
|--|--|
| TSCA Chemical Data Reporting (CDR) Rule | Listed: Acetone; 2-Ethoxyethanol; 4,4'-Sulfonyldianiline; Xylene |
| NIOSH Occupational Carcinogen List | All chemicals are not listed |
| EPCRA Section 313 | All chemicals are not listed |
| CWA 307- Toxic | All chemicals are not listed |
| CERCLA - Hazardous Substances | All chemicals are not listed |
| CWA Section 311 List of Hazardous Substances | All chemicals are not listed |

US State Regulations

| | |
|--|--|
| Proposition 65 (California) | Listed: 2-Ethoxyethanol |
| Massachusetts, New Jersey, Pennsylvania, Rhode Island- State Right to Know Lists | Listed: Acetone; Dimethyl carbonate; 2-Ethoxyethanol; 4,4'-Sulfonyldianiline; Xylene |
| New York - State Right to Know Lists | Listed: Acetone; Dimethyl carbonate; 2-Ethoxyethanol; Xylene |
| Minnesota - State Right to Know Lists | Listed: Acetone; 2-Ethoxyethanol; Xylene |
| Massachusetts – Toxic Use reduction act | Listed: Acetone; 2-Ethoxyethanol; Xylene |

Non-Regional

| | |
|-----------------|--|
| IARC Monographs | Listed: Xylene IARC Classification: Group 3 |
|-----------------|--|

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: Not applicable – V1.0

| | |
|---------------------|-----------------|
| Version | 1.0 |
| Revision Date | 27 January 2023 |
| Date of First Issue | 27 January 2023 |

This Safety Data Sheet was prepared in accordance with US Regulation OSHA HCS (29 CFR 1910.1200)

References:

SAFETY DATA SHEET

M-Bond 450 LVOC Part B

www.vpgsensors.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Date of Issue: 27 January 2023
Date of First Issue: 27 January 2023
Version: 1.0

EU Data:

Harmonised Classification(s) for Acetone (CAS No. 67-64-1), Dimethyl carbonate (CAS No. 616-38-6), 2-Ethoxyethanol (CAS No. 110-80-5), 4,4'-Sulfonyldianiline (CAS No. 80-08-0), Xylene (CAS No. 1330-20-7)
Existing ECHA registration(s) for Acetone (CAS No. 67-64-1), 2-Ethoxyethanol (CAS No. 110-80-5), 4,4'-Sulfonyldianiline (CAS No. 80-08-0), Xylene (CAS No. 1330-20-7), Boron trifluoride ethylamine complex (CAS No. 75-23-0)

| Classification of the substance or mixture in accordance with paragraph (d) of 29 CFR 1910.1200 | Classification Procedure |
|---|--------------------------------|
| Flammable Liquid, Category 2 | Expert judgement - Flash point |
| Serious eye damage/irritation, Category 2 | Threshold Calculation |
| Specific target organ toxicity — single exposure, Category 3 (Narcotic effects) | Threshold Calculation |
| Reproductive toxicant, Category 1B | Threshold Calculation |
| Specific target organ toxicity — single exposure, Category 2 | Threshold Calculation |
| Specific target organ toxicity - Repeated exposure, Category 1 | Threshold Calculation |
| Hazardous to the aquatic environment (Chronic), Category 3 | Threshold Calculation |

LEGEND

| | |
|-----------|---|
| ADR/RID | ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road / RID: Regulations concerning the international railway transport of dangerous goods |
| BCF | Bioconcentration factor (BCF) |
| CAS | CAS: Chemical Abstracts Service |
| DNEL | Derived No Effect Level |
| EU | European Union |
| EC | EC: European Community |
| EU | European Union |
| IATA | IATA: International Air Transport Association |
| ICAO/IATA | ICAO: International Civil Aviation Organization / IATA: International Air Transport Association |
| IMDG | IMDG: International Maritime Dangerous Goods |
| PBT | Persistent, Bioaccumulative and Toxic |
| PNEC | Predicted No Effect Concentration |
| UN | United Nations |
| vPvB | very Persistent and very Bioaccumulative |

Training advice: Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required.

Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Vishay Precision Group gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Vishay Precision Group accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.



Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "VPG"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify VPG's terms and conditions of purchase, including but not limited to, the warranty expressed therein.

VPG makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. **To the maximum extent permitted by applicable law, VPG disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.**

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on VPG's knowledge of typical requirements that are often placed on VPG products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. You should ensure you have the current version of the relevant information by contacting VPG prior to performing installation or use of the product, such as on our website at vpgsensors.com.

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of VPG.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling VPG products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify VPG for any damages arising or resulting from such use or sale. Please contact authorized VPG personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Copyright Vishay Precision Group, Inc., 2014. All rights reserved.