# M-Bond 600 Adhesive

## Vishay Measurements Group, Inc.

Version No: **5.6**
Safety Data Sheet

Initial Date: **11/26/2025**
Revision Date: **04/14/2026**
Print Date: **10/13/2026**
S.GHS.IND.EN

## SECTION 1 Identification of the substance / mixture and of the company / undertaking

### Product Identifier

| | |
|---|---|
| **Product name** | M-Bond 600 Adhesive |
| **Chemical Name** | Not Applicable |
| **Synonyms** | Not Available |
| **Proper shipping name** | ADHESIVES containing flammable liquid |
| **Chemical formula** | Not Applicable |
| **Other means of identification** | Not Available |

### Relevant identified uses of the substance or mixture and uses advised against

| | |
|---|---|
| **Relevant identified uses** | Adhesive. |

### Details of the manufacturer or importer of the safety data sheet

| | |
|---|---|
| **Registered company name** | **Vishay Measurements Group, Inc.** |
| **Address** | 951 Wendell Boulevard NC 27591 United States |
| **Telephone** | 9193745789 |
| **Fax** | Not Available |
| **Website** | www.VPGSensors.com |
| **Email** | mm.us@vpgsensors.com |

### Emergency telephone number

| | |
|---|---|
| **Association / Organisation** | **Velocity EHS** |
| **Emergency telephone number(s)** | 1-813-248-0585 |
| **Other emergency telephone number(s)** | Not Available |

## SECTION 2 Hazards identification

### Classification of the substance or mixture

| | |
|---|---|
| **Classification** | Flammable Liquids Category 2, Acute Toxicity (Oral) Category 5, Acute Toxicity (Dermal) Category 4, Skin Corrosion/Irritation Category 3, Sensitisation (Skin) Category 1, Serious Eye Damage/Eye Irritation Category 2A, Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, Specific Target Organ Toxicity - Single Exposure (Narcotic Effects) Category 3, Carcinogenicity Category 2, Hazardous to the Aquatic Environment Long-Term Hazard Category 2 |

### Label elements

| | |
|---|---|
| **Hazard pictogram(s)** | |
| **Signal word** | **Danger** |

### Hazard statement(s)

**Page 1 continued...**

| | |
|---|---|
| **H225** | Highly flammable liquid and vapour. |
| **H303** | May be harmful if swallowed. |
| **H312** | Harmful in contact with skin. |
| **H316** | Causes mild skin irritation. |
| **H317** | May cause an allergic skin reaction. |
| **H319** | Causes serious eye irritation. |
| **H335** | May cause respiratory irritation. |
| **H336** | May cause drowsiness or dizziness. |
| **H351** | Suspected of causing cancer. |
| **H411** | Toxic to aquatic life with long lasting effects. |

**Precautionary statement(s) Prevention**

| | |
|---|---|
| **P210** | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| **P271** | Use only a well-ventilated area. |
| **P280** | Wear protective gloves, protective clothing, eye protection and face protection. |
| **P240** | Ground and bond container and receiving equipment. |
| **P241** | Use explosion-proof electrical/ventilating/lighting/intrinsically safe equipment. |
| **P242** | Use non-sparking tools. |
| **P243** | Take action to prevent static discharges. |
| **P261** | Avoid breathing mist/vapours/spray. |
| **P273** | Avoid release to the environment. |
| **P202** | Do not handle until all safety precautions have been read and understood. |
| **P264** | Wash all exposed external body areas thoroughly after handling. |
| **P272** | Contaminated work clothing should not be allowed out of the workplace. |

**Precautionary statement(s) Response**

| | |
|---|---|
| **P301+P312** | IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider if you feel unwell. |
| **P308+P313** | IF exposed or concerned: Get medical advice/ attention. |
| **P370+P378** | In case of fire: Use alcohol resistant foam or normal protein foam to extinguish. |
| **P302+P352** | IF ON SKIN: Wash with plenty of water. |
| **P305+P351+P338** | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| **P333+P313** | If skin irritation or rash occurs: Get medical advice/attention. |
| **P337+P313** | If eye irritation persists: Get medical advice/attention. |
| **P362+P364** | Take off contaminated clothing and wash it before reuse. |
| **P391** | Collect spillage. |
| **P303+P361+P353** | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. |
| **P304+P340** | IF INHALED: Remove person to fresh air and keep comfortable for breathing. |

**Precautionary statement(s) Storage**

| | |
|---|---|
| **P403+P235** | Store in a well-ventilated place. Keep cool. |
| **P405** | Store locked up. |

**Precautionary statement(s) Disposal**

| | |
|---|---|
| **P501** | Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation. |

No further product hazard information.

## SECTION 3 Composition / information on ingredients

**Substances**

See section below for composition of Mixtures

**Mixtures**

| CAS No | %[weight] | Name |
|---|---|---|
| 109-99-9 | 45-55 | tetrahydrofuran |
| 28064-14-4 | 30-40 | bisphenol F diglycidyl ether copolymer |
| 78-93-3 | 12-18 | methyl ethyl ketone |

## SECTION 4 First aid measures

**Description of first aid measures**

| | |
|---|---|
| **Eye Contact** | If this product comes in contact with the eyes:<br>‣ Wash out immediately with fresh running water. |

**Continued...**

| | |
|---|---|
| | ▸ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.<br>▸ Seek medical attention without delay; if pain persists or recurs seek medical attention.<br>▸ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. |
| **Skin Contact** | If skin contact occurs:<br>▸ Immediately remove all contaminated clothing, including footwear.<br>▸ Flush skin and hair with running water (and soap if available).<br>▸ Seek medical attention in event of irritation. |
| **Inhalation** | ▸ If fumes or combustion products are inhaled remove from contaminated area.<br>▸ Lay patient down. Keep warm and rested.<br>▸ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.<br>▸ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.<br>▸ Transport to hospital, or doctor. |
| **Ingestion** | ▸ Immediately give a glass of water.<br>▸ First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor. |

**Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

## SECTION 5 Firefighting measures

**Extinguishing media**

- Alcohol stable foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog - Large fires only.

**Special hazards arising from the substance or mixture**

| | |
|---|---|
| **Fire Incompatibility** | ▸ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result |

**Advice for firefighters**

| | |
|---|---|
| **Fire Fighting** | |
| **Fire/Explosion Hazard** | ▸ Liquid and vapour are highly flammable.<br>▸ Severe fire hazard when exposed to heat, flame and/or oxidisers.<br>▸ Vapour may travel a considerable distance to source of ignition.<br>▸ Heating may cause expansion or decomposition leading to violent rupture of containers.<br>▸ On combustion, may emit toxic fumes of carbon monoxide (CO).<br>Combustion products include:<br>,<br>▸ carbon dioxide ($CO_2$)<br>,<br>aldehydes<br>,<br>▸ other pyrolysis products typical of burning organic material.<br>**WARNING**: Long standing in contact with air and light may result in the formation of potentially explosive peroxides. |

## SECTION 6 Accidental release measures

**Personal precautions, protective equipment and emergency procedures**

See section 8

**Environmental precautions**

See section 12

**Methods and material for containment and cleaning up**

| | |
|---|---|
| **Minor Spills** | ▸ Remove all ignition sources.<br>▸ Clean up all spills immediately.<br>▸ Avoid breathing vapours and contact with skin and eyes.<br>▸ Control personal contact with the substance, by using protective equipment.<br>▸ Contain and absorb small quantities with vermiculite or other absorbent material.<br>▸ Wipe up.<br>▸ Collect residues in a flammable waste container.<br>▸ In the event of a spill of a reactive diluent, the focus is on containing the spill to prevent contamination of soil and surface or ground water.<br>▸ If irritating vapors are present, an approved air-purifying respirator with organic vapor canister is recommended for cleaning up spills and leaks.<br>▸ For small spills, reactive diluents should be absorbed with sand. |
| **Major Spills** | ▸ Clear area of personnel and move upwind.<br>▸ Alert Fire Brigade and tell them location and nature of hazard.<br>▸ Wear breathing apparatus plus protective gloves.<br>▸ Prevent, by any means available, spillage from entering drains or water course.<br>▸ Stop leak if safe to do so.<br>▸ Contain spill with sand, earth or vermiculite.<br>▸ Collect recoverable product into labelled containers for recycling.<br>▸ Neutralise/decontaminate residue (see Section 13 for specific agent).<br>▸ Collect solid residues and seal in labelled drums for disposal.<br>▸ Wash area and prevent runoff into drains.<br>▸ After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using. |

**Continued...**

| | |
|---|---|
| | ▸ If contamination of drains or waterways occurs, advise emergency services.<br>Industrial spills or releases of reactive diluents are infrequent and generally contained. If a large spill does occur, the material should be captured, collected, and reprocessed or disposed of according to applicable governmental requirements.<br>An approved air-purifying respirator with organic-vapor canister is recommended for emergency work. |

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## SECTION 7 Handling and storage

### Precautions for safe handling

| | |
|---|---|
| **Safe handling** | ▸ Containers, even those that have been emptied, may contain explosive vapours.<br>▸ Do NOT cut, drill, grind, weld or perform similar operations on or near containers.<br>The substance accumulates peroxides which may become hazardous only if it evaporates or is distilled or otherwise treated to concentrate the peroxides. The substance may concentrate around the container opening for example.<br>Purchases of peroxidisable chemicals should be restricted to ensure that the chemical is used completely before it can become peroxidised.<br>▸ A responsible person should maintain an inventory of peroxidisable chemicals or annotate the general chemical inventory to indicate which chemicals are subject to peroxidation. An expiration date should be determined. The chemical should either be treated to remove peroxides or disposed of before this date.<br>▸ The person or laboratory receiving the chemical should record a receipt date on the bottle. The individual opening the container should add an opening date.<br>▸ Unopened containers received from the supplier should be safe to store for 18 months.<br>▸ Opened containers should not be stored for more than 12 months.<br>▸ Avoid skin contact, including inhalation.<br>▸ Wear protective clothing when risk of exposure occurs.<br>▸ Use in a well-ventilated area.<br>▸ Prevent concentration in hollows and sumps.<br>▸ **DO NOT** enter confined spaces until atmosphere has been checked.<br>▸ Avoid smoking, naked lights, heat or ignition sources.<br>▸ When handling, **DO NOT** eat, drink or smoke.<br>▸ Vapour may ignite on pumping or pouring due to static electricity.<br>▸ **DO NOT** use plastic buckets.<br>▸ Earth and secure metal containers when dispensing or pouring product.<br>▸ Use spark-free tools when handling.<br>▸ Avoid contact with incompatible materials.<br>▸ Keep containers securely sealed.<br>▸ Avoid physical damage to containers.<br>▸ Always wash hands with soap and water after handling.<br>▸ Work clothes should be laundered separately.<br>▸ Use good occupational work practice.<br>▸ Observe manufacturer's storage and handling recommendations contained within this SDS.<br>▸ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.<br>▸ **DO NOT** allow clothing wet with material to stay in contact with skin |
| **Other information** | ▸ Store in original containers in approved flame-proof area.<br>▸ No smoking, naked lights, heat or ignition sources.<br>▸ **DO NOT** store in pits, depression, basement or areas where vapours may be trapped.<br>▸ Keep containers securely sealed.<br>▸ Store away from incompatible materials in a cool, dry well ventilated area.<br>▸ Protect containers against physical damage and check regularly for leaks.<br>▸ Observe manufacturer's storage and handling recommendations contained within this SDS.<br>▸ Tank storage: Tanks must be specifically designed for use with this product. Bulk storage tanks should be diked (bunded). Locate tanks away from heat and other sources of ignition. Cleaning, inspection and maintenance of storage tanks is a specialist operation, which requires the implementation of strict procedures and precautions.<br>▸ Keep in a cool place. Electrostatic charges will be generated during pumping. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk. The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable.<br>▸ For containers, or container linings use mild steel, stainless steel. Examples of suitable materials are: high density polyethylene (HDPE), polypropylene (PP), and Viton (FMK), which have been specifically tested for compatibility with this product.<br>▸ For container linings, use amine-adduct cured epoxy paint.<br>▸ For seals and gaskets use: graphite, PTFE, Viton A, Viton B.<br>▸ Unsuitable material: Some synthetic materials may be unsuitable for containers or container linings depending on the material specification and intended use. Examples of materials to avoid are: natural rubber (NR), nitrile rubber (NBR), ethylene propylene rubber (EPDM), polymethyl methacrylate (PMMA), polystyrene, polyvinyl chloride (PVC), polyisobutylene. However, some may be suitable for glove materials.<br>▸ Do not cut, drill, grind, weld or perform similar operations on or near containers. Containers, even those that have been emptied, can contain explosive vapours. |

### Conditions for safe storage, including any incompatibilities

| | |
|---|---|
| **Suitable container** | ▸ Packing as supplied by manufacturer.<br>▸ Plastic containers may only be used if approved for flammable liquid.<br>▸ Check that containers are clearly labelled and free from leaks.<br>▸ For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.<br>▸ For materials with a viscosity of at least 2680 cSt. (23 deg. C)<br>▸ For manufactured product having a viscosity of at least 250 cSt. (23 deg. C)<br>▸ Manufactured product that requires stirring before use and having a viscosity of at least 20 cSt (25 deg. C): (i) Removable head packaging; (ii) Cans with friction closures and (iii) low pressure tubes and cartridges may be used.<br>▸ Where combination packages are used, and the inner packages are of glass, there must be sufficient inert cushioning material in contact with inner and outer packages<br>▸ In addition, where inner packagings are glass and contain liquids of packing group I there must be sufficient inert absorbent to absorb any spillage, unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic. |
| **Storage incompatibility** | Methyl ethyl ketone:<br>▸ reacts violently with strong oxidisers, aldehydes, nitric acid, perchloric acid, potassium tert-butoxide, oleum<br>▸ is incompatible with inorganic acids, aliphatic amines, ammonia, caustics, isocyanates, pyridines, chlorosulfonic aid<br>▸ forms unstable peroxides in storage, or on contact with propanol or hydrogen peroxide<br>▸ attacks some plastics<br>▸ may generate electrostatic charges, due to low conductivity, on flow or agitation |

**Continued...**

For tetrahydrofuran (THF)
- Avoid contact with oxygen, air, light and heat
- Contact with lithium aluminium hydride or with sodium or potassium hydroxide can be hazardous when peroxides are present. THF may polymerise in the presence of cationic initiators such as Lewis acids or strong proton acids.
- Segregate from lithium aluminium hydride, sodium or potassium hydroxide, cationic initiators such as Lewis acids or strong proton acids.
- In the absence of inhibitors tetrahydrofuran is subject to auto-oxidation with the formation of 2-tetrahydrofuryl hydroperoxide . When heated this tends to decompose smoothly but if allowed to accumulate over a considerable period it transforms to other peroxidic species, such as unstable and explosive polyalkylidene peroxide, which violently decompose.
- Copper(I) chloride has been recommended to remove trace amounts of peroxide. An attempt to remove peroxides by shaking with solid ferrous sulfate, prior to distillation, did not prevent explosion of the distillation residue. Alkali treatment does not appear to be safe.
- Peroxides may be destroyed by passage through activated carbon at 20-66 C with contact time in excess of 2 min.
- is incompatible with borane, calcium hydride, lithium tetrahydroaluminate, sodium aluminium tetrahydride
- reacts violently with strong oxidisers, bromine, oxygen, magnesium tetrahydroaluminate, metal halides, peroxyacetic acid, potassium hydride
- attacks some plastics and coatings
- may accumulate static charges that can result in ignition of its vapours

Storage tanks and other equipment should be absolutely dry and free from air, ammonia, acetylene, hydrogen sulfide, rust and other contaminants.
Epoxides:
- are highly reactive with acids, bases, and oxidising and reducing agents.
- react, possibly violently, with anhydrous metal chlorides, ammonia, amines and group 1 metals.
- may polymerise in the presence of peroxides or heat - polymerisation may be violent
- may react, possibly violently, with water in the presence of acids and other catalysts.
- Phenols are incompatible with strong reducing substances such as hydrides, nitrides, alkali metals, and sulfides.
- Avoid use of aluminium, copper and brass alloys in storage and process equipment.
- Heat is generated by the acid-base reaction between phenols and bases.
- Phenols are sulfonated very readily (for example, by concentrated sulfuric acid at room temperature), these reactions generate heat.
- Phenols are nitrated very rapidly, even by dilute nitric acid.
- Nitrated phenols often explode when heated. Many of them form metal salts that tend toward detonation by rather mild shock.
- Avoid strong acids, bases.
- The unhindered oxygen atom found on cyclic ethers such as the epoxides, oxetanes, furans, dioxanes and pyrans, carries two unshared pairs of electrons - a structure which favors the formation of coordination complexes and the solvation of cations.
- Cyclic ethers are used as important solvents, as chemical intermediate and as monomers for ring-opening polymerization.
- They are unstable at room temperature due to possibility of peroxide formation; stabiliser is sometimes needed for storage and transportation.

NOTE: Ethers lacking non-methyl hydrogen atoms adjacent to the ether link are thought to be relatively safe
Glycidyl ethers:
- may form unstable peroxides on storage in air ,light, sunlight, UV light or other ionising radiation, trace metals - inhibitor should be maintained at adequate levels
- may polymerise in contact with heat, organic and inorganic free radical producing initiators
- may polymerise with evolution of heat in contact with oxidisers, strong acids, bases and amines
- react violently with strong oxidisers, permanganates, peroxides, acyl halides, alkalis, ammonium persulfate, bromine dioxide
- attack some forms of plastics, coatings, and rubber

Reactive diluents are stable under recommended storage conditions, but can decompose at elevated temperatures.In some cases, decomposition can cause pressure build-up in closed systems.
- Avoid cross contamination between the two liquid parts of product (kit).
- If two part products are mixed or allowed to mix in proportions other than manufacturer's recommendation, polymerisation with gelation and evolution of heat (exotherm) may occur.
- This excess heat may generate toxic vapour
- Avoid reaction with amines, mercaptans, strong acids and oxidising agents

## SECTION 8 Exposure controls / personal protection

### Control parameters

**Occupational Exposure Limits (OEL)**

**INGREDIENT DATA**

| Source | Ingredient | Material name | TWA | STEL | Peak | Notes |
|---|---|---|---|---|---|---|
| India Permissible Levels of Certain Chemical Substances in Work Environment | methyl ethyl ketone | 2-Butanone (Metyl ethyl Ketone-MEK) | 200 ppm / 590 mg/m3 | 885 mg/m3 / 300 ppm | Not Available | Not Available |

### Exposure controls

**Appropriate engineering controls**

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.
The basic types of engineering controls are:
Process controls which involve changing the way a job activity or process is done to reduce the risk.
Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.
Employers may need to use multiple types of controls to prevent employee overexposure.
For flammable liquids and flammable gases, local exhaust ventilation or a process enclosure ventilation system may be required. Ventilation equipment should be explosion-resistant.
Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

| Type of Contaminant: | Air Speed: |
|---|---|
| solvent, vapours, degreasing etc., evaporating from tank (in still air). | 0.25-0.5 m/s (50-100 f/min.) |
| aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) | 0.5-1 m/s (100-200 f/min.) |

**Continued...**

| | |
|---|---|
| | direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion) — 1-2.5 m/s (200-500 f/min.) |

Within each range the appropriate value depends on:

| Lower end of the range | Upper end of the range |
|---|---|
| 1: Room air currents minimal or favourable to capture | 1: Disturbing room air currents |
| 2: Contaminants of low toxicity or of nuisance value only. | 2: Contaminants of high toxicity |
| 3: Intermittent, low production. | 3: High production, heavy use |
| 4: Large hood or large air mass in motion | 4: Small hood-local control only |

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.
· Adequate ventilation is typically taken to be that which limits the average concentration to no more than 25% of the LEL within the building, room or enclosure containing the dangerous substance.
· Ventilation for plant and machinery is normally considered adequate if it limits the average concentration of any dangerous substance that might potentially be present to no more than 25% of the LEL. However, an increase up to a maximum 50% LEL can be acceptable where additional safeguards are provided to prevent the formation of a hazardous explosive atmosphere. For example, gas detectors linked to emergency shutdown of the process might be used together with maintaining or increasing the exhaust ventilation on solvent evaporating ovens and gas turbine enclosures.
· Temporary exhaust ventilation systems may be provided for non-routine higher-risk activities, such as cleaning, repair or maintenance in tanks or other confined spaces or in an emergency after a release. The work procedures for such activities should be carefully considered.. The atmosphere should be continuously monitored to ensure that ventilation is adequate and the area remains safe. Where workers will enter the space, the ventilation should ensure that the concentration of the dangerous substance does not exceed 10% of the LEL (irrespective of the provision of suitable breathing apparatus)

**Individual protection measures, such as personal protective equipment**

**Eye and face protection**

- Safety glasses with side shields.
- Chemical goggles.[AS/NZS 1337.1, EN166 or national equivalent]
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

**Skin protection**

See Hand protection below

**Hands/feet protection**

**NOTE:**
- The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.
- Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.
Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.
Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:
· frequency and duration of contact,
· chemical resistance of glove material,
· glove thickness and
· dexterity
Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).
· When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
· When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
· Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.
· Contaminated gloves should be replaced.
As defined in ASTM F-739-96 in any application, gloves are rated as:
· Excellent when breakthrough time > 480 min
· Good when breakthrough time > 20 min
· Fair when breakthrough time < 20 min
· Poor when glove material degrades
For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.
It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.
Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task.
Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:
· Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.
· Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential
Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

**Continued...**

| | |
|---|---|
| | When handling liquid-grade epoxy resins wear chemically protective gloves , boots and aprons.<br>The performance, based on breakthrough times ,of:<br>· Ethyl Vinyl Alcohol (EVAL laminate) is generally excellent<br>· Butyl Rubber ranges from excellent to good<br>· Nitrile Butyl Rubber (NBR) from excellent to fair.<br>· Neoprene from excellent to fair<br>· Polyvinyl (PVC) from excellent to poor<br>As defined in ASTM F-739-96<br>· Excellent breakthrough time > 480 min<br>· Good breakthrough time > 20 min<br>· Fair breakthrough time < 20 min<br>· Poor glove material degradation<br>Gloves should be tested against each resin system prior to making a selection of the most suitable type. Systems include both the resin and any hardener, individually and collectively)<br>· **DO NOT** use cotton or leather (which absorb and concentrate the resin), natural rubber (latex), medical or polyethylene gloves (which absorb the resin).<br>· **DO NOT** use barrier creams containing emulsified fats and oils as these may absorb the resin; silicone-based barrier creams should be reviewed prior to use.<br>Replacement time should be considered when selecting the most appropriate glove. It may be more effective to select a glove with lower chemical resistance but which is replaced frequently than to select a more resistant glove which is reused many times |
| **Body protection** | See Other protection below |
| **Other protection** | ‣ Overalls.<br>‣ PVC Apron.<br>‣ PVC protective suit may be required if exposure severe.<br>‣ Eyewash unit.<br>‣ Ensure there is ready access to a safety shower.<br>‣ Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity.<br>‣ For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets).<br>‣ Non sparking safety or conductive footwear should be considered. Conductive footwear describes a boot or shoe with a sole made from a conductive compound chemically bound to the bottom components, for permanent control to electrically ground the foot an shall dissipate static electricity from the body to reduce the possibility of ignition of volatile compounds. Electrical resistance must range between 0 to 500,000 ohms. Conductive shoes should be stored in lockers close to the room in which they are worn. Personnel who have been issued conductive footwear should not wear them from their place of work to their homes and return. |

### Recommended material(s)

**GLOVE SELECTION INDEX**

Glove selection is based on a modified presentation of the:
**"Forsberg Clothing Performance Index".**
The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:
M-Bond 600 Adhesive

| Material | CPI |
|---|---|
| PE/EVAL/PE | A |
| PVA | B |
| TEFLON | B |
| BUTYL | C |
| BUTYL/NEOPRENE | C |
| CPE | C |
| HYPALON | C |
| NATURAL RUBBER | C |
| NATURAL+NEOPRENE | C |
| NEOPRENE | C |
| NEOPRENE/NATURAL | C |
| NITRILE | C |
| NITRILE+PVC | C |
| PVC | C |
| SARANEX-23 | C |
| VITON/CHLOROBUTYL | C |
| VITON/NEOPRENE | C |

* CPI - Chemwatch Performance Index
A: Best Selection
B: Satisfactory; may degrade after 4 hours continuous immersion
C: Poor to Dangerous Choice for other than short term immersion
**NOTE**: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -
* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

**Ansell Glove Selection**

| **Glove** — In order of recommendation |
|---|
| AlphaTec 02-100 |
| AlphaTec® 15-554 |

### Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

If the amount of gas or particles in the air where you're breathing gets close to or goes over the safe limit, you need to wear a mask or respirator. The level of protection you get depends on the type of mask and filter you use. Here's a simple guide to what kind of mask you need based on how much the gas or particles exceed the safe limit: - If it's up to 5 times the safe limit, you can use a half-face mask with a basic filter or a powered air respirator. - If it's up to 25 times the safe limit, you should use an air-line mask or a full-face mask with a stronger filter. - If it's up to 50 times the safe limit, a full-face mask with an even stronger filter is needed. - If it's more than 50 times the safe limit, you need an air-line mask with continuous airflow. Different filters protect against different things, like organic vapors, acid gases, sulfur dioxide, agricultural chemicals, ammonia, mercury, nitrogen oxides, methyl bromide, and low boiling point organic compounds.

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

**Continued...**

| |
|---|
| AlphaTec® 53-001 |
| AlphaTec® 58-005 |
| MICROFLEX® MidKnight® XTRA 93-862 |
| MICROFLEX® LifeStar EC™ 93-868 |
| MICROFLEX® SafeGrip™ SG-375 |
| AlphaTec® 38-612 |
| AlphaTec® Solvex® 37-175 |
| BioClean™ Emerald BENS |

The suggested gloves for use should be confirmed with the glove supplier.

## SECTION 9 Physical and chemical properties

### Information on basic physical and chemical properties

| | |
|---|---|
| **Appearance** | Almost colourless liquid |

| | | | |
|---|---|---|---|
| **Physical state** | Liquid | **Relative density (Water = 1)** | Not Available |
| **Odour** | Pungent | **Partition coefficient n-octanol / water** | Not Available |
| **Odour threshold** | Not Available | **Auto-ignition temperature (℃)** | Not Available |
| **pH (as supplied)** | Not Available | **Decomposition temperature (℃)** | Not Available |
| **Melting point / freezing point (℃)** | Not Available | **Viscosity (mm2/s)** | Not Available |
| **Initial boiling point and boiling range (℃)** | 66 | **Molecular weight (g/mol)** | Not Available |
| **Flash point (℃)** | -14 | **Taste** | Not Available |
| **Evaporation rate** | 8 BuAC = 1 | **Explosive properties** | Not Available |
| **Flammability** | HIGHLY FLAMMABLE. | **Oxidising properties** | Not Available |
| **Upper Explosive Limit (%)** | Not Available | **Surface Tension (dyn/cm or mN/m)** | Not Available |
| **Lower Explosive Limit (%)** | Not Available | **Volatile Component (%vol)** | Not Available |
| **Vapour pressure (kPa)** | 129 | **Gas group** | Not Available |
| **Solubility in water** | Miscible | **pH as a solution (1%)** | Not Available |
| **Vapour density (Air = 1)** | 2.4 | **VOC g/L** | 598 |
| **Heat of Combustion (kJ/g)** | Not Available | **Ignition Distance (cm)** | Not Available |
| **Flame Height (cm)** | Not Available | **Flame Duration (s)** | Not Available |
| **Enclosed Space Ignition Time Equivalent (s/m3)** | Not Available | **Enclosed Space Ignition Deflagration Density (g/m3)** | Not Available |

## SECTION 10 Stability and reactivity

| | |
|---|---|
| **Reactivity** | See section 7 |
| **Chemical stability** | Presence of a stabilising inhibitor prevents/retards peroxide formation.<br>‣ Unstable in the presence of incompatible materials.<br>‣ Product is considered stable.<br>‣ Hazardous polymerisation will not occur. |
| **Possibility of hazardous reactions** | See section 7 |
| **Conditions to avoid** | See section 7 |
| **Incompatible materials** | See section 7 |
| **Hazardous decomposition products** | See section 5 |

## SECTION 11 Toxicological information

### Information on toxicological effects

| | |
|---|---|
| **a) Acute Toxicity** | There is sufficient evidence to classify this material as acutely toxic. |
| **b) Skin Irritation/Corrosion** | There is sufficient evidence to classify this material as skin corrosive or irritating. |
| **c) Serious Eye Damage/Irritation** | There is sufficient evidence to classify this material as eye damaging or irritating |
| **d) Respiratory or Skin sensitisation** | There is sufficient evidence to classify this material as sensitising to skin or the respiratory system |
| **e) Mutagenicity** | Based on available data, the classification criteria are not met. |
| **f) Carcinogenicity** | There is sufficient evidence to classify this material as carcinogenic |
| **g) Reproductivity** | Based on available data, the classification criteria are not met. |
| **h) STOT - Single Exposure** | There is sufficient evidence to classify this material as toxic to specific organs through single exposure |

**Continued...**

| | |
|---|---|
| **i) STOT - Repeated Exposure** | Based on available data, the classification criteria are not met. |
| **j) Aspiration Hazard** | Based on available data, the classification criteria are not met. |

| | |
|---|---|
| **Inhaled** | Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful.<br>The material is not classified as causing respiratory irritation under Regulation (EC) No 1272/2008 (CLP), as amended. Nevertheless, inhalation of vapours, fumes or aerosols, particularly following prolonged exposure, may cause respiratory discomfort and, occasionally, respiratory distress.<br>In animal testing, exposure to aerosols of reactive diluents (especially o-cresol glycidyl ether, CAS RN:2210-79-9) has been reported to affect the adrenal gland, central nervous system, kidney, liver, ovaries, spleen, testes, thymus and respiratory tract.<br>Inhalation hazard is increased at higher temperatures.<br>Overexposure to tetrahydrofuran by inhalation may result in irritation of the mucous membrane, and may produce coughing, chest pains, nausea, dizziness, headache and stupor. High concentrations affect the central nervous system.<br>Acute exposure of humans to high concentrations of methyl ethyl ketone produces irritation to the eyes, nose and throat. Acute exposure by inhalation also causes nervous system depression, headache, and nausea. High vapour levels are easily detected due to odour, however odour fatigue may occur, with loss of warning of exposure. |
| **Ingestion** | The material is not classified for acute toxicity via the oral route under Regulation (EC) No 1272/2008 (CLP), as amended. Nevertheless, adverse systemic effects have been identified following exposure of animals by at least one other route. Good hygiene practice requires that exposure be kept to a minimum.<br>Reactive diluents exhibit a range of ingestion hazards. Small amounts swallowed incidental to normal handling operations are not likely to cause injury. However, swallowing larger amounts may cause injury.<br>High molecular weight material; on single acute exposure would be expected to pass through gastrointestinal tract with little change / absorption. Occasionally accumulation of the solid material within the alimentary tract may result in formation of a bezoar (concretion), producing discomfort.<br>Ingestion of tetrahydrofuran may not, in itself, produce internal injury, however, contaminating levels of furan, present in certain grades of commercial product, may produce liver and kidney injury exacerbated by the intake of alcoholic beverages.<br>Accidental ingestion of the material may be damaging to the health of the individual. |
| **Skin Contact** | Skin contact with the material may be harmful; systemic effects may result following absorption.<br>In humans exposed to methyl ethyl ketone, skin inflammation has been reported. Animal testing has shown methyl ethyl ketone to have high acute toxicity from skin exposure.<br>Skin contact with reactive diluents may cause slight to moderate irritation with local redness. Repeated or prolonged skin contact may cause burns.<br>Open cuts, abraded or irritated skin should not be exposed to this material<br>Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.<br>Skin contact with tetrahydrofuran may produce smarting and reddening of the skin and after prolonged exposures; skin inflammation may result because the substance removes skin oils (has a degreasing effect).<br>The material may cause severe inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering. |
| **Eye** | Eye contact with reactive diluents may cause slight to severe irritation with the possibility of chemical burns or moderate to severe damage to the cornea.<br>There is evidence that material may produce eye irritation in some persons and produce eye damage 24 hours or more after instillation. Severe inflammation may be expected with pain.<br>Application of a 20% solution of tetrahydrofuran in water in animals to the eye, produced irritation. |
| **Chronic** | Repeated or long-term occupational exposure is likely to produce cumulative health effects involving organs or biochemical systems.<br>There has been concern that this material can cause cancer or mutations, but there is not enough data to make an assessment.<br>Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population.<br>Toxic: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.<br>This material can cause serious damage if one is exposed to it for long periods. It can be assumed that it contains a substance which can produce severe defects.<br>Ample evidence from experiments exists that there is a suspicion this material directly reduces fertility.<br>This product contains a polymer with reactive functional groups (aldehydes and phenolics) regarded as being of moderate concern.<br>Aldehydes are reactive, soluble and are highly irritating.<br>Glycidyl ethers can cause genetic damage and cancer.<br>This material contains a substantial amount of polymer considered to be of low concern. These are classified under having MWs of between 1000 to 10000 with less than 25% of molecules with MWs under 1000 and less than 10% under 500; or having a molecular weight average of over 10000.<br>For some reactive diluents, prolonged or repeated skin contact may result in absorption of potentially harmful amounts or allergic skin reactions.<br>Exposure to some reactive diluents (notably, neopentylglycol diglycidyl ether, CAS RN: 17557-23-2) has caused cancer in some animal testing.<br>Cyclic ethers can cause cancers, especially of the liver.<br>Animal testing shows that methyl ethyl ketone may have slight effects on the nervous system, liver, kidney and respiratory system; there may also be developmental effects and an increase in birth defects. However, there is limited information available on the long-term effects of methyl ethyl ketone in humans, and no information is available on whether it causes developmental or reproductive toxicity or cancer. It is generally considered to have low toxicity, but it is often used in combination with other solvents, and the toxic effects of the mixture may be greater than with either solvent alone. Combinations of n-hexane or methyl n-butyl ketone with methyl ethyl ketone may increase the rate of peripheral neuropathy, a progressive disorder of the nerves of the extremities. Combinations with chloroform also show increase in toxicity.<br>Bisphenol F, bisphenol A, fluorine-containing bisphenol A (bisphenol AF) and other diphenylalkanes were found to have oestrogen-like effects. Bisphenol F is present in the environment and as a contaminant of food, so humans may therefore be exposed to bisphenol. Testing shows bisphenol F has genetic toxicity as well as the ability to disrupt hormonal balance.<br>Bisphenol A may have effects similar to female sex hormones and when administered to pregnant women, may damage the foetus. It may also damage male reproductive organs and sperm.<br>Repeated exposure to tetrahydrofuran (THF) and related compounds has been associated with liver inflammation and fatty degeneration of the liver. Animal testing suggests that this group of compounds can cause liver damage, irritation of the skin and airway, metabolic imbalance, gynaecological disturbance, damage to the adrenal glands and may increase the rate of cancer. |

| | | |
|---|---|---|
| **M-Bond 600 Adhesive** | **TOXICITY** | **IRRITATION** |
| | Not Available | Not Available |
| **tetrahydrofuran** | **TOXICITY** | **IRRITATION** |
| | dermal (rat) LD50: >2000 mg/kg[1] | Eye: adverse effect observed (irritating)[1] |
| | Inhalation (Rat) LC50: 45 mg/l4h[2] | Skin: no adverse effect observed (not irritating)[1] |
| | Oral (Rat) LD50: 2816 mg/kg[2] | |

**Continued...**

| | |
|---|---|
| **bisphenol F diglycidyl ether copolymer** | **TOXICITY** / **IRRITATION**<br>dermal (rat) LD50: 4000 mg/kg[2] / Not Available<br>Oral (Rat) LD50: 4000 mg/kg[2] / |
| **methyl ethyl ketone** | **TOXICITY** / **IRRITATION**<br>Dermal (rabbit) LD50: 6480 mg/kg[2] / Eye (Human): 350ppm<br>Inhalation (Mouse) LC50: 32 mg/L4h[2] / Eye (Rodent - rabbit): 80mg<br>Oral (Rat) LD50: 2054 mg/kg[1] / Eye: adverse effect observed (irritating)[1]<br>/ Skin (Rodent - rabbit): 14mg/24H - Mild<br>/ Skin (Rodent - rabbit): 402mg/24H - Mild<br>/ Skin (Rodent - rabbit): 500mg/24H - Moderate<br>/ Skin: no adverse effect observed (not irritating)[1] |
| **Legend:** | 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances |
| **M-Bond 600 Adhesive** | The various members of the bisphenol family produce hormone like effects, seemingly as a result of binding to estrogen receptor-related receptors (ERRs; not to be confused with estrogen receptors)<br>A suspected estrogen-related receptors (ERR) binding agent:<br>Estrogen-related receptors (ERR, oestrogen-related receptors) are so named because of sequence homology with estrogen receptors but do not appear to bind estrogens or other tested steroid hormones. The ERR family have been demonstrated to control energy homeostasis, oxidative metabolism and mitochondrial biogenesis ,while effecting mammalian physiology in the heart, brown adipose tissue, white adipose tissue, placenta, macrophages, and demonstrated additional roles in diabetes and cancer.<br>ERRs bind enhancers throughout the genome where they exert effects on gene regulation<br>Although their overall functions remain uncertain, they also share DNA-binding sites, co-regulators, and target genes with the conventional estrogen receptors ERalpha and ERbeta and may function to modulate estrogen signaling pathways.<br>· ERR-alpha has wide tissue distribution but it is most highly expressed in tissues that preferentially use fatty acids as energy sources such as kidney, heart, brown adipose tissue, cerebellum, intestine, and skeletal muscle. ERRalpha has been detected in normal adrenal cortex tissues, in which its expression is possibly related to adrenal development, with a possible role in fetal adrenal function, in dehydroepiandrosterone (DHEAS) production in adrenarche, and also in steroid production of post-adrenarche/adult life. DHEA and other adrenal androgens such as androstenedione, although relatively weak androgens, are responsible for the androgenic effects of adrenarche, such as early pubic and axillary hair growth, adult-type body odor, increased oiliness of hair and skin, and mild acne.<br>· ERR-beta is a nuclear receptor . Its function is unknown; however, a similar protein in mouse plays an essential role in placental development<br>· ERR-gamma is a nuclear receptor that behaves as a constitutive activator of transcription. There is evidence that bisphenol A functions as an endocrine disruptor by binding strongly to ERRgamma BPA as well as its nitrated and chlorinated metabolites seems to binds strongly to ERR-gamma (dissociation constant = 5.5 nM), but not to the estrogen receptor (ER). BPA binding to ERR-gamma preserves its basal constitutive activity.Different expression of ERR-gamma in different parts of the body may account for variations in bisphenol A effects. For instance, ERR-gamma has been found in high concentration in the placenta, explaining reports of high bisphenol A accumulation there |
| **TETRAHYDROFURAN** | Oral (human) LDLo: 50 mg/kg* [CCINFO]* Nil reported<br>The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.<br>The material may cause severe skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Repeated exposures may produce severe ulceration. |
| **METHYL ETHYL KETONE** | The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. |
| **M-Bond 600 Adhesive & BISPHENOL F DIGLYCIDYL ETHER COPOLYMER** | The following information refers to contact allergens as a group and may not be specific to this product.<br>Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.<br>The chemical structure of hydroxylated diphenylalkanes or bisphenols consists of two phenolic rings joined together through a bridging carbon. This class of endocrine disruptors that mimic oestrogens is widely used in industry, particularly in plastics.<br>Bisphenol A (BPA) and some related compounds exhibit oestrogenic activity in human breast cancer cell line MCF-7, but there were remarkable differences in activity. Several derivatives of BPA exhibited significant thyroid hormonal activity towards rat pituitary cell line GH3, which releases growth hormone in a thyroid hormone-dependent manner. However, BPA and several other derivatives did not show such activity. Results suggest that the 4-hydroxyl group of the A-phenyl ring and the B-phenyl ring of BPA derivatives are required for these hormonal activities, and substituents at the 3,5-positions of the phenyl rings and the bridging alkyl moiety markedly influence the activities. Bisphenols promoted cell proliferation and increased the synthesis and secretion of cell type-specific proteins. When ranked by proliferative potency, the longer the alkyl substituent at the bridging carbon, the lower the concentration needed for maximal cell yield; the most active compound contained two propyl chains at the bridging carbon. Bisphenols with two hydroxyl groups in the para position and an angular configuration are suitable for appropriate hydrogen bonding to the acceptor site of the oestrogen receptor.<br>In vitro cell models were used to evaluate the ability of 22 bisphenols (BPs) to induce or inhibit estrogenic and androgenic activity. BPA, Bisphenol AF (BPAF), bisphenol Z (BPZ), bisphenol C (BPC), tetramethyl bisphenol A (TMBPA), bisphenol S (BPS), bisphenol E (BPE), 4,4-bisphenol F (4,4-BPF), bisphenol AP (BPAP), bisphenol B (BPB), tetrachlorobisphenol A (TCBPA), and benzylparaben (PHBB) induced estrogen receptor (ER)alpha and/or ERbeta-mediated activity. With the exception of BPS, TCBPA, and PHBB, these same BPs were also androgen receptor (AR) antagonists. Only 3 BPs were found to be ER antagonists. Bisphenol P (BPP) selectively inhibited ERbeta-mediated activity and 4-(4-phenylmethoxyphenyl)sulfonylphenol (BPS-MPE) and 2,4-bisphenol S (2,4-BPS) selectively inhibited ERalpha-mediated activity. None of the BPs induced AR-mediated activity.<br>Oxiranes (including glycidyl ethers and alkyl oxides, and epoxides) share many common characteristics with respect to animal toxicology. One such oxirane is ethyloxirane; data presented here may be taken as representative. |
| **M-Bond 600 Adhesive & METHYL ETHYL KETONE** | Methyl ethyl ketone is considered to have a low order of toxicity; however, methyl ethyl ketone is often used in combination with other solvents and the mixture may have greater toxicity than either solvent alone. Combinations of n-hexane with methyl ethyl ketone, and also methyl n-butyl ketone with methyl ethyl ketone may result in an increased in peripheral neuropathy, a progressive disorder of the nerves of the extremities. Combinations with chloroform also show an increase in toxicity. |

**Continued...**

| | |
|---|---|
| **TETRAHYDROFURAN & METHYL ETHYL KETONE** | Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production. |

| | | | |
|---|---|---|---|
| **Acute Toxicity** | ✔ | **Carcinogenicity** | ✔ |
| **Skin Irritation/Corrosion** | ✔ | **Reproductivity** | ✘ |
| **Serious Eye Damage/Irritation** | ✔ | **STOT - Single Exposure** | ✔ |
| **Respiratory or Skin sensitisation** | ✔ | **STOT - Repeated Exposure** | ✘ |
| **Mutagenicity** | ✘ | **Aspiration Hazard** | ✘ |

**Legend:** ✘ – Data either not available or does not fill the criteria for classification
✔ – Data available to make classification

## SECTION 12 Ecological information

### Toxicity

**M-Bond 600 Adhesive**

| Endpoint | Test Duration (hr) | Species | Value | Source |
|---|---|---|---|---|
| Not Available | Not Available | Not Available | Not Available | Not Available |

**tetrahydrofuran**

| Endpoint | Test Duration (hr) | Species | Value | Source |
|---|---|---|---|---|
| NOEC(ECx) | 24h | Fish | >=5mg/l | 1 |
| LC50 | 96h | Fish | 1970-2360mg/L | 4 |

**bisphenol F diglycidyl ether copolymer**

| Endpoint | Test Duration (hr) | Species | Value | Source |
|---|---|---|---|---|
| Not Available | Not Available | Not Available | Not Available | Not Available |

**methyl ethyl ketone**

| Endpoint | Test Duration (hr) | Species | Value | Source |
|---|---|---|---|---|
| EC50 | 72h | Algae or other aquatic plants | 1220mg/l | 2 |
| EC50 | 48h | Crustacea | 308mg/l | 2 |
| EC50 | 96h | Algae or other aquatic plants | >500mg/L | 4 |
| LC50 | 96h | Fish | >324mg/L | 4 |
| NOEC(ECx) | 48h | Crustacea | 68mg/l | 2 |

**Legend:** Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. US EPA, Ecotox database - Aquatic Toxicity Data 4. ECETOC Aquatic Hazard Assessment Data 5. NITE (Japan) - Bioconcentration Data 6. METI (Japan) - Bioconcentration Data 7. Vendor Data 8. User defined data

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.
Wastes resulting from use of the product must be disposed of on site or at approved waste sites.
For high molecular weight synthetic polymers: (according to the Sustainable Futures (SF) program (U.S. EPA 2005b; U.S. EPA 2012c) polymer assessment guidance.)
High MW polymers are expected:
· to have low vapour pressure and are not expected to undergo volatilization .
· to adsorb strongly to soil and sediment
· to be non-biodegradable (not anticipated to be assimilated by microorganisms.- therefore, biodegradation is not expected to be an important removal process. However many exceptions exist
High MW polymers are not expected to undergo removal by other degradative processes under environmental conditions
For bisphenol A and related bisphenols:
Environmental fate:
Biodegradability (28 d) 89% - Easily biodegradable
Bioconcentration factor (BCF) 7.8 mg/l
Bisphenol A, its derivatives and analogues, can be released from polymers, resins and certain substances by metabolic products
Substance does not meet the criteria for PBT or vPvB according to Regulation (EC) No 1907/2006, Annex XIII
As an environmental contaminant, bisphenol A interferes with nitrogen fixation at the roots of leguminous plants associated with the bacterial symbiont Sinorhizobium meliloti.
Despite a half-life in the soil of only 1-10 days, its ubiquity makes it an important pollutant. According to Environment Canada, "initial assessment shows that at low levels, bisphenol A can harm fish and organisms over time. Studies also indicate that it can currently be found in municipal wastewater." However, a study conducted in the United States found that 91-98% of bisphenol A may be removed from water during treatment at municipal water treatment plants.
Ecotoxicity:
Fish LC50 (96 h): 4.6 mg/l (freshwater fish); 11 mg/l (saltwater fish): NOEC 0.016 mg/l (freshwater fish- 144 d); 0.064 mg/l (saltwater fish 164 d)
Fresh water invertebrates EC50 (48 h): 10.2 mg/l: NOEC 0.025 mg/l - 328 d)
Marine water invertebrate EC50 (96 h): 1.1 mg/l; NOEC 0.17 mg/l (28 d)
Freshwater algae (96 h): 2.73 mg/l
Marine water algae (96 h): 1.1 mg/l
Fresh water plant EC50 (7 d): 20 mg/l: NOEC 7.8 mg/l
In general, studies have shown that bisphenol A can affect growth, reproduction and development in aquatic organisms.
Among freshwater organisms, fish appear to be the most sensitive species. Evidence of endocrine-related effects in fish, aquatic invertebrates, amphibians and reptiles has been reported at environmentally relevant exposure levels lower than those required for acute toxicity. There is a widespread variation in reported values for endocrine-related effects, but many fall in the range of 1 ug/L to 1 mg/L
A 2009 review of the biological impacts of plasticisers on wildlife published by the Royal Society with a focus on annelids (both aquatic and terrestrial), molluscs, crustaceans, insects, fish and amphibians concluded that bisphenol A has been shown to affect reproduction in all studied animal groups, to impair development in crustaceans and

**Continued...**

amphibians and to induce genetic aberrations.
A large 2010 study of two rivers in Canada found that areas contaminated with hormone-like chemicals including bisphenol A showed females made up 85 per cent of the population of a certain fish, while females made up only 55 per cent in uncontaminated areas.
Although abundant data are available on the toxicity of bisphenol-A (2,2-bis (4-hydroxydiphenyl)propane;(BPA) A variety of BPs were examined for their acute toxicity against Daphnia magna, mutagenicity, and oestrogenic activity using the Daphtoxkit (Creasel Ltd.), the umu test system, and the yeast two-hybrid system, respectively, in comparison with BPA. BPA was moderately toxic to D. magna (48-h EC50 was 10 mg/l) according to the current U.S. EPA acute toxicity evaluation standard, and it was weakly oestrogenic with 5 orders of magnitude lower activity than that of the natural estrogen 17 beta-oestradiol in the yeast screen, while no mutagenicity was observed. All seven BPs tested here showed moderate to slight acute toxicity, no mutagenicity, and weak oestrogenic activity as well as BPA. Some of the BPs showed considerably higher oestrogenic activity than BPA, and others exhibited much lower activity. Bisphenol S (bis(4-hydroxydiphenyl)sulfone) and bis(4-hydroxyphenyl)sulfide) showed oestrogenic activity.
Biodegradation is a major mechanism for eliminating various environmental pollutants. Studies on the biodegradation of bisphenols have mainly focused on bisphenol A. A number of BPA-degrading bacteria have been isolated from enrichments of sludge from wastewater treatment plants. The first step in the biodegradation of BPA is the hydroxylation of the carbon atom of a methyl group or the quaternary carbon in the BPA molecule. Judging from these features of the biodegradation mechanisms, it is possible that the same mechanism used for BPA is used to biodegrade all bisphenols that have at least one methyl or methylene group bonded at the carbon atom between the two phenol groups. However, bisphenol F ([bis(4-hydroxyphenyl)methane; BPF), which has no substituent at the bridging carbon, is unlikely to be metabolised by such a mechanism. Nevertheless BPF is readily degraded by river water microorganisms under aerobic conditions. From this evidence, it was clear that a specific mechanism for biodegradation of BPF does exist in the natural ecosystem,
Algae can enhance the photodegradation of bisphenols. The photodegradation rate of BPF increased with increasing algae concentration. Humic acid and Fe3+ ions also enhanced the photodegradation of BPF. The effect of pH value on the BPF photodegradation was also important.
Reactive diluents generally have a low to moderate potential for bioconcentration (tendency to accumulate in the food chain) and a high to very high potential for mobility in soil. Small amounts that escape to the atmosphere will photodegrade.
They would not be expected to persist in the environment.
Most reactive diluents should be considered slightly to moderately toxic to aquatic organisms on an acute basis while some might also be considered harmful to the environment. Environmental toxicity is a function of the n-octanol/water partition coefficient (log Pow, log Kow). Compounds with log Pow >5 act as neutral organics, but at a lower log Pow, the toxicity of epoxide-containing polymers is greater than that predicted for simple narcotics.
Significant environmental findings are limited. Oxiranes (including glycidyl ethers and alkyl oxides, and epoxides) exhibit common characteristics with respect to environmental fate and ecotoxicology. One such oxirane is ethyloxirane and data presented here may be taken as representative.
For 1,2-Butylene oxide (Ethyloxirane):
log Kow values of 0.68 and 0.86. BAF and BCF : 1 to 17 L./kg.
Aquatic Fate - Ethyloxirane is highly soluble in water and has a very low soil-adsorption coefficient, which suggests that, if released to water, adsorption of ethyloxirane to sediment and suspended solids is not expected. Volatilization of ethyloxirane from water surfaces would be expected. Ethyloxirane is hydrolysable, with a half-life of 6.5 days, and biodegradable up to 100% degradation and is not expected to persist in water. Models have predicted a biodegradation half-life in water of 15 days.
Terrestrial Fate: When released to soil, ethyloxirane is expected to have low adsorption and thus very high mobility. Volatilization from moist soil and dry soil surfaces is expected. Ethyloxirane is not expected to be persistent in soil.
Atmospheric Fate: It is expected that ethyloxirane exists solely as a vapor in ambient atmosphere. Ethyloxirane may also be removed from the atmosphere by wet deposition processes. The half-life in air is about 5.6 days from the reaction of ethyloxirane with photochemically produced hydroxyl radicals which indicates that this chemical meets the persistence criterion in air (half-life of = 2 days).
Ecotoxicity - The potential for bioaccumulation of ethyloxirane in organisms is likely to be low and has low to moderate toxicity to aquatic organisms. Ethyloxirane is acutely toxic to water fleas and toxicity values for bacteria are close to 5000 mg/L. For algae, toxicity values exceed 500 mg/L.

For Methyl Ethyl Ketone:
log Kow: 0.26-0.69;
log Koc: 0.69;
Koc: 34;
Half-life (hr) air: 2.3;
Half-life (hr) H2O surface water: 72-288;
Henry's atm m3 /mol: 1.05E-05;
BOD 5: 1.5-2.24, 46%;
COD: 2.2-2.31, 100%;
ThOD: 2.44;
BCF: 1.
Environmental Fate: Terrestrial Fate - Measured Koc values of 29 and 34 were obtained for methyl ethyl ketone in silt loams. Methyl ethyl ketone is expected to have very high mobility in soil. Volatilization of methyl ethyl ketone from moist and dry soil surfaces is expected. The volatilization half-life of methyl ethyl ketone from silt and sandy loams was measured as 4.9 days. Methyl ethyl ketone is expected to biodegrade under both aerobic and anaerobic conditions.
Aquatic Fate: Methyl ethyl ketone is not expected to adsorb to suspended solids and sediment in water and is expected to volatilize from water surfaces. Estimated half-lives for a model river and model lake are 19 and 197, hours respectively. Bioconcentration is expected to be low in aquatic systems.
Atmospheric Fate: Methyl ethyl ketone will exist solely as a vapour in the ambient atmosphere. Vapour-phase methyl ethyl ketone is degraded in the atmosphere by reaction with photochemically-produced hydroxyl radicals; the half-life for this reaction in air is estimated to be about 14 days. Methyl ethyl ketone is also expected to undergo photodecomposition in the atmosphere by natural sunlight.
Ecotoxicity: Methyl ethyl ketone is not acutely toxic to fish, specifically, bluegill sunfish, guppy, goldfish, fathead minnow, mosquito fish, Daphnia magna water fleas and brine shrimp.
For Phenols:
Ecotoxicity - Phenols with log Pow >7.4 are expected to exhibit low toxicity to aquatic organisms however; the toxicity of phenols with a lower log Pow is variable. Dinitrophenols are more toxic than predicted from QSAR estimates. Hazard information for these groups is not generally available.
For Ketones: Ketones, unless they are alpha, beta--unsaturated ketones, can be considered as narcosis or baseline toxicity compounds.
Aquatic Fate: Hydrolysis of ketones in water is thermodynamically favourable only for low molecular weight ketones. Reactions with water are reversible with no permanent change in the structure of the ketone substrate. Ketones are stable to water under ambient environmental conditions. When pH levels are greater than 10, condensation reactions can occur which produce higher molecular weight products. Under ambient conditions of temperature, pH, and low concentration, these condensation reactions are unfavourable. Based on its reactions in air, it seems likely that ketones undergo photolysis in water.
Terrestrial Fate: It is probable that ketones will be biodegraded by micro-organisms in soil and water.
Ecotoxicity: Ketones are unlikely to bioconcentrate or biomagnify.
For Tetrahydrofuran (THF): Koc: 23 and 18; Henry's Law Constant: 7.1X10-5 atm-m3/mole; Vapor pressure: 162 mm Hg at 25 deg C.
Atmospheric Fate: Tetrahydrofuran exists only as a vapor in the ambient atmosphere. Vapor-phase tetrahydrofuran will be degraded in the atmosphere by reaction with photochemically-produced hydroxyl and nitrate radicals; the half-life for these reactions in air is about 1 and 3 days, respectively. Tetrahydrofuran is moderately reactive in photochemical smog conditions where nitrogen oxides are present; reactions occur in hours under these conditions. Acrolein and formaldehyde have been reported as reaction products.
Terrestrial Fate: Tetrahydrofuran is expected to have very high mobility in soil. Volatilization from moist soil surfaces is expected to be an important fate process. Tetrahydrofuran may also volatilize from dry soil surfaces. Tetrahydrofuran added to surface soil had an abiotic half-life of 5.7 days. Tetrahydrofuran is expected to biodegrade under aerobic conditions but may be resistant to biodegradation in anaerobic environments.
Aquatic Fate: Tetrahydrofuran is slightly persistent in water with a half-life of between 2 to 20 days. If tetrahydrofuran should contact the water table, aquifer or navigable waterway, time is of the essence. It is highly soluble in water and total remediation may not be possible. A comprehensive emergency response or disaster preparedness / recovery plan should be in place prior to use. Volatilization from water surfaces is expected to be an important fate process. Hydrolysis is not expected to occur. Tetrahydrofuran is not expected to adsorb to suspended solids and sediment.
Ecotoxicity: The potential for bioaccumulation of THF in aquatic organisms is considered to be low and it is not expected to bioaccumulate in aquatic organisms. The concentration of tetrahydrofuran in edible fish tissue is expected to be negligible as compared to the levels found in the water from which the fish were taken. Acute short term toxic environmental effects of THF may include the death of animals, birds, fish and death or low growth rate in plants. Acute effects are seen 2 to 4 days after animals or plants are exposed to tetrahydrofuran. Chronic toxic effects include shortened life span, reproductive problems, lowered fertility, and changes in appearance or behavior in exposed animals. These effects have been seen long after the first exposure(s).
**DO NOT** discharge into sewer or waterways.

**Persistence and degradability**

**Continued...**

| Ingredient | Persistence: Water/Soil | Persistence: Air |
|---|---|---|
| tetrahydrofuran | LOW | LOW |
| methyl ethyl ketone | LOW (Half-life = 14 days) | LOW (Half-life = 26.75 days) |

**Bioaccumulative potential**

| Ingredient | Bioaccumulation |
|---|---|
| tetrahydrofuran | LOW (LogKOW = 0.46) |
| methyl ethyl ketone | LOW (LogKOW = 0.29) |

**Mobility in soil**

| Ingredient | Mobility |
|---|---|
| tetrahydrofuran | LOW (Log KOC = 4.881) |
| methyl ethyl ketone | MEDIUM (Log KOC = 3.827) |

## SECTION 13 Disposal considerations

**Waste treatment methods**

| | |
|---|---|
| **Product / Packaging disposal** | ‣ Containers may still present a chemical hazard/ danger when empty.<br>‣ Return to supplier for reuse/ recycling if possible.<br>Otherwise:<br>‣ If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.<br>‣ Where possible retain label warnings and SDS and observe all notices pertaining to the product.<br>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.<br>A Hierarchy of Controls seems to be common - the user should investigate:<br>‣ Reduction<br>‣ Reuse<br>‣ Recycling<br>‣ Disposal (if all else fails)<br>This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.<br>‣ **DO NOT** allow wash water from cleaning or process equipment to enter drains.<br>‣ It may be necessary to collect all wash water for treatment before disposal.<br>‣ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.<br>‣ Where in doubt contact the responsible authority.<br>‣ Recycle wherever possible.<br>‣ Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.<br>‣ Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material).<br>‣ Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed. |

## SECTION 14 Transport information

**Labels Required**

| | |
|---|---|
| | |
| **Marine Pollutant** | |

**Land transport (UN)**

| | |
|---|---|
| 14.1. **UN number or ID number** | 1133 |
| 14.2. **UN proper shipping name** | ADHESIVES containing flammable liquid |
| 14.3. **Transport hazard class(es)** | Class: 3<br>Subsidiary Hazard: Not Applicable |
| 14.4. **Packing group** | II |
| 14.5. **Environmental hazard** | Not Applicable |
| 14.6. **Special precautions for user** | Special provisions: Not Applicable<br>Limited quantity: 5 L |

**Continued...**

**Air transport (ICAO-IATA / DGR)**

| | |
|---|---|
| 14.1. **UN number** | 1133 |
| 14.2. **UN proper shipping name** | Adhesives containing flammable liquid |
| 14.3. **Transport hazard class(es)** | ICAO/IATA Class: 3<br>ICAO / IATA Subsidiary Hazard: Not Applicable<br>ERG Code: 3L |
| 14.4. **Packing group** | II |
| 14.5. **Environmental hazard** | Environmentally hazardous |
| 14.6. **Special precautions for user** | Special provisions: A3<br>Cargo Only Packing Instructions: 364<br>Cargo Only Maximum Qty / Pack: 60 L<br>Passenger and Cargo Packing Instructions: 353<br>Passenger and Cargo Maximum Qty / Pack: 5 L<br>Passenger and Cargo Limited Quantity Packing Instructions: Y341<br>Passenger and Cargo Limited Maximum Qty / Pack: 1 L |

**Sea transport (IMDG-Code / GGVSee)**

| | |
|---|---|
| 14.1. **UN number** | 1133 |
| 14.2. **UN proper shipping name** | ADHESIVES containing flammable liquid |
| 14.3. **Transport hazard class(es)** | IMDG Class: 3<br>IMDG Subsidiary Hazard: Not Applicable |
| 14.4. **Packing group** | II |
| 14.5 **Environmental hazard** | Marine Pollutant |
| 14.6. **Special precautions for user** | EMS Number: F-E, S-D<br>Special provisions: Not Applicable<br>Limited Quantities: 5 L |

**14.7. Maritime transport in bulk according to IMO instruments**

**14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code**

Not Applicable

**14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code**

| Product name | Group |
|---|---|
| tetrahydrofuran | Not Applicable |
| bisphenol F diglycidyl ether copolymer | Not Applicable |
| methyl ethyl ketone | Not Applicable |

**14.7.3. Transport in bulk in accordance with the IGC Code**

| Product name | Ship Type |
|---|---|
| tetrahydrofuran | Not Applicable |
| bisphenol F diglycidyl ether copolymer | Not Applicable |
| methyl ethyl ketone | Not Applicable |

## SECTION 15 Regulatory information

**Safety, health and environmental regulations / legislation specific for the substance or mixture**

**tetrahydrofuran is found on the following regulatory lists**

Chemical Footprint Project - Chemicals of High Concern List
EAEU Narcotic drugs, psychotropic substances and their precursors - II. Precursors of narcotic drugs and psychotropic substances - List III (Russian)
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans

**bisphenol F diglycidyl ether copolymer is found on the following regulatory lists**

Chemical Footprint Project - Chemicals of High Concern List

**methyl ethyl ketone is found on the following regulatory lists**

EAEU Narcotic drugs, psychotropic substances and their precursors - II. Precursors of narcotic drugs and psychotropic substances - List II (Russian)

**Continued...**

India Permissible Levels of Certain Chemical Substances in Work Environment

**Additional Regulatory Information**

Not Applicable

**National Inventory Status**

| National Inventory | Status |
|---|---|
| Australia - AIIC / Australia Non-Industrial Use | Yes |
| Canada - DSL | Yes |
| Canada - NDSL | No (tetrahydrofuran; bisphenol F diglycidyl ether copolymer; methyl ethyl ketone) |
| China - IECSC | Yes |
| Colombia - Colombia National Industrial Chemicals Inventory | No (tetrahydrofuran; bisphenol F diglycidyl ether copolymer; methyl ethyl ketone) |
| Europe - EINEC / ELINCS / NLP | No (bisphenol F diglycidyl ether copolymer) |
| Japan - ENCS | Yes |
| Korea - KECI | Yes |
| New Zealand - NZIoC | Yes |
| Philippines - PICCS | Yes |
| USA - TSCA | All chemical substances in this product have been designated as TSCA Inventory 'Active' |
| Taiwan - TCSI | Yes |
| Mexico - INSQ | No (bisphenol F diglycidyl ether copolymer) |
| Vietnam - NCI | Yes |
| Russia - FBEPH | Yes |
| UAE - Control List (Banned/Restricted Substances) | No (tetrahydrofuran; bisphenol F diglycidyl ether copolymer; methyl ethyl ketone) |
| **Legend:** | Yes = All CAS declared ingredients are on the inventory<br>No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration. |

## SECTION 16 Other information

| | |
|---|---|
| **Revision Date** | 04/14/2026 |
| **Initial Date** | 11/26/2025 |

**Other information**

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Powered by AuthorITe, from Chemwatch.

**end of SDS**

# Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, “VPG”), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify VPG’s terms and conditions of purchase, including but not limited to, the warranty expressed therein.

VPG makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. **To the maximum extent permitted by applicable law, VPG disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.**

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on VPG’s knowledge of typical requirements that are often placed on VPG products. It is the customer’s responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. You should ensure you have the current version of the relevant information by contacting VPG prior to performing installation or use of the product, such as on our website at vpgsensors.com.

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of VPG.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling VPG products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify VPG for any damages arising or resulting from such use or sale. Please contact authorized VPG personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Copyright Vishay Precision Group, Inc., 2014. All rights reserved.