

SAFETY DATA SHEET

Version: 4.0
Date of Issue: 27 April 2017
Date of First Issue: 20 March 2012

www.vishaypg.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

SECTION 1: IDENTIFICATION

Product identifier used on the label	M-Bond 600 Adhesive	
Other means of identification	Not applicable	
Recommended use of the chemical and restrictions on use		
Recommended use	Adhesives.	
Restrictions on use	Anything other than the above.	
Details of the supplier of the safety data sheet		
Supplier	VISHAY MEASUREMENTS GROUP, INC.	
Address of Supplier	Post Office Box 27777 Raleigh, NC 27611 USA	
Telephone	+1 919-365-3800	
Fax	+1 919-365-3945	
E-Mail (competent person)	mm.us@vishaypg.com	
Emergency telephone number	1-800-424-9300	CHEMTREC (24 hours)

SECTION 2: HAZARD(S) IDENTIFICATION

Classification of the substance or mixture in accordance with paragraph (d) of 29 CFR 1910.1200

Physical hazards	Flammable Liquid, Category 2
Health hazards	Acute toxicity, Category 4 Skin Irritation, Category 2 Skin Sensitisation, Category 1 Eye Irritation, Category 2 Specific target organ toxicity — single exposure, Category 3 Carcinogen, Category 2
Environmental hazards	Hazardous to the aquatic environment, Chronic, Category 2

Hazard Symbol



Signal Word(s)

Danger

Hazard Statement(s)

Highly flammable liquid and vapour.
Harmful if swallowed.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause respiratory irritation.
Suspected of causing cancer.
Toxic to aquatic life with long lasting effects.

Precautionary Statement(s)

Obtain special instructions before use.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Keep container tightly closed.
Avoid breathing vapours.

SAFETY DATA SHEET

Version: 4.0
Date of Issue: 27 April 2017
Date of First Issue: 20 March 2012

www.vishaypg.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Wash hands and exposed skin thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection.
IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.
Rinse mouth.
IF ON SKIN: Wash with plenty of water.
If skin irritation or rash occurs: Get medical advice/attention.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a POISON CENTER/doctor if you feel unwell.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists, get medical advice/attention.
IF exposed or concerned: Get medical advice/attention.

Other hazards

May form explosive peroxides.

Percent of the mixture consists of ingredient(s) of unknown acute toxicity:

0%

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Substances Not applicable

Mixtures Substances in preparations / mixtures

Chemical identity of the substance	%W/W	CAS No.	EC No.	Hazard classification
Tetrahydrofuran	45 – 55	109-99-9	203-726-8	Flammable Liquid, Category 2 Acute toxicity, Category 4 Eye Irritation, Category 2 (SCL ≥ 25%) Specific target organ toxicity — single exposure, Category 3 (SCL ≥ 25%) Carcinogen, Category 2
Polyglycidyl Ether of Phenol-Formaldehyde	30 – 40	28064-14-4	608-164-0	Skin Irritation, Category 2 Skin Sensitisation, Category 1 Eye Irritation, Category 2 Hazardous to the aquatic environment, Chronic, Category 2
Ethyl methyl ketone	12-18	78-93-3	201-159-0	Flammable Liquid, Category 2 Eye Irritation, Category 2 Specific target organ toxicity — single exposure, Category 3

SECTION 4: FIRST AID MEASURES



Description of first aid measures

Self-protection of the first aider

Use personal protective equipment as required. Wear appropriate personal protective equipment, avoid direct contact. Ensure adequate ventilation. Avoid breathing vapours. Avoid all contact. Contaminated clothing should be laundered before reuse.

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF exposed or concerned: Get medical advice/attention.

Skin Contact

IF ON SKIN: Remove contaminated clothing and wash all affected areas with plenty of water. Wash contaminated clothing before reuse. If skin irritation or rash

SAFETY DATA SHEET

Version: 4.0
Date of Issue: 27 April 2017
Date of First Issue: 20 March 2012

www.vishaypg.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Eye Contact	occurs: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention.
Ingestion	IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Harmful if swallowed. Make victim drink plenty of water. Do not give anything by mouth to an unconscious person. Do not induce vomiting unless instructed to do so by medical personnel. IF exposed or concerned: Get medical advice/attention.
Most important symptoms and effects, both acute and delayed	Harmful if swallowed. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause respiratory irritation. Suspected of causing cancer.
Indication of any immediate medical attention and special treatment needed	Treat symptomatically.
Notes to a physician:	IF INHALED: Respiratory symptoms, including pulmonary edema, may be delayed. IF IN EYES: After rinsing affected eyes must be seen by an ophthalmologist.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing media	As appropriate for surrounding fire. Extinguish with carbon dioxide, dry chemical, foam or waterspray.
Suitable Extinguishing Media	
Unsuitable extinguishing Media	Do not use water jet. Direct water jet may spread the fire.
Special hazards arising from the substance or mixture	Highly flammable liquid and vapour. May decompose in a fire giving off toxic fumes. Carbon monoxide, Carbon dioxide, Phenolic and Explosive Peroxides. Vapours are heavier than air and may travel considerable distances to a source of ignition and flashback. Prevent liquid entering sewers, basements and workpits; vapour may create explosive atmosphere. May form explosive peroxides.
Special protective equipment and precautions for fire fighters	Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Do not breathe fumes. Keep containers cool by spraying with water if exposed to fire. Avoid run off to waterways and sewers.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	Ensure adequate ventilation. Stop leak if safe to do so. Eliminate all ignition sources if safe to do so. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use personal protective equipment as required. See Section: 8. Avoid breathing vapours.
Methods and material for containment and cleaning up	Use non-sparking equipment when picking up flammable spill. Adsorb spillages onto sand, earth or any suitable adsorbent material. Transfer to a container for disposal. Ventilate the area and wash spill site after material pick-up is complete. Dispose of this material and its container as hazardous waste.

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling	Ensure operatives are trained to minimise exposures. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid all contact. Do not breathe vapour. Ensure adequate ventilation. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only non-sparking tools. May form explosive peroxides. Take precautionary measures against static discharges. Use personal protective equipment as required. See Section: 8. Do not eat, drink or smoke when using this product. Wash hands before breaks and after work.
Conditions for safe storage, including any incompatibilities	Ground/bond container and receiving equipment. Keep only in original container. Store in a well-ventilated place. Keep container tightly closed. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. May form explosive peroxides. Keep away from direct sunlight.
Storage temperature	Ambient. Keep at temperature not exceeding (°C): 32

SAFETY DATA SHEET

Version: 4.0
Date of Issue: 27 April 2017
Date of First Issue: 20 March 2012

www.vishaypg.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Incompatible materials

Keep away from: Oxidizing agents, Corrosive Substances, Reducing agent, Strong Acids and Alkalis.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

SUBSTANCE	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m ³)	STEL (ppm)	STEL (mg/m ³)	Note
Tetrahydrofuran	109-99-9	200	590	250*	735*	NIOSH
		200	590	-	-	OSHA
		50	-	100	-	ACGIH, Sk, A3
Ethyl methyl ketone	78-93-3	200	590	300*	885*	NIOSH
		200	590	-	-	OSHA
		200	-	300	-	ACGIH

Note: OSHA PELs 1910.1000 TABLE Z-1/ NIOSH RELs / ACGIH TLVs

*NIOSH average value of 15 minutes.

Sk: Can be absorbed through the skin.

A3: Confirmed Animal Carcinogen with Unknown Relevance to Humans: The agent is carcinogenic in experimental animals at a relatively high dose, by route(s) of administration, at site(s), of histological type(s), or by mechanism(s) that may not be relevant to worker exposure. Available epidemiological studies do not confirm an increased risk of cancer in exposed humans. Available evidence does not suggest that the agent is likely to cause cancer in humans except under uncommon or unlikely routes or levels of exposure.

The other components listed in Section 3 do not have occupational exposure limits.

Biological Exposure Indices

SUBSTANCE	CAS No.	Determinant	Biological Exposure Indices	Sampling Time	Note
Tetrahydrofuran	109-99-9	Tetrahydrofuran in urine	2 mg/L	End of shift	-
Ethyl methyl ketone	78-93-3	Methyl ethyl ketone in urine	2 mg/L	End of shift	Ns

Source: 2015 ACGIH Biological Exposure Indices (BEIs)

Ns - Nonspecific

The other components listed in Section 3 do not have biological exposure indices.

Appropriate engineering controls

Ensure operatives are trained to minimise exposures. Ensure adequate ventilation. Atmospheric levels should be controlled in compliance with the occupational exposure limit.

Individual protection measures, such as personal protective equipment (PPE)

General hygiene measures for the handling of chemicals are applicable. Keep good industrial hygiene. Avoid all contact. Avoid breathing vapours. Wash hands before breaks and after work. Keep work clothes separately. Do not eat, drink or smoke at the work place.

IF exposed: Flush with fresh water if contact with skin or eyes.

Eye/face protection



Wear protective eye glasses for protection against liquid splashes. Wear eye protection with side protection.

Skin protection



Hand protection:

Wear impervious gloves. Gloves should be changed regularly to avoid permeation problems. Breakthrough time of the glove material: refer to the information provided by the gloves' producer. Recommended: Polyethylene-Laminate (Minimum thickness 0.1mm).

SAFETY DATA SHEET

Version: 4.0
Date of Issue: 27 April 2017
Date of First Issue: 20 March 2012

www.vishaypg.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Respiratory protection



Body protection:

Wear impervious protective clothing, including boots, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

In case of inadequate ventilation wear respiratory protection. A suitable mask with filter type A may be appropriate.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Almost colourless Liquid
Odor	Ether-like Odour
Odor Threshold	Not available.
pH	Not established.
Melting Point/Freezing Point	Not available.
Initial boiling point and boiling range	66°C
Flash Point	-14 °C (Mixture)
Evaporation rate (Butyl acetate = 1)	8 (BuAc = 1)
Flammability (solid, gas)	Not applicable - Liquid
Upper/lower flammability or explosive limits	Flammable Limits (Lower) (%v/v): 1.8 Flammable Limits (Upper) (%v/v): 11.8
Vapour pressure	129 (mmHg) @ 20°C
Vapour density	2.4 (Air = 1)
Relative density	0.9 (H ₂ O = 1)
Solubility(ies)	Water: >50%
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature	320 °C
Decomposition Temperature	Not available.
Viscosity	Not available.

Other information: VOC 598 g/L

SECTION 10: STABILITY AND REACTIVITY

Reactivity	Stable under normal conditions. May form peroxides on prolonged storage if air is present.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	Highly flammable liquid and vapour. The vapour may be invisible, heavier than air and spread along ground. May form explosive peroxides. Contact with aliphatic amines will cause irreversible polymerization with considerable heat build-up.
Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep away from direct sunlight. Keep at a temperature not exceeding (°C): 32. Avoid contact with air. Avoid contact with heat and ignition sources and oxidizers. Avoid distillation to dryness, which can form explosive peroxides.
Incompatible materials	Oxidizing agents, Corrosive Substances, Reducing agent, Strong Acids and Alkalis.
Hazardous decomposition product(s)	May decompose in a fire giving off toxic fumes. Carbon monoxide, Carbon dioxide, Phenolic and Explosive Peroxides.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on toxicological effects (Substances in preparations / mixtures)

SAFETY DATA SHEET

Version: 4.0
Date of Issue: 27 April 2017
Date of First Issue: 20 March 2012

www.vishaypg.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Acute toxicity - Ingestion

Tetrahydrofuran:

Acute toxicity - Inhalation

Acute toxicity - Skin Contact

Skin corrosion/irritation

Polyglycidyl Ether of Phenol-Formaldehyde:

Ethyl methyl ketone:

Serious eye damage/irritation

Tetrahydrofuran:

Polyglycidyl Ether of Phenol-Formaldehyde:

Ethyl methyl ketone:

Respiratory or skin sensitization

Polyglycidyl Ether of Phenol-Formaldehyde:

Germ cell mutagenicity

Carcinogenicity

Tetrahydrofuran:

Reproductive toxicity

STOT - single exposure

Tetrahydrofuran:

Ethyl methyl ketone:

STOT - repeated exposure

Aspiration hazard

Information on likely routes of exposure

Inhalation

Ingestion

Skin Contact

Eye Contact

Early onset symptoms related to exposure

Delayed health effects from exposure

Other information

NTP Report on Carcinogens

IARC Monographs

OSHA Designated Carcinogen

Acute Toxicity, Category 4: Harmful if swallowed. Harmful in contact with skin. Harmful if inhaled.

Acute Toxicity Estimate Mixture Calculation: Estimated LC50 >750 mg/kg bw/day.

Test Result LD50 <1 ml/kg bw (Standard acute method).

Based upon the available data, the classification criteria are not met.

Acute Toxicity Estimate Mixture Calculation: Estimated LC50 >20.0 mg/l.

Based upon the available data, the classification criteria are not met.

Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 2000 mg/kg bw/day.

Skin Irritation, Category 2: Causes skin irritation.

No data. EU classification and labelling inventory

Prolonged skin contact will result in defatting of the skin, leading to irritation, and in some cases, dermatitis. (Smith R & Mayers MR, 1944).

Eye Irritation, Category 2: Causes serious eye irritation.

No data. EU Harmonised Classification.

No data. EU classification and labelling inventory

Test Result: Irritating to eyes. (OECD 405)

Skin Sensitisation, Category 1: May cause an allergic skin reaction.

Allergic contact dermatitis (Pontén, A et al, 1999)

Based on available data, the classification criteria are not met.

Carcinogen, Category 2: Suspected of causing cancer.

Test Result: NOAEC 1800 ppm Suspected carcinogen (Unnamed, 1998)

Based on available data, the classification criteria are not met.

Specific target organ toxicity - single exposure, Category 3: May cause respiratory irritation. May cause drowsiness or dizziness.

Test Result: Central nervous depression (Malley, L.A. et al, 2001)

Rats at all dose levels: gait and/or posture abnormalities. Higher dose groups some rats were comatose or prostrate within a few hours of dosing, with some animals being unconscious for 24 hours. (OECD 423)

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

Possible – accidental exposure.

Unlikely – accidental exposure.

Possible – accidental exposure.

Possible – accidental exposure.

Causes irritation to skin and eyes. Harmful if swallowed.

Suspected to causing cancer.

Not listed.

Not listed.

Not listed.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Polyglycidyl Ether of Phenol-Formaldehyde:

Persistence and degradability

Bioaccumulative potential

Mobility in soil

Other adverse effects

Aquatic Chronic 2: Toxic to aquatic life with long lasting effects.

Estimated Mixture LC50 > 1 to ≤ 10 mg/l. (Fish)

EC50 1.6 mg/l 48hr (Daphnia magna) (Wyness LE et al, 1993)

Part of the components are poorly biodegradable.

The product has low potential for bioaccumulation.

The product is predicted to have high mobility in soil.

None known.

SAFETY DATA SHEET

Version: 4.0
Date of Issue: 27 April 2017
Date of First Issue: 20 March 2012

www.vishaypg.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Dispose of this material and its container as hazardous waste. Send after pre-treatment to a appropriate hazardous waste incinerator facility according to legislation. Send after pre-treatment to a appropriate hazardous waste incinerator facility according to legislation.

Additional Information

Dispose of contents in accordance with local, state or national regulations.

SECTION 14: TRANSPORT INFORMATION

	ADR/RID	IMDG	IATA
UN number	UN 1133	UN 1133	UN 1133
UN proper shipping name	ADHESIVES containing flammable liquid	ADHESIVES containing flammable liquid	ADHESIVES containing flammable liquid
Transport hazard class(es)	3	3	3
Packing group	II	II	II
Environmental hazards	Environmentally hazardous substance	Classified as a Marine Pollutant.	Environmentally hazardous substance
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.		
Special precautions for user	See Section: 2		

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

US Federal Regulations

TSCA (Toxic Substance Control Act)

Tetrahydrofuran - Subject to 25,000 lb reporting threshold.
Ethyl methyl ketone - Subject to 25,000 lb reporting threshold.

EPCRA/SARA Section 302 Extremely Hazardous Substances

Not listed.

EPCRA Section 313 Toxics Release Inventory (TRI) Program

Not listed.

NIOSH Occupational Carcinogen List

Not listed.

OSHA List of highly hazardous chemicals, toxics and reactives

Not listed.

NTP Report on Carcinogens (RoC) List

Not listed.

Poison Prevention Packaging Act

Not listed.

US State Regulations

California State, Proposition 65 List

Not listed.

California State, Safer Consumer Products Regulations

Tetrahydrofuran - Initial Candidate Chemicals List, Group Member List:
Polychlorinated dibenzo-p-furans (PCDFs) and Furan Compounds.
Ethyl methyl ketone- Candidate Chemicals List.

Maine State, Toxic Chemicals in Children's Products Act

Not listed.

New Jersey State Worker and Community RTK Act

Tetrahydrofuran - RTKHSL and SHHSL.

Ethyl methyl ketone - RTKHSL and SHHSL.

Pennsylvania State, Worker and Community RTK Act

Tetrahydrofuran - Hazardous Substances List and the Environmental Hazard List.

Ethyl methyl ketone - Hazardous Substances List and the Environmental Hazard List.

Rhode Island State, Hazardous Substances RTK Act

Tetrahydrofuran - Hazardous Substances List.

Ethyl methyl ketone - Hazardous Substances List.

Non-Regional

IARC Monographs, List of Classifications

Not listed.

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: New SDS Regulation compliant with HazCom 2012 format, all sections have been updated to include new information. Please review SDS with care.

SAFETY DATA SHEET

Version: 4.0
Date of Issue: 27 April 2017
Date of First Issue: 20 March 2012

www.vishaypg.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Version 4.0
Revision Date 27-Apr-2017
Date of First Issue 20-Mar-2012

References:

Existing Safety Data Sheet (SDS), EU Data: Harmonised Classification(s) for Tetrahydrofuran (CAS No. 109-99-9) and Ethyl methyl ketone (CAS No. 78-93-3). Existing ECHA registration(s) for Tetrahydrofuran (CAS No. 109-99-9), Ethyl methyl ketone (CAS No. 78-93-3), the Classification and Labelling Inventory for Polyglycidyl Ether of Phenol-Formaldehyde (CAS No. 28064-14-4).

Literature References:

1. Smith R & Mayers MR, 1944, Study of poisoning and fire hazards of butanone and acetone, Industrial Hygiene: 23, 174-176
2. Pontén, A. and Bruze, M. (1999), Occupational allergic contact dermatitis from epoxy resins based on bisphenol F. Contact Dermatitis, 41: 235. doi:10.1111/j.1600-0536.1999.tb06149.x
3. Malley, L.A., Christoph G.R., Stadler, J.C., Hansen, J.F., Biesemeir, J.A. and Jasti, S., 2001, Acute and subchronic neurotoxicology evaluation of tetrahydrofuran by inhalation in rats, Drug Chem. Toxicol., 24(3): 201-219
4. Wyness LE, Cheeman H, Lad DD and Baldwin MK (1993), EPIKOTE 862: Acute toxicity to *Oncorhynchus mykiss*, *Daphnia magna* and *Selenastrum capricornutum*; SBGR.92.237

GHS Classification of the substance or mixture	Classification Procedure
Flammable Liquid, Category 2	Flash Point [Closed cup] Test Result/ Boiling Point (°C) Test Result
Acute toxicity, Category 4	Acute Toxicity Estimate (ATE) Calculation.
Skin Irritation, Category 2	Threshold Calculation
Skin Sensitisation, Category 1	Threshold Calculation
Eye Irritation, Category 2	Threshold Calculation
Specific target organ toxicity — single exposure, Category 3	Threshold Calculation
Carcinogen, Category 2	Threshold Calculation
Hazardous to the aquatic environment, Chronic, Category 2	Summation Calculation

LEGEND

ACGIH: American Conference of Governmental Industrial Hygienists
BEI: Biological Exposure Indices (ACGIH)
IARC: International Agency for Research on Cancer
Irr: Irritation
NIOSH: National Institute of Occupational Safety and Health
NTP: National Toxicology Program
OSHA: The Occupational Safety & Health Administration
PBT: Persistent, Bioaccumulative and Toxic
PEL: Permissible exposure limit

REL: Recommended exposure limit
SCL: Specific Concentration Limit
Skin^o: Risk of overexposure via dermal contact
STEL: Short Term Exposure Limit
TLV: Threshold Limit value
TSCA: Toxic Substance Control Act
TWA: Time Weighted Average
URT: Upper respiratory tract
vPvB: very Persistent and very Bioaccumulative

Training advice: Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required.

Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Vishay Precision Group gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Vishay Precision Group accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.



Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "VPG"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify VPG's terms and conditions of purchase, including but not limited to, the warranty expressed therein.

VPG makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. **To the maximum extent permitted by applicable law, VPG disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.**

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on VPG's knowledge of typical requirements that are often placed on VPG products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. You should ensure you have the current version of the relevant information by contacting VPG prior to performing installation or use of the product, such as on our website at vpgsensors.com.

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of VPG.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling VPG products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify VPG for any damages arising or resulting from such use or sale. Please contact authorized VPG personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Copyright Vishay Precision Group, Inc., 2014. All rights reserved.