

# SAFETY DATA SHEET

## QA-600 Adhesive Part A

### ACCORDING TO OSHA HCS (29 CFR 1910.1200)

#### SECTION 1: IDENTIFICATION

**Product identifier used on the label**

Product Name QA-600 Adhesive Part A

**Other means of identification**

Not applicable

**Recommended use of the chemical and restrictions on use**

Recommended use Adhesives  
Restrictions on use Anything other than the above.

**Details of the supplier of the safety data sheet**

Supplier VISHAY MEASUREMENTS GROUP, INC.  
Address of Supplier Post Office Box 27777  
Raleigh, NC 27611  
USA  
Telephone +1 919-365-3800  
Fax +1 919-365-3945  
E-Mail (competent person) [mm.us@vpgsensors.com](mailto:mm.us@vpgsensors.com)

**Emergency telephone number**

Emergency Phone No. +1 800-262-8200 (for spills and releases)  
Languages spoken English - CHEMTREC (24 hours)

#### SECTION 2: HAZARD(S) IDENTIFICATION

**Classification of the chemical in accordance with paragraph (d) of §1910.1200**

Physical hazards Flammable Liquids, Category 2  
Health hazards Acute Toxicity (oral), Category 4  
Skin sensitizer, Category 1  
Eye irritation, Category 2  
Specific target organ toxicity (single exposure), Category 3 Irritation to respiratory tract  
Specific target organ toxicity (single exposure), Category 3 Narcotic effects  
Carcinogen, Category 2  
Environmental hazards Not classified

**Label elements**

Hazard Symbol



Signal Word(s)

Danger

Hazard Statement(s)

Highly flammable liquid and vapour.  
Harmful if swallowed.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.

# SAFETY DATA SHEET



## QA-600 Adhesive Part A

[www.vpgsensors.com](http://www.vpgsensors.com)

Date of issue: 17 February 2022  
Date of First Issue: 11 October 2012  
Version: 3.0

### ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Suspected of causing cancer.

Precautionary Statement(s)  
Prevention

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ventilating/lighting/equipment.  
Use non-sparking tools.  
Use only outdoors or in a well-ventilated area.  
Take precautionary measures against static discharge.  
Wear protective gloves/eye protection/face protection.  
Wash hands and exposed skin thoroughly after handling.  
Do not eat, drink or smoke when using this product.  
Avoid breathing vapours.

Response

Contaminated work clothing must not be allowed out of the workplace.  
IF exposed or concerned: Get medical advice/attention.  
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/or shower. If skin irritation or rash occurs: Get medical advice/attention.  
IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.  
Wash contaminated clothing before reuse.

Storage  
Disposal

Store in a well-ventilated place. Keep container tightly closed. Store locked up.  
Dispose of contents/container to hazardous waste collection point.

#### Other hazards

May form explosive peroxides.

Percent of the mixture consists of ingredient(s) of unknown acute toxicity:

0 percent of the mixture consists of ingredient(s) of unknown acute inhalation toxicity  
0 percent of the mixture consists of ingredient(s) of unknown acute oral toxicity  
0 percent of the mixture consists of ingredient(s) of unknown acute dermal toxicity

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

**Substances** Not applicable

**Mixtures** Substances in preparations / mixtures

Classification: OSHA HCS (29 CFR 1910.1200)

Chemical identity of the substance	%W/W	Synonym(s)	CAS No.	Hazard classification
Tetrahydrofuran	55-60	Furan, tetrahydro-	109-99-9	Flammable Liquid, Category 2 Acute Toxicity - Oral, Category 4 Eye Irritant, Category 2, (SCL ≥ 25%) STOT, Single Exposure, Category 3, Respiratory Tract Irritation (SCL ≥ 25%) STOT, Single Exposure, Category 3, Narcotic Effects Carcinogen, Category 2

# SAFETY DATA SHEET

## QA-600 Adhesive Part A

### ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Formaldehyde, polymer with 2-(chloromethyl)oxirane and 4,4'-(1- ethylethylidene)bis[phenol]	39-44	--	28906-96-9	Skin Sensitizer, Category 1 Eye Irritant, Category 2
---	-------	----	------------	---

#### SECTION 4: FIRST AID MEASURES



##### Description of first aid measures

Self-protection of the first aider

Use personal protective equipment as required. Wear appropriate personal protective equipment, avoid direct contact. Ensure adequate ventilation. Avoid breathing vapours. Avoid all contact. Contaminated clothing should be laundered before reuse.

Inhalation

IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. If unconscious, place in recovery position and get medical attention immediately. Apply artificial respiration if necessary (do not employ mouth-to-mouth method).

Skin Contact

IF ON SKIN: Remove contaminated clothing and wash all affected areas with plenty of water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention.

Eye Contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Hold eye open and rinse slowly and gently with water for 15-20 minutes. If eye irritation persists: Get medical advice/attention.

Ingestion

IF SWALLOWED: Rinse mouth. Make victim drink plenty of water. Do not give anything by mouth to an unconscious person. Do not induce vomiting unless instructed to do so by medical personnel. Call a POISON CENTER/doctor if you feel unwell. IF exposed or concerned: Get medical advice/attention.

**Most important symptoms and effects, both acute and delayed**

Harmful if swallowed. May cause an allergic skin reaction. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of causing cancer.

**Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

#### SECTION 5: FIRE-FIGHTING MEASURES

##### Extinguishing media

Suitable Extinguishing Media

As appropriate for surrounding fire. Extinguish with carbon dioxide, dry chemical, foam or waterspray.

Unsuitable extinguishing Media

Do not use water jet. Direct water jet may spread the fire.

**Special hazards arising from the substance or mixture**

Highly flammable liquid and vapour. May decompose in a fire giving off toxic fumes. Carbon monoxide, Carbon dioxide, Phenolic and Explosive Peroxides. Vapours are heavier than air and may travel considerable distances to a source of ignition and flashback. Prevent liquid entering sewers, basements and workpits; vapour may create explosive atmosphere. May form explosive peroxides.

**Special protective equipment and precautions for fire fighters**

Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Do not breathe fumes. Keep containers cool by spraying with water if exposed to fire. Avoid run off to waterways and sewers.

# SAFETY DATA SHEET



## QA-600 Adhesive Part A

[www.vpgsensors.com](http://www.vpgsensors.com)

Date of issue: 17 February 2022  
Date of First Issue: 11 October 2012  
Version: 3.0

### ACCORDING TO OSHA HCS (29 CFR 1910.1200)

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

##### Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Stop leak if safe to do so. Eliminate all ignition sources if safe to do so. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use personal protective equipment as required. See Section: 8. Avoid breathing vapours.

##### Environmental precautions

Avoid release to the environment. Do not allow to enter drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be alerted to the Environment Agency or other appropriate regulatory body.

##### Methods and material for containment and cleaning up

Use non-sparking equipment when picking up flammable spill. Adsorb spillages onto sand, earth or any suitable adsorbent material. Transfer to a container for disposal. Ventilate the area and wash spill site after material pick-up is complete. Dispose of this material and its container as hazardous waste

#### SECTION 7: HANDLING AND STORAGE

##### Precautions for safe handling

Ensure operatives are trained to minimise exposures. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid all contact. Avoid breathing vapours. Ensure adequate ventilation. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. May form explosive peroxides. Take precautionary measures against static discharges. Use personal protective equipment as required. See Section: 8. Do not eat, drink or smoke when using this product. Wash hands before breaks and after work.

##### Conditions for safe storage, including any incompatibilities

Ground/bond container and receiving equipment. Keep only in original container. Store in a well-ventilated place. Keep container tightly closed. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. May form explosive peroxides. Keep away from direct sunlight.

##### Storage temperature

Ambient. Keep at temperature not exceeding (°C): 32

##### Incompatible materials

Stable under normal conditions.

#### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

##### Occupational Exposure Limits

Substances	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m <sup>3</sup> )	STEL (ppm)	STEL (mg/m <sup>3</sup> )	Note	Source
Tetrahydrofuran	109-99-9	50	-	100	-	Skin; A3	ACGIH
		200	590	250	735	-	NIOSH
		200	590	-	-	-	OSHA (Z-1)

##### Source:

ACGIH: American Conference of Governmental Industrial Hygienists - Threshold limit values (TLV) 2019

NIOSH: National Institute for Occupational Safety and Health (NIOSH) Recommended exposure limits (RELs)

OSHA: Occupational Safety and Health Standards - Permissible Exposure Limit (PEL), 1910.1000 TABLE Z-1

Skin: Danger of cutaneous absorption (skin, mucous membranes and eyes) by contact with vapors, liquids and solids;

A3: Confirmed Animal Carcinogen with Unknown Relevance to Humans. See "Appendix A: Carcinogenicity" of ACGIH book.

##### Biological Exposure Indices

None assigned.

##### Appropriate engineering controls

Ensure operatives are trained to minimise exposures. Ensure adequate ventilation. Atmospheric levels should be controlled in compliance with the occupational exposure limit. A washing facility/water for eye and skin cleaning purposes should be present.

# SAFETY DATA SHEET

## QA-600 Adhesive Part A

### ACCORDING TO OSHA HCS (29 CFR 1910.1200)

#### Individual protection measures, such as personal protective equipment (PPE)

General hygiene measures for the handling of chemicals are applicable. Keep good industrial hygiene. Avoid all contact. Avoid breathing vapours. Wash hands before breaks and after work. Keep work clothes separately. Do not eat, drink or smoke at the work place.

IF exposed: Flush with fresh water if contact with skin or eyes.

Protective clothing should be selected specifically for the working place, depending on concentration and quantity of the hazardous substances handled. The resistance of the protective clothing to chemicals should be ascertained with the respective supplier.

#### Eye/face protection



Wear protective eye glasses for protection against liquid splashes. Wear eye protection with side protection (EN166).

#### Skin protection



#### Hand protection:

Wear impervious gloves (EN374). Protective index 6, corresponding > 480 minutes of permeation time according to EN 374.

Gloves should be changed regularly to avoid permeation problems. Breakthrough time of the glove material: refer to the information provided by the gloves' producer. Gloves should be changed regularly to avoid permeation problems. Care must be taken to wash down suit, gloves and boots before removal.

Protective clothing should be selected specifically for the working place, depending on concentration and quantity of the hazardous substances handled. The resistance of the protective clothing to chemicals should be ascertained with the respective supplier.

Recommended: Polyethylene-Nylon Laminate Gauntlet

#### Body protection:

Wear impervious protective clothing, including boots, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

#### Respiratory protection



In case of inadequate ventilation wear respiratory protection. A suitable mask with filter type A (EN141 or EN405) may be appropriate.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

#### Information on basic physical and chemical properties

Appearance

Odor

Odor Threshold

pH

Melting Point/Freezing Point

Initial boiling point and boiling range

Flash Point

Evaporation rate (Butyl acetate = 1)

Flammability (solid, gas)

Upper/lower flammability or explosive limits

Vapour pressure

Vapour density

The following information is based on a consideration of the properties of the main components of this mixture. (Tetrahydrofuran CAS# 109-99-9)

Almost colourless Liquid

Ether-like Odour

Not available

Not established

-108.44 °C

66°C (CAS# 109-99-9)

-14 °C (CAS# 109-99-9)

8 (BuAc = 1) (CAS# 109-99-9)

Not available - Liquid

Flammable Limits (Lower) (%v/v): 2.0 (CAS# 109-99-9)

Flammable Limits (Upper) (%v/v): 11.8 (CAS# 109-99-9)

129 (mmHg) @ (20°C) (CAS# 109-99-9)

2.4 (Air = 1) (CAS# 109-99-9)

# SAFETY DATA SHEET

## QA-600 Adhesive Part A

### ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Relative density	0.9 (H <sub>2</sub> O = 1) (Mixture)
Solubility(ies)	> 50% (Water) (Mixture)
Partition coefficient: n-octanol/water	0.45 log Pow (25 °C) (CAS# 109-99-9)
Auto-ignition temperature	321 °C (CAS# 109-99-9)
Decomposition Temperature	Not available
Viscosity	Not available

#### Other information

Volatile Organic Compound Content (%)	58.3
Explosive properties	Not explosive. May form explosive peroxides.
Oxidising properties	Not oxidising.

### SECTION 10: STABILITY AND REACTIVITY

<b>Reactivity</b>	Stable under normal conditions. May form peroxides on prolonged storage if air is present.
<b>Chemical stability</b>	Stable under normal conditions.
<b>Possibility of hazardous reactions</b>	Highly flammable liquid and vapour. The vapour may be invisible, heavier than air and spread along ground. May form explosive peroxides. Contact with aliphatic amines will cause irreversible polymerization with considerable heat build-up. May polymerise on prolonged heating.
<b>Conditions to avoid</b>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep away from direct sunlight. Keep at a temperature not exceeding (°C): 32. Avoid contact with air. Avoid contact with heat and ignition sources and oxidizers. Avoid distillation to dryness, which can form explosive peroxides.
<b>Incompatible materials</b>	Oxidizing agents, Corrosive Substances, Reducing agent, Strong Acids and Alkalis. Mild steel. Reacts violently with - Oxidizing agents and Acids.
<b>Hazardous decomposition product(s)</b>	May decompose in a fire giving off toxic fumes. Carbon monoxide, Carbon dioxide, Phenolic and Explosive Peroxides.

### SECTION 11: TOXICOLOGICAL INFORMATION

#### Information on toxicological effects (Substances in preparations / mixtures)

<b>Acute toxicity - Ingestion</b>	Mixture: Acute Toxicity (oral), Category 4; Harmful if swallowed. Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 500 mg/kg bw/day.
	Tetrahydrofuran Acute Toxicity (oral), Category 4; Harmful if swallowed. Test Result: LD50 <1 mg/kg bw (Standard acute method) (Unnamed publication, 1971).
<b>Acute toxicity - Inhalation</b>	Mixture: Based upon the available data, the classification criteria are not met. Acute Toxicity Estimate Mixture Calculation: Estimated LC50 >20.0 mg/l.
<b>Acute toxicity - Skin Contact</b>	Mixture: Based upon the available data, the classification criteria are not met. Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 2000 mg/kg bw/day.
<b>Skin corrosion/irritation</b>	Mixture: Based upon the available data, the classification criteria are not met.
<b>Serious eye damage/irritation</b>	Mixture: Eye irritation, Category 2; Causes serious eye irritation.
	Tetrahydrofuran Eye irritation, Category 2; Causes eye irritation. (SCL ≥ 25%). EU Harmonised Classification. Test Result: Corrosive to eyes. (rabbit) (Unnamed publication, 1971).
	Formaldehyde, polymer with 2-(chloromethyl)oxirane and 4,4'-(1- ethylethylidene)bis[phenol] Eye irritation, Category 2; Causes eye irritation. EU classification and labelling inventory (88 Notifiers) No data available
<b>Respiratory or skin sensitization</b>	Mixture: Skin sensitizer, Category 1; May cause an allergic skin reaction.

# SAFETY DATA SHEET



## QA-600 Adhesive Part A

[www.vpgsensors.com](http://www.vpgsensors.com)

Date of issue: 17 February 2022  
Date of First Issue: 11 October 2012  
Version: 3.0

### ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Formaldehyde, polymer with 2-(chloromethyl)oxirane and 4,4'-(1- ethylethylidene)bis[phenol]	Skin sensitizer, Category 1; May cause an allergic skin reaction. No data available
<b>Germ cell mutagenicity</b>	Mixture: Based upon the available data, the classification criteria are not met.
<b>Carcinogenicity</b>	Mixture: Carcinogen, Category 2; Suspected of causing cancer.
Tetrahydrofuran	Carcinogen, Category 2; Suspected of causing cancer. EU Harmonised Classification. Test Result: NOAEC 1800 ppm Suspected carcinogen (Unnamed, 1998)
<b>Reproductive toxicity</b>	Mixture: Based upon the available data, the classification criteria are not met.
<b>STOT - single exposure</b>	Mixture: STOT-single exposure, Category 3; May cause respiratory irritation. STOT-single exposure, Category 3; May cause drowsiness or dizziness.
Tetrahydrofuran	STOT-single exposure, Category 3; May cause respiratory irritation. (SCL ≥ 25%). EU Harmonised Classification. STOT-single exposure, Category 3; May cause drowsiness or dizziness. Test Result: Irritation to respiratory tract (Rat), LC50: 375mg/L air (Unnamed publication, 1979). Test Result: Central nervous depression, NOEC (rats): 500ppm (Malley et al, 2001)
<b>STOT - repeated exposure</b>	Mixture: Based upon the available data, the classification criteria are not met.
<b>Aspiration hazard</b>	Mixture: Based upon the available data, the classification criteria are not met.
<b>Information on likely routes of exposure</b>	
Inhalation	Possible – accidental exposure
Ingestion	Unlikely – accidental exposure
Skin Contact	Possible – accidental exposure
Eye Contact	Unlikely – accidental exposure
<b>Early onset symptoms related to exposure</b>	Harmful if swallowed. May cause an allergic skin reaction. Causes serious eye damage. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness.
<b>Delayed health effects from exposure</b>	Suspected of causing cancer.
<b>Other information</b>	
NTP Report on Carcinogens	Not listed
IARC Monographs	Tetrahydrofuran: Group 2B.
OSHA Designated Carcinogen	Not listed

### SECTION 12: ECOLOGICAL INFORMATION

<b>Ecotoxicity</b>	Based upon the available data, the classification criteria are not met. Estimated Mixture LC50 >100 mg/l (Fish)
<b>Persistence and degradability</b>	This product is readily biodegradable in water.
<b>Bioaccumulative potential</b>	The product has low potential for bioaccumulation.
<b>Mobility in soil</b>	The product is predicted to have high mobility in soil. (Water Soluble)
<b>Other adverse effects</b>	None known.

### SECTION 13: DISPOSAL CONSIDERATIONS

<b>Waste treatment methods</b>	Dispose of this material and its container as hazardous waste. Send after pre-treatment to a appropriate hazardous waste incinerator facility according to legislation. Dispose of contents in accordance with local, state or national legislation.
--------------------------------	--

### SECTION 14: TRANSPORT INFORMATION

ADR/RID                      IMDG                      IATA

# SAFETY DATA SHEET



## QA-600 Adhesive Part A

[www.vpgsensors.com](http://www.vpgsensors.com)

Date of issue: 17 February 2022  
Date of First Issue: 11 October 2012  
Version: 3.0

### ACCORDING TO OSHA HCS (29 CFR 1910.1200)

<b>UN number</b>	UN 1133	UN 1133	UN 1133
<b>UN proper shipping name</b>	ADHESIVES containing flammable liquid	ADHESIVES containing flammable liquid	ADHESIVES containing flammable liquid
<b>Transport hazard class(es)</b>	3	3	3
<b>Packing group</b>	II	II	II
<b>Environmental hazards</b>	Not classified	Not classified as a Marine Pollutant.	Not classified
<b>Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code</b>	See Section: 2		
<b>Special precautions for user</b>	Not applicable.		

### SECTION 15: REGULATORY INFORMATION

#### Safety, health and environmental regulations/legislation specific for the substance or mixture

##### US Federal Regulations

TSCA (Toxic Substance Control Act)

Tetrahydrofuran: Listed  
Formaldehyde, polymer with 2-(chloromethyl)oxirane and 4,4'-(1-ethylethylidene)bis[phenol]: Listed

EPCRA/ SARA 302 - Extremely Hazardous Substances

Not listed

SARA Title III Section 313 Toxic Release Inventory

Not listed

NIOSH Occupational Carcinogen List

Not listed

OSHA (List of Highly Hazardous Chemicals, Toxics and Reactives)

Not listed

NTP Report on Carcinogens

Not listed

Poison Prevention Packaging Act

Not listed

##### US State Regulations

California Proposition 65 list of chemicals

Tetrahydrofuran: Listed (Listing by the Labour Code mechanism, Group member list: 2-Ethylhexyl acrylate, Methy acrylate, Trimethylolpropane triacrylate)

California State Safer Consumer Products Regulations

Not listed

Maine State, Toxic Chemicals in Children's Products Act

Not listed

New Jersey State Worker and Community RTK Act

Tetrahydrofuran: Listed

Pennsylvania State, Worker and Community RTK Act

Tetrahydrofuran: Listed

Rhode Island State, Hazardous Substances RTK Act

Tetrahydrofuran: Listed

##### Non-Regional

IARC Monographs - List of Classifications

Tetrahydrofuran: Group 2B.

### SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: Updated substance / mixture classification. New SDS Regulation Hazcom 2012 format, all sections have been updated to include new information. Please review SDS with care.

<b>Version</b>	3.0
<b>Revision date</b>	17 February 2022
<b>Date of First Issue</b>	11 October 2012

#### References:

Existing Safety Data Sheet (SDS).

EU Data: Existing ECHA registration(s) and Harmonised Classification(s) for Tetrahydrofuran (CAS No. 109-99-9) and EU classification and labelling inventory for Formaldehyde, polymer with 2-(chloromethyl)oxirane and 4,4'-(1- ethylethylidene)bis[phenol] (CAS No. 28906-96-9)

#### Literature References:

1. Malley, L.A., Christoph G.R., Stadler, J.C., Hansen, J.F., Biesemeir, J.A. and Jasti, S. (2001). Acute and subchronic neurotoxicology evaluation of tetrahydrofuran by inhalation in rats. Drug Chem. Toxicol., 24(3): 201-219

GHS Classification of the substance or mixture	Classification Procedure
Flammable Liquid, Category 2	Flash Point Test Result
Acute Toxicity - Oral, Category 4	Acute Toxicity Estimate (ATE) Calculation.



# SAFETY DATA SHEET



## QA-600 Adhesive Part A

[www.vpgsensors.com](http://www.vpgsensors.com)

Date of issue: 17 February 2022  
Date of First Issue: 11 October 2012  
Version: 3.0

### ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Skin Sensitizer, Category 1	Threshold Calculation
Eye Irritation, Category 2	Threshold Calculation
STOT, Single Exposure, Category 3 - Respiratory Tract Irritation	Threshold Calculation
STOT, Single Exposure, Category 3 - Narcotic Effects	Threshold Calculation
Carcinogen, Category 2	Threshold Calculation

#### LEGEND

ACGIH	American Conference of Governmental Industrial Hygienists
ADR/RID	European Agreement concerning the International Carriage of Dangerous Goods by Road/ Regulations concerning the International Carriage of Dangerous Goods by Rail
CAS	Chemical Abstracts Service
EC	European Community
EU	European Union
ICAO/IATA	International Civil Aviation Organization / International Air Transport Association
IMDG	International Maritime Dangerous Goods
IARC	International Agency for Research on Cancer
NIOSH	National Institute for Occupational Safety & Health
NOAEC	No observed adverse effect concentration
NTP	National Toxicology Program
OSHA	Occupational Safety & Health Administration
PEL	Permissible Exposure Limit
REL	Recommended exposure limit
SCL	Specific Concentration Limit
STEL	Short-term Exposure Limit
TLV	Threshold Limit Value
TSCA	Toxic Substance Control Act
TWA	Time Weighted Average
UN	United Nations

Training advice: Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required.

#### Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Vishay Precision Group gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Vishay Precision Group accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

## Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "VPG"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify VPG's terms and conditions of purchase, including but not limited to, the warranty expressed therein.

VPG makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. **To the maximum extent permitted by applicable law, VPG disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.**

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on VPG's knowledge of typical requirements that are often placed on VPG products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. You should ensure you have the current version of the relevant information by contacting VPG prior to performing installation or use of the product, such as on our website at [vpgsensors.com](http://vpgsensors.com).

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of VPG.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling VPG products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify VPG for any damages arising or resulting from such use or sale. Please contact authorized VPG personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Copyright Vishay Precision Group, Inc., 2014. All rights reserved.