

Safety Data Sheet

M-Line 361A-20R Solder



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP)
& 2020/878

www.vpgsensors.com
Date of issue: 06/12/2022
Date of First Issue: 07/08/2012
Version 5.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier		
Product name	M-Line 361A-20R Solder	
Product code	Not applicable	
Unique Formula Identifier (UFI)	Not applicable	
Nanoform	The product does not contain nanoparticles.	
1.2 Relevant identified uses of the substance or mixture and uses advised against		
Identified Use(s)	PC38 Welding and soldering products (with flux coatings or flux cores.), flux products. For professional users only.	
Uses advised against	None Known	
1.3 Details of the supplier of the safety data sheet		
Company Identification	VISHAY MEASUREMENTS GROUP GMBH Tatschenweg 1 74078 Heilbronn Deutschland	
Telephone	+49 (0) 7131 39099-0	
Fax	+49 (0) 7131 39099-229	
E-mail (competent person)	mm.de@vpgsensors.com	
1.4 Emergency telephone number		
National Poisons Information Service (United Kingdom)	+44 (0) 3448 920111	24 hr. emergency phone number Healthcare Professionals ONLY Members of Public CHEMTREC (24 hours)
NHS 24	111	
Emergency Phone No.	(00-1) 703-527-3887	
Languages spoken	All official European languages.	

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture		
2.1.1 Regulation (EC) No. 1272/2008 (CLP)	Skin Sens. 1; H317 Repr. 1A; H360FD Lact.; H362 STOT RE 1; H372	
2.2 Label elements		
Product name	M-Line 361A-20R Solder	
Hazard Pictogram(s)	 	
Signal Word(s)	DANGER	
Contains:	Lead (Massive form) and Rosin	
Hazard Statement(s)	H317: May cause an allergic skin reaction. H360FD: May damage fertility. May damage the unborn child. H362: May cause harm to breast-fed children.	

Safety Data Sheet

M-Line 361A-20R Solder

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP)
& 2020/878

www.vpgsensors.com
Date of issue: 06/12/2022
Date of First Issue: 07/08/2012
Version 5.0

Precautionary Statement(s)

H372: Causes damage to organs through prolonged or repeated exposure.

P201: Obtain special instructions before use.
P260: Do not breathe fume.
P263: Avoid contact during pregnancy and while nursing.
P280: Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P302+P352: IF ON SKIN: Wash with plenty of water.
P308+P313: IF exposed or concerned: Get medical advice/attention.

Supplemental information

None assigned

2.3 Other hazards

None

SECTION 3: Composition/information on ingredients

3.1 Substances - not applicable.

3.2 Mixtures

EC Classification Regulation (EC) No. 1272/2008 (CLP)

Chemical identity of the substance	%W/W	CAS No.	EC No.	REACH Registration No.	Hazard classification
Lead Massive form	35 - 40	7439-92-1	231-100-4	Not yet assigned in the supply chain	Repr. 1A; H360FD Lact.; H362 STOT RE 1; H372
Rosin	1 - 5	8050-09-7	232-475-7	Not yet assigned in the supply chain	Skin Sens. 1; H317

Note: For full text of H phrases see section 16.

SECTION 4: First aid measures



4.1 Description of first aid measures
Self-protection of the first aider

No action should be taken involving personal risk. Wear appropriate personal protective equipment, avoid direct contact. Wear suitable respiratory protective equipment if exposure to high levels of material are likely. Avoid contact with skin. Do not breathe fumes. Remove contaminated clothing.

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Apply artificial respiration if breathing has ceased or shows signs of failing. IF exposed or concerned: Get medical advice/attention.

Skin contact

IF ON SKIN: Remove contaminated clothing and wash all affected areas with plenty of water. Contaminated clothing should be thoroughly cleaned. If skin irritation or rash occurs: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention.

Eye contact

Molten material can cause severe burns. Do NOT try to peel molten material from the skin. Cool rapidly with water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if eye irritation develops or persists.

Ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. Get medical advice/attention if you feel unwell.

Safety Data Sheet

M-Line 361A-20R Solder

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP)
& 2020/878

www.vpgsensors.com
Date of issue: 06/12/2022
Date of First Issue: 07/08/2012
Version 5.0

- 4.2 Most important symptoms and effects, both acute and delayed** May cause an allergic skin reaction. May damage fertility. May damage the unborn child. May cause harm to breast-fed children. Causes damage to organs through prolonged or repeated exposure.
Flux fumes during soldering may cause irritation and damage of mucous membranes and respiratory system. Smoke produced during soldering will contain rosin which is an allergen and can cause pulmonary irritation and damage. High atmospheric concentrations may lead to adverse effects on the central nervous system and anaesthetic effects, including drowsiness, giddiness, headache, nausea and unconsciousness. Lead is a cumulative poison and continuous exposure to small amounts over time can raise the body's content to toxic levels. Symptoms of lead poisoning include abdominal pain, nausea, vomiting and headache. May cause gastrointestinal tract irritation if s Molten material can cause severe burns.
- 4.3 Indication of any immediate medical attention and special treatment needed** Treat symptomatically.
If thought to be overexposed, the person should have a blood-lead analysis done. Patient should be kept under medical observation for at least 48 hours.
When molten: In case of burns immediately cool affected skin as long as possible with cold water.
- Notes to a physician:**

SECTION 5: Firefighting measures

- 5.1 Extinguishing media**
Suitable extinguishing media As appropriate for surrounding fire.
Unsuitable extinguishing media Do not use water on fires when molten metal is present.
- 5.2 Special hazards arising from the substance or mixture** Flux in cored solder may ignite when the solder melts in a fire. When heated to soldering temperatures, the solvent in the flux will boil away and carry up droplets of rosin and thermal degradation products such as aliphatic aldehydes, acids and terpenes. No lead or antimony are detected in fumes from soldering below 537°C. Melted solder may liberate carbon monoxide, carbon dioxide, lead oxide fumes.
- 5.3 Advice for firefighters** Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Do not breathe fumes. Keep containers cool by spraying with water if exposed to fire. Avoid run off to waterways and sewers.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures** Ensure adequate ventilation Use personal protective equipment as required. See Section: 8. Avoid all contact. Avoid breathing smoke fumes during soldering. Melted solder will solidify on cooling and can be scraped up. Use caution to avoid breathing fumes if a gas torch is used to cut up large pieces.
- 6.2 Environmental precautions** Avoid release to the environment. Do not allow to enter drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be alerted to the Environment Agency or other appropriate regulatory body.
- 6.3 Methods and material for containment and cleaning up** Ensure suitable personal protection during removal of spillages. Allow product to cool/solidify and pick up as a solid. Transfer to a container for disposal. Recover or recycle if possible. Dispose of this material and its container as hazardous waste
- Large spillages:** Ensure adequate ventilation Use personal protective equipment as required. See Section: 8. Avoid all contact. Melted solder will solidify on cooling and can be scraped up. Avoid breathing smoke fumes during soldering. Use caution to avoid breathing fumes if a gas torch is used to cut up large pieces.
- 6.4 Reference to other sections** See Section: 8, 13

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Ensure adequate ventilation Avoid all contact. Avoid breathing smoke fumes during soldering. Use caution to avoid breathing

Safety Data Sheet

M-Line 361A-20R Solder

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

www.vpgsensors.com
Date of issue: 06/12/2022
Date of First Issue: 07/08/2012
Version 5.0

7.2 Conditions for safe storage, including any incompatibilities

storage temperature
Storage life
Incompatible materials

fumes if a gas torch is used to cut up large pieces. Use personal protective equipment as required. See Section: 8. Do not eat, drink or smoke when using this product. Wash hands before breaks and after work.
When molten: Keep from any possible contact with water.
Store in a well-ventilated place.

Ambient
Stable under normal conditions
Store away from sources of sulfur. Keep away from: Strong Acids, Alkalis, Chlorine and Strong oxidising agents. Use of strong acid fluxes may result in liberation of toxic lead chloride fumes.

7.3 Specific end use(s)

See Section: 1.2.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

8.1.1 Occupational exposure limits

United Kingdom

SUBSTANCE	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m ³)	STEL (ppm)	STEL (mg/m ³)	Note
Tin (inorganic compounds as Sn)	-	-	2	-	-	-
Rosin-based solder flux fume	8050-09-7	-	0.05	-	0.15	Sen
Lead and its compounds	7439-92-1	-	0.15	-	-	-
Antimony and compounds except stibine (as Sb)	7440-36-0	-	0.5	-	-	-

Source: UK WEL: Workplace Exposure Limit (UK HSE EH40)

Notes:

Sen: Capable of causing occupational asthma.

Ireland

SUBSTANCE	CAS No.	Occupational Exposure Limit Value (8-hour reference period)		Occupational Exposure Limit Value (15-minute reference period)		Notes
		ppm	mg/m ³	ppm	mg/m ³	
Tin, as Sn Metal	7440-31-5	-	2	-	-	IOELV
Rosin core solder pyrolysis products - (as airborne total resin acid)	-	-	0.05	-	0.15	Sens.
Lead and its compounds	7439-92-1	-	0.15	-	-	Repr 1A, BOELV
Antimony and compounds	7440-36-0	-	0.5	-	-	-

Source: 2021 Code of Practice for Safety, Health and Welfare at Work (Chemical Agents) Regulation (2001 – 2021) and the Safety, Health and Welfare at Work (Carcinogens) Regulations (2001 – 2019); Health and Safety Authority

Notes:

BOELV: binding occupational exposure limit values

Sens: Sensitizer

8.1.2 Biological Limit Value

United Kingdom: The Control of Lead at Work Regulations SI 2002/2676

In accordance with SI 2002/2676: 2. (1) In these Regulations: "action level" means a blood-lead concentration of:

Safety Data Sheet

M-Line 361A-20R Solder

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP)
& 2020/878

www.vpgsensors.com
Date of issue: 06/12/2022
Date of First Issue: 07/08/2012
Version 5.0

(a) in respect of a woman of reproductive capacity, 25 µg/dl;
(b) in respect of a young person, 40 µg/dl; or
(c) in respect of any other employee, 50 µg/dl
"suspension level" means - (a) a blood-lead concentration of –
(i) in respect of a woman of reproductive capacity, 30 µg/dl
(ii) in respect of a young person, 50 µg/dl, or
(iii) in respect of any other employee, 60 µg/dl; or
(b) a urinary lead concentration of –
(i) in respect of a woman of reproductive capacity, 25 µg Pb/g creatinine,
or (ii) in respect of any other employee, 110 µg Pb/g creatinine;

8.1.3 PNECs and DNELs

Not established

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure adequate ventilation Or Use appropriate containment. Atmospheric levels should be controlled in compliance with the occupational exposure limit. Local exhaust recommended.

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable. Avoid all contact. Avoid breathing smoke fumes during soldering. Use caution to avoid breathing fumes if a gas torch is used to cut up large pieces. Wash hands before breaks and after work. Keep work clothes separately. Contaminated clothing should be thoroughly cleaned. Do not eat, drink or smoke at the work place.

Protective clothing should be selected specifically for the working place, depending on concentration and quantity of the hazardous substances handled. The resistance of the protective clothing to chemicals should be ascertained with the respective supplier.

Eye / face protection



Wear eye protection with side protection (EN166).

Skin protection



Hand protection:

Wear impervious gloves (EN374). Gloves should be changed regularly to avoid permeation problems. Breakthrough time of the glove material: refer to the information provided by the gloves' producer.

Hot/molten product: Use gloves with insulation for thermal protection, when needed.

Body protection:

Wear impervious protective clothing, including boots, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Hot/molten product: Wear flameproof clothing.

Respiratory protection



In case of inadequate ventilation wear respiratory protection. A suitable mask with filter type A (EN141 or EN405) may be appropriate. Recommended: Dust mask/ Half-face mask (DIN EN 140), Filter type: P2

Thermal hazards

Hot/molten product: Wear appropriate personal protective equipment, avoid direct contact.

8.2.3 Environmental exposure controls

Avoid release to the environment. Do not allow to enter drains, sewers or watercourses.

Safety Data Sheet

M-Line 361A-20R Solder

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP)
& 2020/878

www.vpgsensors.com
Date of issue: 06/12/2022
Date of First Issue: 07/08/2012
Version 5.0

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	solid (metal in wire form)
Colour	silver - grey
Odour	Not available
Melting point and freezing point	Not available
Boiling point or initial boiling point and boiling range	Not available
Flammability	Not available
Lower and upper explosion limit or lower and upper flammability limit	not applicable - solid
Flash point	not applicable - solid
Auto-ignition temperature	Not available
Decomposition temperature	Not available
pH	Not available
Kinematic viscosity	not applicable - solid
Solubility	Insoluble in water
Partition coefficient: n-octanol/water (log value)	Not available
Vapour pressure	Not available
Density and/or relative density	>1 (H ₂ O = 1)
Relative vapour density	not applicable - solid
Particle characteristics	Not available

9.2 Other information

Explosive properties	Not explosive.
Oxidising properties	Not oxidising.

SECTION 10: Stability and reactivity

10.1 Reactivity	Stable under normal conditions
10.2 Chemical stability	Stable under normal conditions Hazardous polymerisation will not occur.
10.3 Possibility of hazardous reactions	Flux in cored solder may ignite when the solder melts in a fire. Reacts vigorously with chlorine and oxidising agents. Use of strong acid fluxes may result in liberation of toxic lead chloride fumes.
10.4 Conditions to avoid	When molten: Keep from any possible contact with water.
10.5 Incompatible materials	Keep away from: Strong Acids, Alkalis, Chlorine and Strong oxidising agents. Store away from sources of sulfur.
10.6 Hazardous decomposition products	When heated to soldering temperatures, the solvent in the flux will boil away and carry up droplets of rosin and thermal degradation products such as aliphatic aldehydes, acids and terpenes. No lead or antimony are detected in fumes from soldering below 537°C. Melted solder may liberate carbon monoxide, carbon dioxide, lead oxide fumes.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Ingestion	Mixture: Acute Tox. 4; H302: Harmful if swallowed. Acute Toxicity Estimate Mixture Calculation: estimated estimated LD50 >300 - ≤2000 mg/kg bw/day
Inhalation	Based upon the available data, the classification criteria are not met. Acute Toxicity Estimate Mixture Calculation: estimated LC50 > 5 mg/L. (dust/mist)
Skin contact	Mixture: Based upon the available data, the classification criteria are not met. Acute Toxicity Estimate Mixture Calculation: estimated LD50 > 2000 mg/kg bw/day
Skin corrosion/irritation	Mixture: Based upon the available data, the classification criteria are not met.
Serious eye damage/irritation	Mixture: Based upon the available data, the classification criteria are not met.

Safety Data Sheet

M-Line 361A-20R Solder

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP)
& 2020/878

www.vpgsensors.com
Date of issue: 06/12/2022
Date of First Issue: 07/08/2012
Version 5.0

Respiratory or skin sensitisation	Mixture: Skin Sens. 1; H317: May cause an allergic skin reaction.
	Rosin Skin Sens. 1: May cause an allergic skin reaction. Harmonised Classification Sensitisation (guinea pig) - Negative, ECHA Registration Endpoint summary
Germ cell mutagenicity	Mixture: Based upon the available data, the classification criteria are not met.
Carcinogenicity	Mixture: Based upon the available data, the classification criteria are not met.
Reproductive toxicity	Mixture: Repr. 1A: H360FD: May damage fertility. May damage the unborn child. Mixture: Lact. H362: May cause harm to breast-fed children.
	lead Massive form Repr. 1A: H360FD: May damage fertility. May damage the unborn child. Specific concentration limit: C ≥ 0.03 %. Harmonised Classification Lact. H362: May cause harm to breast-fed children. Harmonised Classification ECHA Registration Endpoint summary: Adverse effects observed: oral intake and inhalation intake. NOAEL (Weight of evidence approach) µg/dL : 30.
STOT - single exposure	Mixture: Based upon the available data, the classification criteria are not met.:
STOT - repeated exposure	Mixture: STOT RE 1; H372: Causes damage to organs through prolonged or repeated exposure:
	lead Massive form STOT RE 1; H372: Causes damage to organs through prolonged or repeated exposure: ECHA Registration Endpoint summary: Adverse effects observed central nervous system, Cardiovascular system/Blood circulatory system , urogenital
Aspiration hazard	Mixture: Based upon the available data, the classification criteria are not met.
11.2 Information on other hazards	
11.2.1 Endocrine disrupting properties	This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.
11.2.2 Other information	None

SECTION 12: Ecological information

12.1 Toxicity	Based upon the available data, the classification criteria are not met. estimated Mixture LC50 >100 mg/L (Fish)
12.2 Persistence and degradability	No data for the mixture as a whole.
	lead (Massive form) Not applicable for inorganic substances.
	Rosin Readily biodegradable. ECHA Registration Endpoint summary
12.3 Bioaccumulative potential	No data for the mixture as a whole.
	lead (Massive form) The substance has potential for bioaccumulation. Bioconcentration factor (BCF) freshwater: 1533L/kg wet weight
	Rosin The product is predicted to have low potential for bioaccumulation Bioconcentration factor (BCF): Fish <25 - 130L/kg mussels 110 – 330 l/kg. Weight of evidence approach. ECHA registration dossier
12.4 Mobility in soil	No data for the mixture as a whole.
	lead (Massive form) The substance is predicted to have low mobility in soil. Partition Coefficient: Log Kdsoil): 3.8 L/kg . Weight of evidence approach. ECHA Registration Endpoint summary
	Rosin The substance is predicted to have low mobility in soil. Slightly soluble in: Water Log Koc: 0.88 – 5.37 l/kg. Read across / (Q)SAR. ECHA registration dossier
12.5 Results of PBT and vPvB assessment	Not classified as PBT or vPvB.
12.6 Endocrine disrupting properties	This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.
12.7 Other adverse effects	None known

SECTION 13: Disposal considerations

13.1 Waste treatment methods	Solder can be reclaimed. This material and its container must be disposed of as hazardous waste. Dispose of wastes in an approved waste disposal facility. Disposal of electrical waste must be in accordance with the Waste Electrical and Electronic Equipment Directive (WEEE Directive, 2012/19/EU).
13.2 Additional information	Dispose of contents in accordance with local, state or national legislation.

Safety Data Sheet

M-Line 361A-20R Solder

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

www.vpgsensors.com
Date of issue: 06/12/2022
Date of First Issue: 07/08/2012
Version 5.0

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA/ICAO
14.1 UN number or ID number	Not classified	Not classified	Not classified	Not classified
14.2 UN proper shipping name	Not classified	Not classified	Not classified	Not classified
14.3 Transport hazard class(es)	Not classified	Not classified	Not classified	Not classified
14.4 Packing group	Not classified	Not classified	Not classified	Not classified
14.5 Environmental hazards	Not classified	Not classified	Not classified as a Marine Pollutant.	Not classified
14.6 Special precautions for user	See Section: 2			
14.7 Maritime transport in bulk according to IMO instruments	Not applicable	Not applicable	Not applicable	Not applicable
14.8 Additional information	Not applicable			

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture	
15.1.1 EU regulations	Lead concentrations in electrical equipment are controlled by Directive 2002/95/EC (commonly referred to as the Restriction of Hazardous Substances Directive or RoHS) and recast Directive 2011/65/EU.
Use restriction according to REACH annex XVII, no.:	lead: REACH: Annex XVII Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles. Entry number: 63.
Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]	not applicable
Restrictions of occupation:	Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
To follow:	Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work
15.1.2 National regulations	
Germany	
Water hazard class (WGK)	Water hazard class: 1 (Self classification)
15.2 Chemical Safety Assessment	A REACH chemical safety assessment has not been carried out.

SECTION 16: Other information

The following sections contain revisions or new statements: New SDS Regulation 2020/878 format, all sections have been updated to include new information. Please review SDS with care.

Existing Safety Data Sheet (SDS).

Harmonised Classification(s) for and Existing ECHA registration(s) for lead (Massive form) (CAS No. 7439-92-1) and Rosin (CAS No. 8050-09-7).

EU Classification: This Safety Data Sheet was prepared in accordance with EC Regulation (EC) 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

Safety Data Sheet

M-Line 361A-20R Solder

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP)
& 2020/878

www.vpgsensors.com
Date of issue:06/12/2022
Date of First Issue: 07/08/2012
Version 5.0

Classification of the substance or mixture According to Regulation (EC) No. 1272/2008 (CLP)	Classification procedure
Skin Sens. 1; H317	Threshold Calculation
Repr. 1A; H360FD	Threshold Calculation
Lact.; H362	Threshold Calculation
STOT RE 1; H372	Threshold Calculation

Legend

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
BCF	Bioconcentration factor (BCF)
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
DNEL	Derived no effect level
EU	European Union
EC	European Community
ECHA	European Chemicals Agency
EN	European Standard
IATA	International Air Transport Association
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
LC50	Lethal concentration at which 50% of the population is killed
LD50	Lethal dose at which 50% of the population is killed
LTEL	Long term exposure limit
NOAEC	No observed adverse effect concentration
NOEC	No Observed Effect Concentration
OECD	Organisation for Economic Cooperation and Development
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
TWA	Time Weighted Average
STEL	Short term exposure limit
vPvB	very Persistent and very Bioaccumulative
UK	United Kingdom
UN	United Nations

Hazard classification / Classification code:

Skin Sens. 1; Skin Sensitisation, Category 1	Hazard Statement(s) H317: May cause an allergic skin reaction.
Repr. 1A; Reproductive toxicity , Category 1A	H360FD: May damage fertility. May damage the unborn child.
Lact.; Effects on or via lactation	H362: May cause harm to breast-fed children.
STOT RE 1; Specific target organ toxicity — repeated exposure, Category 1	H372: Causes damage to organs through prolonged or repeated exposure.

Training advice: Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required.

Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. VISHAY MEASUREMENTS GROUP GMBH gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. VISHAY MEASUREMENTS GROUP GMBH accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "VPG"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify VPG's terms and conditions of purchase, including but not limited to, the warranty expressed therein.

VPG makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. **To the maximum extent permitted by applicable law, VPG disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.**

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on VPG's knowledge of typical requirements that are often placed on VPG products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. You should ensure you have the current version of the relevant information by contacting VPG prior to performing installation or use of the product, such as on our website at vpgsensors.com.

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of VPG.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling VPG products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify VPG for any damages arising or resulting from such use or sale. Please contact authorized VPG personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Copyright Vishay Precision Group, Inc., 2014. All rights reserved.