

SAFETY DATA SHEET

M-LINE GC-6 Isopropyl Alcohol



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP)
& 2020/878

www.vpgsensors.com
Date of issue: 06/01/2023
Date of First Issue: 07/08/2012
Version 3.0

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier		
Product Name	M-LINE GC-6 Isopropyl Alcohol	
Product Code	Not applicable	
Unique Formula Identifier (UFI)	Not applicable	
Nanoform	The product does not contain nanoparticles.	
1.2 Relevant identified uses of the substance or mixture and uses advised against		
Identified Use(s)	PC14 Metal surface treatment products, including galvanic and electroplating products	
Uses Advised Against	None Known	
1.3 Details of the supplier of the safety data sheet		
Company Identification	VISHAY MEASUREMENTS GROUP GMBH Tatschenweg 1 74078 Heilbronn Deutschland	
Telephone	+49 (0) 7131 39099-0	
Fax	+49 (0) 7131 39099-229	
E-Mail (competent person)	mm.de@vpgsensors.com	
1.4 Emergency telephone number		
National Poisons Information Service (United Kingdom)	+44 (0) 3448 920111	24 hr. emergency phone number Healthcare Professionals ONLY Members of Public CHEMTREC (24 hours)
NHS 24	111	
Emergency Phone No.	(00-1) 703-527-3887	
Languages spoken	All official European languages.	

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture		
2.1.1 Regulation (EC) No. 1272/2008 (CLP)	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	
2.2 Label elements		
Product Name	M-LINE GC-6 Isopropyl Alcohol	
Hazard Pictogram(s)	 	
Signal Word(s)	DANGER	
Contains:	Propan-2-ol	
Hazard Statement(s)	H225: Highly flammable liquid and vapour. H319: Causes serious eye irritation. H336: May cause drowsiness or dizziness.	

SAFETY DATA SHEET

M-LINE GC-6 Isopropyl Alcohol

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP)
& 2020/878

www.vpgsensors.com
Date of issue: 06/01/2023
Date of First Issue: 07/08/2012
Version 3.0

Precautionary Statement(s)

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233: Keep container tightly closed.
P235: Keep cool.
P370+P378: In case of fire: Use dry powder to extinguish.
P403+P235: Store in a well-ventilated place. Keep cool.
P501: Dispose of contents in accordance with local, state or national legislation.

Supplemental information

None assigned

2.3 Other hazards

Vapours can form explosive mixtures with air.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances - Not applicable.

EC Classification Regulation (EC) No. 1272/2008 (CLP)

SUBSTANCE	CAS No.	EC No.	REACH Registration No.	%W/W
Propan-2-ol	67-63-0	200-661-7	Not yet assigned in the supply chain	≤100

3.2 Mixtures - Not applicable

Note: For full text of H phrases see section 16.

SECTION 4: FIRST AID MEASURES



4.1 Description of first aid measures

Self-protection of the first aider

Avoid breathing mist/vapours/spray. Ensure adequate ventilation. Wear suitable protective clothing. Wear suitable respiratory protective equipment if exposure to high levels of material are likely. Avoid contact with skin. Contaminated clothing should be laundered before reuse. Do not use mouth-to-mouth resuscitation. Eyewash facilities should be stationed close to workplace where possible.

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

Skin Contact

IF ON SKIN: Gently wash with plenty of soap and water. Remove contaminated clothing and wash clothing before reuse. If irritation (redness, rash, blistering) develops, get medical attention.

Eye Contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion

IF SWALLOWED: Rinse mouth. Do not give anything by mouth to an unconscious person. Do NOT induce vomiting. If symptoms occur obtain medical attention.

4.2 Most important symptoms and effects, both acute and delayed

Causes serious eye irritation. May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable Extinguishing media

As appropriate for surrounding fire. Extinguish preferably with foam, carbon dioxide or dry chemical.

Unsuitable extinguishing media

Do not use water jet. Direct water jet may spread the fire.

SAFETY DATA SHEET

M-LINE GC-6 Isopropyl Alcohol

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP)
& 2020/878

www.vpgsensors.com
Date of issue: 06/01/2023
Date of First Issue: 07/08/2012
Version 3.0

- 5.2 Special hazards arising from the substance or mixture** Flammable liquid and vapour. Vapours can form explosive mixtures with air. Containers may explode when involved in a fire. Keep container(s) exposed to fire cool, by spraying with water. Thermal decomposition will evolve toxic and corrosive vapours: Carbon dioxide, Carbon monoxide lammable liquid and vapour. Vapours are heavier than air and may travel considerable distances to a source of ignition and flashback. Sealed containers may rupture explosively if hot.
- 5.3 Advice for fire-fighters** Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Do not breathe fumes. Keep containers cool by spraying with water if exposed to fire. Avoid run off to waterways and sewers.

SECTION 6: ACCIDENTAL RELEASE MEASURES

- 6.1 Personal precautions, protective equipment and emergency procedures** Ensure adequate ventilation. Stop leak if safe to do so. Eliminate all ignition sources if safe to do so. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing mist/vapours/spray. Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. See Section: 8. The vapour is heavier than air; beware of pits and confined spaces.
- 6.2 Environmental precautions** Avoid release to the environment. Do not allow to enter drains, sewers or watercourses.
- 6.3 Methods and material for containment and cleaning up** Ensure suitable personal protection during removal of spillages. Use non-sparking equipment when picking up flammable spill. Adsorb spillages onto sand, earth or any suitable adsorbent material. Do NOT absorb in saw-dust or other combustible absorbents. Transfer to a lidded container for disposal or recovery. Ventilate the area and wash spill site after material pick-up is complete. Dispose of this material and its container as hazardous waste. Allow small spillages to evaporate provided there is adequate ventilation.
- Large spillages:** Evacuate the area and keep personnel upwind. Notify police and fire brigade as soon as possible.
- 6.4 Reference to other sections** See Section: 8, 13

SECTION 7: HANDLING AND STORAGE

- 7.1 Precautions for safe handling** Ensure adequate ventilation. Avoid breathing mist/vapours/spray. Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. See Section: 8. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Do not use sparking tools. Do not spray on an open flame or other ignition source. Do not eat, drink or smoke when using this product. Wash hands before breaks and after work. Ground/bond container and receiving equipment.
- 7.2 Conditions for safe storage, including any incompatibilities** Store in a cool/low-temperature, well-ventilated (dry) place away from heat and ignition sources. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep away from direct sunlight. Do not reuse empty containers.
- Storage temperature: Store in a cool/low temperature. Keep at a temperature not exceeding (°C): 17.
- Storage life: Stable under normal conditions.
- Incompatible materials: Keep away from: Strong oxidising agents, Strong acids and alkali., Iron, Aluminium, Air, Halogens, Peroxides.
- 7.3 Specific end use(s)** See Section: 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

- 8.1 Control parameters**
8.1.1 Occupational Exposure Limits

United Kingdom

SAFETY DATA SHEET

M-LINE GC-6 Isopropyl Alcohol

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

www.vpgsensors.com
Date of issue: 06/01/2023
Date of First Issue: 07/08/2012
Version 3.0

SUBSTANCE	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m ³)	STEL (ppm)	STEL (mg/m ³)	Note
Propan-2-ol	67-63-0	400	999	500	1250	-

Source: UK WEL: Workplace Exposure Limit (UK HSE EH40)

Ireland

SUBSTANCE	CAS No.	Occupational Exposure Limit Value (8-hour reference period)		Occupational Exposure Limit Value (15-minute reference period)		Notes
		ppm	mg/m ³	ppm	mg/m ³	
Propan-2-ol	67-63-0	200	-	400	-	Sk

Source: 2021 Code of Practice for Safety, Health and Welfare at Work (Chemical Agents) Regulation (2001 – 2021) and the Safety, Health and Welfare at Work (Carcinogens) Regulations (2001 – 2019); Health and Safety Authority

Notations:

Sk: Can be absorbed through skin.

8.1.2 Biological limit value Not established.

8.1.3 PNECs and DNELs

Propan-2-ol Derived No Effect Level	Oral	Inhalation	Dermal
Worker - Long Term - Systemic effects	-	500 mg/m ³	888 mg/kg bw/day
Worker - Short Term (acute) - Systemic effects	-	1000 mg/m ³	-
Consumer - Long Term - Systemic effects	26 mg/kg bw/day	89 mg/m ³	319 mg/kg bw/day
Consumer - Short Term (acute) - Systemic effects	51 mg/kg bw/day	178 mg/m ³	

Propan-2-ol Predicted No Effect Concentration	Value
Aquatic Compartment	PNEC Aqua (marine water) 140.9 mg/l PNEC Aqua (freshwater) 140.9 mg/l PNEC freshwater sediment 552 mg/kg dw PNEC marine sediment 552 mg/kg dw
Soil	PNEC 28 Soil mg/kg dw
STP (Sewage Treatment Plant)	PNEC STP 2251 mg/l
Hazard for predators (Secondary Poisoning)	PNEC Oral 160 mg/kg food

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure adequate ventilation or use appropriate containment. Atmospheric levels should be controlled in compliance with the occupational exposure limit. Local exhaust recommended. Use non-sparking ventilation systems, approved explosion-proof equipment, and intrinsically safe electrical systems. Eyewash facilities should be stationed close to workplace where possible.

8.2.2 Individual protection measures, such as personal protective equipment (PPE)

Use personal protective equipment as required. Protective clothing should be selected specifically for the working place, depending on concentration and quantity of the hazardous substances handled. The resistance of the protective clothing to chemicals should be ascertained with the respective supplier. Wash contaminated clothing before reuse. Avoid contact with skin and eyes. Do not breathe vapour. Wash hands before breaks and after work. Do not eat, drink or smoke at the work place.

Protective clothing should be selected specifically for the working place, depending on concentration and quantity of the hazardous substances handled. The resistance of the protective clothing to chemicals should be ascertained with the respective supplier.

Eye/ face protection



Wear protective eye glasses for protection against liquid splashes. Wear eye protection with side protection (EN166).

SAFETY DATA SHEET

M-LINE GC-6 Isopropyl Alcohol

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP)
& 2020/878

www.vpgsensors.com
Date of issue: 06/01/2023
Date of First Issue: 07/08/2012
Version 3.0

Skin protection



Hand protection:

Wear impervious gloves (EN374). Nitrile rubber, Butyl rubber. Breakthrough time of the glove material: refer to the information provided by the gloves' producer. Recommended: Nitrile rubber, Butyl rubber. Unsuitable gloves materials: Natural rubber / PVC.

Respiratory protection



Body protection:

Wear dustproof working clothes. Wear impervious protective clothing, including boots, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Normally no personal respiratory protection is necessary. In case of inadequate ventilation wear respiratory protection. A suitable mask with filter type A (EN141 or EN405) may be appropriate.

Thermal hazards

Not applicable

8.2.3 Environmental exposure controls

Avoid release to the environment. Do not allow to enter drains, sewers or watercourses.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Physical state	Liquid
Colour	Blue
Odour	Alcohol-like.
Melting point and freezing point	-88.5 °C
Boiling point or initial boiling point and boiling range	82 °C
Flammability	Highly flammable liquid and vapour.
Lower and upper explosion limit or lower and upper flammability limit	Upper explosion limit: 12.0 Vol% Lower explosion limit: 2.0 Vol%
Flash point	11.7 °C
Auto-ignition temperature	399 °C
Decomposition temperature	Not established.
pH	Not established.
Kinematic viscosity	Not established.
Solubility	Soluble in water.
Partition coefficient: n-octanol/water (log value)	Not established.
Vapour pressure	6.02 kPa @ 25 °C
Density and/or relative density	0.88 g/cm ³
Relative vapour density	2.1 (Air = 1)
Particle characteristics	Not applicable - Liquid

9.2 Other information

Explosive properties	Not explosive. Vapours can form explosive mixtures with air.
Oxidising properties	Not oxidising.
Evaporation Rate	2.83 (BuAc = 1)
Viscosity	2.1 mPa · s @ 25 °C Dynamic viscosity

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity	Stable under normal conditions.
10.2 Chemical stability	Stable under normal conditions. Hazardous polymerisation will not occur.
10.3 Possibility of hazardous reactions	Highly flammable liquid and vapour. Vapour is explosive in air at temperatures higher than the flash point. Vapours are heavier than air and may travel considerable distances to a source of ignition and flashback.

SAFETY DATA SHEET

M-LINE GC-6 Isopropyl Alcohol

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP)
& 2020/878

www.vpgsensors.com
Date of issue: 06/01/2023
Date of First Issue: 07/08/2012
Version 3.0

10.4	Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep from direct sunlight. Do not spray on an open flame or other ignition source. Take precautionary measures against static discharge.
10.5	Incompatible materials	Flammable liquid, Oxidizing agents, Corrosive Substances, Alcohols, Strong Acids and Alkalis.
10.6	Hazardous decomposition product(s)	Decomposes in a fire giving off toxic fumes: Carbon monoxide, Carbon dioxide.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1	Information on hazard classes as defined in Regulation (EC) No 1272/2008	
	Acute toxicity	
	Ingestion	Based upon the available data, the classification criteria are not met. LD50 (oral, rat) mg/kg: 58400 (OECD 401)
	Inhalation	Based upon the available data, the classification criteria are not met. LC50 (inhalation, rat) mg/l/4h: 10000 (OECD 403)
	Skin Contact	Based upon the available data, the classification criteria are not met. LD50 (Dermal, (rabbit)) ml/kg bw 16.4 (OECD 402)
	Skin corrosion/irritation	Based upon the available data, the classification criteria are not met. Not irritating to skin (rabbit) ECHA registration dossier
	Serious eye damage/irritation	Eye Irrit. 2; Causes serious eye irritation. Irritating to eyes. (rabbit) (OECD 405) ECHA registration dossier
	Respiratory or skin sensitization	Based upon the available data, the classification criteria are not met. Skin sensitization: Sensitisation (guinea pig) - Negative (OECD 406) Respiratory sensitization: No data ECHA registration dossier
	Germ cell mutagenicity	Based upon the available data, the classification criteria are not met. In vitro: Negative (Chinese Hamster ovary) (OECD 476) In vivo: Negative (mouse) (OECD 474) ECHA registration dossier
	Carcinogenicity	Based upon the available data, the classification criteria are not met. NOEL 5000 ppm (OECD 451)
	Reproductive toxicity	Based upon the available data, the classification criteria are not met. Reproductive toxicity: NOAEL: 1000 mg/kg bw/day (OECD 416) Developmental toxicity: NOAEL: 596 mg/kg bw/day (OECD 414) ECHA registration dossier
	STOT - single exposure	STOT SE 3; May cause drowsiness or dizziness. Test Result: Higher concentrations can produce central nervous system depression, narcosis, and unconsciousness. (OECD 403) ECHA registration dossier
	STOT - repeated exposure	Based upon the available data, the classification criteria are not met.
	Aspiration hazard	Based upon the available data, the classification criteria are not met.
11.2	Information on other hazards	
11.2.1	Endocrine disrupting properties	This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.
11.2.2	Other information	None

SECTION 12: ECOLOGICAL INFORMATION

12.1	Toxicity	Based upon the available data, the classification criteria are not met. Estimated Mixture LC50 >100 mg/l (Fish)
12.2	Persistence and degradability	Readily biodegradable (according to OECD criteria).
12.3	Bioaccumulative potential	The substance has low potential for bioaccumulation. Log Pow < 3.
12.4	Mobility in soil	The substance is predicted to have high mobility in soil. Water Soluble. Log Pow: < 3. Readily biodegradable.
12.5	Results of PBT and vPvB assessment	Not classified as PBT or vPvB.
12.6	Endocrine disrupting properties	This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.
12.7	Other adverse effects	None known

SAFETY DATA SHEET

M-LINE GC-6 Isopropyl Alcohol

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

www.vpgsensors.com
Date of issue: 06/01/2023
Date of First Issue: 07/08/2012
Version 3.0

SECTION 13: DISPOSAL CONSIDERATIONS

- 13.1 Waste treatment methods** This material and its container must be disposed of as hazardous waste. Dispose of wastes in an approved waste disposal facility.
Directive 2008/98/EC (Waste Framework Directive) HP3, HP4, HP5
- 13.2 Additional Information** Dispose of contents in accordance with local, state or national legislation.

SECTION 14: TRANSPORT INFORMATION

	ADR/RID	ADN	IMDG	IATA/ICAO
14.1 UN number or ID number	UN 1219	UN 1219	UN 1219	UN 1219
14.2 UN proper shipping name	ISOPROPANOL (ISOPROPYL ALCOHOL)	ISOPROPANOL (ISOPROPYL ALCOHOL)	ISOPROPANOL (ISOPROPYL ALCOHOL)	ISOPROPANOL (ISOPROPYL ALCOHOL)
14.3 Transport hazard class(es)	3	3	3	3
14.4 Packing group	II	II	II	II
14.5 Environmental hazards	Not applicable	Not applicable	Not classified as a Marine Pollutant.	Not applicable
14.6 Special precautions for user	See Section: 2			
14.7 Maritime transport in bulk according to IMO instruments	Pollution category: Z			
14.8 Additional information	Recommended: Road/Rail/Sea transport only.			

SECTION 15: REGULATORY INFORMATION

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- 15.1.1 EU regulations**
Use restriction according to REACH annex XVII, no.: Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]
Restrictions of occupation:
To follow:
- 15.1.2 National regulations**
Germany
Water hazard class (WGK)
- 15.2 Chemical Safety Assessment**
- Not restricted
P5c
- Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).
Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work
- Water hazard class: 1 (Self classification)
A REACH chemical safety assessment has not been carried out.

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: New SDS Regulation 2020/878 format, all sections have been updated to include new information. Please review SDS with care.

References:

Existing Safety Data Sheet (SDS) and Existing ECHA registration(s) for Propan-2-ol (CAS No. 1330-20-7).

EU Classification: This Safety Data Sheet was prepared in accordance with EC Regulation (EC) 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

SAFETY DATA SHEET

M-LINE GC-6 Isopropyl Alcohol

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP)
& 2020/878

www.vpgsensors.com
Date of issue: 06/01/2023
Date of First Issue: 07/08/2012
Version 3.0

Classification of the substance or mixture According to Regulation (EC) No. 1272/2008 (CLP)	Classification Procedure
Flam. Liq. 2; H225	Physical and chemical properties / Harmonised Classification
Eye Irrit. 2; H319	Harmonised Classification
STOT SE 3; H336	Harmonised Classification

LEGEND

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
BCF	Bioconcentration factor (BCF)
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
DNEL	Derived no effect level
EU	European Union
EC	European Community
ECHA	European Chemicals Agency
EN	European Standard
IATA	International Air Transport Association
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
LC50	Lethal concentration at which 50% of the population is killed
LD50	Lethal dose at which 50% of the population is killed
LTEL	Long term exposure limit
NOAEC	No observed adverse effect concentration
NOEC	No Observed Effect Concentration
OECD	Organisation for Economic Cooperation and Development
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
TWA	Time Weighted Average
STEL	Short term exposure limit
vPvB	very Persistent and very Bioaccumulative
UK	United Kingdom
UN	United Nations

Hazard classification / Classification code:

Flam. Liq. 2; Flammable Liquid Category 2
Eye Irrit. 2; Eye Irritation Category 2
STOT SE 3; Specific target organ toxicity — single exposure Category 3

Hazard Statement(s)

H225: Highly flammable liquid and vapour.
H319: Causes serious eye irritation.
H336: May cause drowsiness or dizziness.

Training advice: Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required.

Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Vishay Precision Group gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Vishay Precision Group accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "VPG"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify VPG's terms and conditions of purchase, including but not limited to, the warranty expressed therein.

VPG makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. **To the maximum extent permitted by applicable law, VPG disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.**

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on VPG's knowledge of typical requirements that are often placed on VPG products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. You should ensure you have the current version of the relevant information by contacting VPG prior to performing installation or use of the product, such as on our website at vpgsensors.com.

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of VPG.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling VPG products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify VPG for any damages arising or resulting from such use or sale. Please contact authorized VPG personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Copyright Vishay Precision Group, Inc., 2014. All rights reserved.