

SAFETY DATA SHEET



Version: 2.0
Date of Issue: 26 April 2017
Date of First Issue: 11 October 2012

www.vishaypg.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

SECTION 1: IDENTIFICATION

Product identifier used on the label	3145-RTV
Other means of identification	Not applicable
Recommended use of the chemical and restrictions on use	
Recommended use	
Restrictions on use	PC1 Adhesives, sealants Anything other than the above.
Details of the supplier of the safety data sheet	
Supplier	VISHAY MEASUREMENTS GROUP, INC.
Address of Supplier	Post Office Box 27777 Raleigh, NC 27611 USA
Telephone	+1 919-365-3800
Fax	+1 919-365-3945
E-Mail (competent person)	mm.us@vishaypg.com
Emergency telephone number	1-800-424-9300 CHEMTREC (24 hours)

SECTION 2: HAZARD(S) IDENTIFICATION

Classification of the substance or mixture in accordance with paragraph (d) of 29 CFR 1910.1200	
Physical hazards	Not classified
Health hazards	Not classified
Environmental hazards	Not classified
Hazard Symbol	None assigned.
Signal Word(s)	None assigned.
Hazard Statement(s)	None assigned.
Precautionary Statement(s)	None assigned.
Other hazards	Repeated exposure may cause skin dryness or cracking. Contact with water or humid air will form methanol. Product may emit formaldehyde vapour at temperatures above 180°C in the presence of air. Formaldehyde vapour is a suspected carcinogen, toxic by inhalation and irritating to eyes and the respiratory system. Exposure limits should be strictly respected.
Percent of the mixture consists of ingredient(s) of unknown acute toxicity:	0%

SAFETY DATA SHEET

Version: 2.0
Date of Issue: 26 April 2017
Date of First Issue: 11 October 2012

www.vishaypg.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Substances Not applicable

Mixtures Substances in preparations / mixtures

Chemical identity of the substance	%W/W	CAS No.	EC No.	Hazard classification
Trimethylated silica	< 25	68909-20-6	272-697-1	Not classified
Trimethoxy(methyl)silane	5 - 10	1185-55-3	214-685-0	Flammable Liquid, Category 2
Methanol	< 0.2	67-56-1	200-659-6	Flammable Liquid, Category 2 Acute toxicity, Category 4 – Oral Acute toxicity, Category 4 – Dermal Acute toxicity, Category 4 – Inhalation Carcinogen, Category 2 (SCL ≥ 10%) Specific target organ toxicity — single exposure, Category 1 (SCL ≥ 10%)

SECTION 4: FIRST AID MEASURES



Description of first aid measures

Self-protection of the first aider

Inhalation

Skin Contact

Eye Contact

Ingestion

Most important symptoms and effects, both acute and delayed

Indication of any immediate medical attention and special treatment needed

Use personal protective equipment as required. Wear appropriate personal protective equipment, avoid direct contact. Ensure adequate ventilation. Avoid breathing vapours. Avoid contact with skin and eyes. Contaminated clothing should be laundered before reuse.

If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

Wash skin with soap and water. If skin irritation occurs: Get medical advice/attention.

Flush eyes with water for at least 15 minutes while holding eyelids open. If eye irritation persists, get medical advice/attention.

Wash out mouth with water and give 200-300 ml (half a pint) of water to drink. Do not induce vomiting. If symptoms develop, obtain medical attention.

Repeated exposure may cause skin dryness or cracking.

Unlikely to be required but if necessary treat symptomatically.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing media

Suitable Extinguishing Media

Unsuitable extinguishing Media

Special hazards arising from the substance or mixture

Special protective equipment and precautions for fire fighters

As appropriate for surrounding fire. Extinguish with carbon dioxide, dry chemical, foam or waterspray.

Do not use water jet. Direct water jet may spread the fire.

Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Silica, Carbon oxides and traces of incompletely burned carbon compounds, Formaldehyde, Sulphur products, Nitrogen products. Product may emit formaldehyde vapour at temperatures above 180°C in the presence of air. Formaldehyde vapour is a suspected carcinogen, toxic by inhalation and irritating to eyes and the respiratory system. Exposure limits should be strictly respected.

Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Do not breathe fumes. Keep containers cool by spraying

SAFETY DATA SHEET

Version: 2.0
Date of Issue: 26 April 2017
Date of First Issue: 11 October 2012

www.vishaypg.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

with water if exposed to fire. Avoid run off to waterways and sewers.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Stop leak if safe to do so. Use personal protective equipment as required. See Section: 8. Avoid breathing vapours. Avoid contact with skin and eyes. Avoid release to the environment. Do not allow to enter drains, sewers or watercourses.

Methods and material for containment and cleaning up

Absorb spillage to prevent material damage. Cover spills with inert absorbent material. Neutralize with dilute acid. Ventilate the area and wash spill site after material pick-up is complete.

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling

Ensure operatives are trained to minimise exposures. Ensure adequate ventilation. Avoid breathing vapours. In case of inadequate ventilation wear respiratory protection. Wear protective gloves/protective clothing/eye protection/face protection. Avoid contact with skin and eyes. Do not eat, drink or smoke when using this product.

Conditions for safe storage, including any incompatibilities

Storage temperature
Incompatible materials

Store in a well-ventilated place. Keep away from heat, sources of ignition and direct sunlight. Protect from moisture.

Maximum: 32°C

Stable under normal conditions.

Keep away from: Oxidizing agents and Water. Contact with water or humid air will form methanol.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

SUBSTANCE	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m ³)	STEL (ppm)	STEL (mg/m ³)	Note
Methanol	67-56-1	200	260	250(1)	325(1)	NIOSH
		200	260	-	-	OSHA
		200	-	250	-	ACGIH, Sk

Note: OSHA PELs 1910.1000 TABLE Z-1/ NIOSH RELs / ACGIH TLVs

Sk - Can be absorbed through skin.

(1) 15 minutes average value

The other components listed in Section 3 do not have occupational exposure limits.

Biological Exposure Indices

SUBSTANCE	CAS No.	Determinant	Biological Exposure Indices	Sampling Time	Note
Methanol	67-56-1	Methanol in Urine	15 mg/l	End of shift	B, Ns

Source: 2015 ACGIH Biological Exposure Indices (BEIs)

B – Background

Ns – Nonspecific

The other components listed in Section 3 do not have biological exposure indices.

Appropriate engineering controls

Ensure operatives are trained to minimise exposures. Ensure adequate ventilation. Atmospheric levels should be controlled in compliance with the occupational exposure limit.

SAFETY DATA SHEET

Version: 2.0
Date of Issue: 26 April 2017
Date of First Issue: 11 October 2012

www.vishaypg.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Individual protection measures, such as personal protective equipment (PPE)

General hygiene measures for the handling of chemicals are applicable. Keep good industrial hygiene. Avoid contact with skin and eyes. Avoid breathing vapours. Wash hands before breaks and after work. Keep work clothes separately. Do not eat, drink or smoke at the work place. IF exposed: Flush with fresh water if contact with skin or eyes.

Eye/face protection



Wear protective eye glasses for protection against liquid splashes. Wear eye protection with side protection (EN166).

Skin protection



Hand protection:

Wear impervious gloves (EN374). Protective index 6, corresponding > 480 minutes of permeation time according to EN 374 Gloves should be changed regularly to avoid permeation problems. Breakthrough time of the glove material: refer to the information provided by the gloves' producer. Neoprene or rubber gloves are recommended.

Respiratory protection



Body protection:

Wear suitable coveralls to prevent exposure to the skin.

In case of inadequate ventilation wear respiratory protection. Open system(s): Wear suitable respiratory protective equipment. A suitable mask with filter type A (EN141 or EN405) may be appropriate.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Translucent white paste
Odor	Slight
Odor Threshold	Not available.
pH	Not available.
Melting Point/Freezing Point	Not available.
Initial boiling point and boiling range	Not available.
Flash Point	Not applicable.
Evaporation rate (Butyl acetate = 1)	Not applicable.
Flammability (solid, gas)	Non-flammable.
Upper/lower flammability or explosive limits	Not applicable.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	1.12 (H ₂ O = 1)
Solubility(ies)	Insoluble in water.
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature	Not available.
Decomposition Temperature	Not available.
Viscosity	Not available.

SECTION 10: STABILITY AND REACTIVITY

Reactivity	This product releases methanol.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	Contact with water or humid air will form methanol.
Conditions to avoid	Protect from moisture.
Incompatible materials	Keep away from: Oxidizing agents and Water.

SAFETY DATA SHEET

Version: 2.0
Date of Issue: 26 April 2017
Date of First Issue: 11 October 2012

www.vishaypg.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Hazardous decomposition product(s)

Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Silica, Carbon oxides and traces of incompletely burned carbon compounds, Formaldehyde, Sulphur products, Nitrogen products.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on toxicological effects (Substances in preparations / mixtures)

Acute toxicity - Ingestion

Based upon the available data, the classification criteria are not met.
Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 2000 mg/kg bw/day.

Acute toxicity - Inhalation

Based upon the available data, the classification criteria are not met.
Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 20.0 mg/l.

Acute toxicity - Skin Contact

Based upon the available data, the classification criteria are not met.
Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 2000 mg/kg bw/day.

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Serious eye damage/irritation

Based upon the available data, the classification criteria are not met.

Respiratory or skin sensitization

Based upon the available data, the classification criteria are not met.

Germ cell mutagenicity

Based upon the available data, the classification criteria are not met.

Carcinogenicity

Based upon the available data, the classification criteria are not met.

Reproductive toxicity

Based upon the available data, the classification criteria are not met.

STOT - single exposure

Based upon the available data, the classification criteria are not met.

STOT - repeated exposure

Based upon the available data, the classification criteria are not met.

Aspiration hazard

Based upon the available data, the classification criteria are not met.

Information on likely routes of exposure

Inhalation

Possible – accidental exposure

Ingestion

Unlikely – accidental exposure

Skin Contact

Possible – accidental exposure

Eye Contact

Unlikely – accidental exposure

Early onset symptoms related to exposure

None anticipated

Delayed health effects from exposure

Repeated exposure may cause skin dryness or cracking.

Other information

NTP Report on Carcinogens

All chemicals are not listed

IARC Monographs

All chemicals are not listed

OSHA Designated Carcinogen

All chemicals are not listed

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Based upon the available data, the classification criteria are not met.
Estimated Mixture LC50 > 100 mg/l (Fish).

Persistence and degradability

No adverse effects on bacteria are predicted.

Siloxanes are removed from water by sedimentation or binding to sewage sludge. Removed > 90% by binding onto sewage sludge. The siloxanes in this product do not contribute to the BOD. In soil, siloxanes are degraded. This product hydrolyses in water or moist air, releasing methanol and organosilicons.

Bioaccumulative potential

The product has low potential for bioaccumulation.

Mobility in soil

The product is predicted to have high mobility in soil.

Other adverse effects

None known.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Dispose of contents in accordance with local, state or national legislation.

SAFETY DATA SHEET

Version: 2.0
Date of Issue: 26 April 2017
Date of First Issue: 11 October 2012

www.vishaypg.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

SECTION 14: TRANSPORT INFORMATION

(Not classified according to the United Nations 'Recommendations on the Transport of Dangerous Goods')

	ADR/RID	IMDG	IATA
UN number	Not classified	Not classified	Not classified
UN proper shipping name	Not classified	Not classified	Not classified
Transport hazard class(es)	Not classified	Not classified	Not classified
Packing group	Not classified	Not classified	Not classified
Environmental hazards	Not classified	Not classified as a Marine Pollutant.	Not classified
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable		
Special precautions for user	See Section: 2		

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

US Federal Regulations

TSCA (Toxic Substance Control Act)

Trimethylated silica: Subject to 25,000 lb reporting threshold
Trimethoxy(methyl)silane: Subject to 25,000 lb reporting threshold
Methanol: Subject to 25,000 lb reporting threshold
All chemicals are not listed

EPCRA/SARA Section 302 Extremely Hazardous
Substances

EPCRA Section 313 Toxics Release Inventory (TRI)
Program

Methanol: De Minimis limit: 1%

NIOSH Occupational Carcinogen List

All chemicals are not listed

OSHA List of highly hazardous chemicals, toxics and
reactives

All chemicals are not listed

NTP Report on Carcinogens (RoC) List

All chemicals are not listed

Poison Prevention Packaging Act

Methanol: Substance requiring special packaging

US State Regulations

California State, Proposition 65 List

Methanol: Safe harbor level - MADL: 47000 (inhalation) ug/day, 23000 (oral)
ug/day

California State, Safer Consumer Products Regulations

Methanol: Initial Candidate Chemicals List

Maine State, Toxic Chemicals in Children's Products Act

Methanol: COC list

New Jersey State Worker and Community RTK Act

Methanol: CHC list

Pennsylvania State, Worker and Community RTK Act

Methanol: RTKHSL. SHHSL

Rhode Island State, Hazardous Substances RTK Act

Methanol: Hazardous Substance List. Environmental Hazard List

Non-Regional

IARC Monographs, List of Classifications

All chemicals are not listed

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: Updated substance / mixture classification. New SDS Regulation compliant with HazCom 2012 format, all sections have been updated to include new information. Please review SDS with care.

Version 2.0
Revision Date 26 April 2017
Date of First Issue 11 October 2012

References:

Existing Safety Data Sheet (SDS), EU Data: Harmonised Classification(s) for Methanol (CAS No. 67-58-1) and Existing ECHA registration(s) for Trimethoxy(methyl)silane (CAS No. 1185-55-3) and Methanol (CAS No. 67-58-1).

SAFETY DATA SHEET



Version: 2.0
Date of Issue: 26 April 2017
Date of First Issue: 11 October 2012

www.vishaypg.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

GHS Classification of the substance or mixture	Classification Procedure
Not classified	Threshold Calculation

LEGEND

ACGIH: American Conference of Governmental Industrial Hygienists
BEI: Biological Exposure Indices (ACGIH)
IARC: International Agency for Research on Cancer
Irr: Irritation
NIOSH: National Institute of Occupational Safety and Health
NTP: National Toxicology Program
OSHA: The Occupational Safety & Health Administration
PBT: Persistent, Bioaccumulative and Toxic
PEL: Permissible exposure limit

REL: Recommended exposure limit
SCL: Specific Concentration Limit
Skin²: Risk of overexposure via dermal contact
STEL: Short Term Exposure Limit
TLV: Threshold Limit value
TSCA: Toxic Substance Control Act
TWA: Time Weighted Average
URT: Upper respiratory tract
vPvB: very Persistent and very Bioaccumulative

Training advice: Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required.

Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Vishay Precision Group gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Vishay Precision Group accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "VPG"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify VPG's terms and conditions of purchase, including but not limited to, the warranty expressed therein.

VPG makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. **To the maximum extent permitted by applicable law, VPG disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.**

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on VPG's knowledge of typical requirements that are often placed on VPG products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. You should ensure you have the current version of the relevant information by contacting VPG prior to performing installation or use of the product, such as on our website at vpgsensors.com.

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of VPG.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling VPG products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify VPG for any damages arising or resulting from such use or sale. Please contact authorized VPG personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Copyright Vishay Precision Group, Inc., 2014. All rights reserved.