

SAFETY DATA SHEET

Revision: 1.1 Date: 25.08.2015

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 2015/830

www.vishaypg.com

1. SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier**
Product Name PC-11C & PL-3
Chemical Name Mixture
CAS No. Mixture
EINECS No. Mixture
REACH Registration No. None assigned.
- 1.2 Relevant identified uses of the substance or mixture and uses advised against**
Identified Use(s) Photostress® measurements.
Uses Advised Against None known.
- 1.3 Details of the supplier of the safety data sheet**
Company Identification VISHAY MEASUREMENTS GROUP UK LTD
Stroudley Road
Basingstoke
Hampshire
United Kingdom
RG24 8FW
Telephone +44 (0) 1256 462131
Fax +44 (0) 1256 471441
E-Mail (competent person) mm.uk@vishaypg.com
- 1.4 Emergency telephone number** (00-1) 703-527-3887
CHEMTREC

2. SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture**
2.1.1 Regulation (EC) No. 1272/2008 (CLP) Skin Irrit. 2; H315
Skin Sens. 1; H317
Eye Irrit. 2; H319
Muta. 2; H341
Carc. 2; H351
Aquatic Chronic 2; H411
- 2.2 Label elements** Regulation (EC) No. 1272/2008 (CLP)
Product Name PC-11C
- Hazard Pictogram(s)
- Signal Word(s) Warning
- Contains: Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700), N-Butyl Glycidyl and Ether P-Tert-butylphenyl 1-(2,3-epoxy)propyl ether.
- Hazard Statement(s)
H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H319: Causes serious eye irritation.
H341: Suspected of causing genetic defects.
H351: Suspected of causing cancer.
H411: Toxic to aquatic life with long lasting effects.



SAFETY DATA SHEET

Revision: 1.1 Date: 25.08.2015

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 2015/830

www.vishaypg.com

Precautionary Statement(s)

P201: Obtain special instructions before use.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352: IF ON SKIN: Wash with plenty of water.
P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313: IF exposed or concerned: Get medical advice/attention.

Additional Information

None.

2.3 Other hazards

None.

3. SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances Not applicable

3.2 Mixtures

Regulation (EC) No. 1272/2008 (CLP)

Chemical identity of the substance	%W/W	CAS No.	EC No.	REACH Registration No.	Hazard Statement(s)
Reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight \leq 700)	< 100	25068-38-6	500-033-5	None assigned.	Skin Irrit. 2; H315 (SCL: \geq 5%) Skin Sens. 1; H317 Eye Irrit. 2; H319 (SCL: \geq 5%) Aquatic Chronic 2; H411
N-Butyl Glycidyl Ether	4 - 7	2426-08-6	219-376-4	None assigned.	Flam. Liq. 3; H226 Acute Tox. 4; H302 Skin Sens. 1; H317 Acute Tox. 4; H332 STOT SE 3; H335 Muta. 2; H341 Carc. 2; H351 Aquatic Chronic 3; H412
Tert-butylphenyl 1-(2,3- epoxy)propyl ether	1 - 5	3101-60-8	221-453-2	None assigned.	Skin Irrit. 2; H315 Skin Sens. 1; H317 Eye Irrit. 2; H319 Aquatic Chronic 2; H411

H226: Flammable liquid and vapour. H302: Harmful if swallowed. H315: Causes skin irritation. H317: May cause an allergic skin reaction. H319: Causes serious eye irritation. H332: Harmful if inhaled. H335: May cause respiratory irritation. H341: Suspected of causing genetic defects. H351: Suspected of causing cancer. H411: Toxic to aquatic life with long lasting effects. H412: Harmful to aquatic life with long lasting effects. SCL: Specific Concentration Limit.

4. SECTION 4: FIRST AID MEASURES



4.1 Description of first aid measures

Self-protection of the first aider

Do not breathe vapour. Wear suitable protective clothing. Wear suitable respiratory protective equipment if exposure to high levels of material are likely. Do not use mouth-to-mouth resuscitation.

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Apply artificial respiration if breathing has ceased or shows signs of failing. IF exposed or concerned: Call a POISON CENTER/doctor.

Skin Contact

IF ON SKIN: Remove contaminated clothing and wash all affected areas with

SAFETY DATA SHEET

Revision: 1.1 Date: 25.08.2015

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 2015/830

www.vishaypg.com

Eye Contact	plenty of water. Contaminated clothing should be thoroughly cleaned. If skin irritation or rash occurs: Get medical advice/attention. IF exposed or concerned: Call a POISON CENTER/doctor.
Ingestion	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if eye irritation develops or persists. IF SWALLOWED: Rinse mouth. Do not induce vomiting. Do not give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep head below hips to prevent aspiration into the lungs. If symptoms develop, obtain medical attention.
4.2 Most important symptoms and effects, both acute and delayed	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Suspected of causing genetic defects. Suspected of causing cancer.
4.3 Indication of any immediate medical attention and special treatment needed	Treat symptomatically.

5. SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media Suitable Extinguishing media	As appropriate for surrounding fire. Extinguish with carbon dioxide, dry chemical, foam or waterspray. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.
Unsuitable extinguishing media	Do not use water jet. Direct water jet may spread the fire.
5.2 Special hazards arising from the substance or mixture	May decompose in a fire giving off toxic fumes. Carbon monoxide, Carbon dioxide, Phenolics, Acids and Aldehydes. Sealed containers may rupture explosively if hot. Dense smoke is emitted when burned without sufficient oxygen.
5.3 Advice for fire-fighters	Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Do not breathe fumes. Keep containers cool by spraying with water if exposed to fire. Avoid run off to waterways and sewers.

6. SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures	Ensure adequate ventilation. Eliminate all ignition sources if safe to do so. Stop leak if safe to do so. Use personal protective equipment as required. See Section: 8. Do not breathe vapour.
6.2 Environmental precautions	Avoid release to the environment. Do not allow to enter drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be alerted to the Environment Agency or other appropriate regulatory body.
6.3 Methods and material for containment and cleaning up	Ensure suitable personal protection during removal of spillages. Contain spillages. Adsorb spillages onto sand, earth or any suitable adsorbent material. Transfer to a container for disposal. Ventilate the area and wash spill site after material pick-up is complete. Dispose of this material and its container as hazardous waste (2008/98/EEC).
6.4 Reference to other sections	See Section: 8, 13

7. SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid contact with skin, eyes or clothing. Do not breathe vapour. Ensure adequate ventilation. Use personal protective equipment as required. See Section: 8. Do not eat, drink or smoke when using this product. Wash hands before breaks and after work.
7.2 Conditions for safe storage, including any incompatibilities Storage temperature Storage life Incompatible materials	Store in a well-ventilated place. Keep container tightly closed. Keep away from heat, sources of ignition and direct sunlight. Ambient. Stable under normal conditions. Keep away from: Acids, strong bases, Oxidizing agents, mercaptans and

SAFETY DATA SHEET

Revision: 1.1 Date: 25.08.2015

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 2015/830

www.vishaypg.com

unintended contact with amines. The following may occur: Hazardous
Polymerization.
Photostress® measurements.

7.3 Specific end use(s)

8. SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

8.1.1 Occupational Exposure Limits

SUBSTANCE	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m ³)	STEL (ppm)	STEL (mg/m ³)	Note
N-Butyl Glycidyl Ether*	2426-08-6	25	135	-	-	WEL

Note: WEL: Workplace Exposure Limit (UK HSE EH40).

* The UK Advisory Committee on Toxic Substances has expressed concern that, for the OELs shown in parentheses, health may not be adequately protected because of doubts that the limit was not soundly-based. These OELs were included in the published UK 2002 list and its 2003 supplement, but are omitted from the published 2005 list.

8.1.2 Biological limit value

Not established.

8.1.3 PNECs and DNELs

Not established.

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure adequate ventilation or use appropriate containment. Atmospheric levels should be controlled in compliance with the occupational exposure limit. Guarantee that the eye flushing systems and safety showers are located close to the working place.

8.2.2 Individual protection measures, such as personal protective equipment (PPE)

General hygiene measures for the handling of chemicals are applicable. Avoid contact with skin, eyes or clothing. Do not breathe vapour. Wash hands before breaks and after work. Keep work clothes separately. Contaminated clothing should be thoroughly cleaned. Contaminated leather articles should be discarded (e.g. shoes). Do not eat, drink or smoke at the work place.

Eye/ face protection



Wear protective eye glasses for protection against liquid splashes. Wear eye protection with side protection (EN166).

Skin protection



Hand protection: Wear impervious gloves (EN374). Gloves should be changed regularly to avoid permeation problems. The gloves type used must be chosen based on the work activity and duration as well as concentration/quantity of material being handled. Recommended: Neoprene.

Body protection: Wear impervious protective clothing, including boots, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Respiratory protection



In case of inadequate ventilation wear respiratory protection. Open system(s): Wear suitable respiratory protective equipment.

Thermal hazards

Not applicable.

8.2.3 Environmental Exposure Controls

Avoid release to the environment.

9. SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

SAFETY DATA SHEET

Revision: 1.1 Date: 25.08.2015

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 2015/830

www.vishaypg.com

Appearance	Clear - Light coloured liquid
Odour	Faint Odour
Odour threshold	Not available.
pH	Not established.
Melting point/freezing point	-16 °C (CAS# 25068-38-6)
Initial boiling point and boiling range	~320 °C (CAS# 25068-38-6)
Flash point	73.3°C [Closed cup]
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable - Liquid.
Upper/lower flammability or explosive limits	Not applicable.
Vapour pressure	< 1 mm Hg
Vapour density	>1 (Air = 1)
Relative density	1.13 (H2O = 1)
Solubility(ies)	Insoluble in water.
Partition coefficient: n-octanol/water	$\geq 2.64 \leq 3.78 \log Pow$ (25 °C) (CAS# 25068-38-6)
Auto-ignition temperature	Not applicable.
Decomposition Temperature	>350 °C (CAS# 25068-38-6)
Viscosity	Not available.
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.

9.2 Other information Volatile Organic Compound Content (%): 0

10. SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity	Stable under normal conditions.
10.2 Chemical stability	Stable under normal conditions.
10.3 Possibility of hazardous reactions	Keep away from: Acids, strong bases, Amines and mercaptans. The following may occur: Hazardous Polymerization. Contact with aliphatic amines will cause irreversible polymerization with considerable heat build-up.
10.4 Conditions to avoid	Keep away from heat, sources of ignition and direct sunlight.
10.5 Incompatible materials	Keep away from: Acids, strong bases, Amines and mercaptans.
10.6 Hazardous decomposition product(s)	May decompose in a fire giving off toxic fumes. Carbon monoxide, Carbon dioxide, Phenolics, Acids and Aldehydes.

11. SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects (Substances in preparations / mixtures)	
Acute toxicity	
Ingestion	Based upon the available data, the classification criteria are not met. Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 2000 mg/kg bw/day.
Inhalation	Based upon the available data, the classification criteria are not met. Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 20.0 mg/l.
Skin Contact	Based upon the available data, the classification criteria are not met. Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 2000 mg/kg bw/day.
Skin corrosion/irritation	Skin Irrit. 2: Causes skin irritation.
Serious eye damage/irritation	Eye Irrit. 2: Causes serious eye irritation.
Respiratory or skin sensitization	Skin Sens. 1: May cause an allergic skin reaction.
Germ cell mutagenicity	Muta. 2: Suspected of causing genetic defects.
Carcinogenicity	Carc. 2: Suspected of causing cancer.
Reproductive toxicity	Based upon the available data, the classification criteria are not met.
STOT - single exposure	Based upon the available data, the classification criteria are not met.
STOT - repeated exposure	Based upon the available data, the classification criteria are not met.
Aspiration hazard	Based upon the available data, the classification criteria are not met.
11.2 Other information	None.

SAFETY DATA SHEET

Revision: 1.1 Date: 25.08.2015

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 2015/830

www.vishayppg.com

12. SECTION 12: ECOLOGICAL INFORMATION

12.1	Toxicity	Aquatic Chronic 2: Toxic to aquatic life with long lasting effects. Estimated Mixture LC50 > 1 ≤ 10 mg/l (Fish)
12.2	Persistence and degradability	Part of the components are poorly biodegradable.
12.3	Bioaccumulative potential	The product has low potential for bioaccumulation.
12.4	Mobility in soil	The product is predicted to have low mobility in soil. (Insoluble in water.)
12.5	Results of PBT and vPvB assessment	Not classified as PBT or vPvB.
12.6	Other adverse effects	None known.

13. SECTION 13: DISPOSAL CONSIDERATIONS

13.1	Waste treatment methods	Dispose of this material and its container as hazardous waste (2008/98/EEC). Containers of this material may be hazardous when empty since they retain product residue.
13.2	Additional Information	Dispose of contents in accordance with local, state or national legislation.

14. SECTION 14: TRANSPORT INFORMATION

		ADR/RID / IMDG / IATA
14.1	UN number	UN 3082
14.2	UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S (Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700) and Tert-butylphenyl 1-(2,3-epoxy)propyl ether)
14.3	Transport hazard class(es)	9
14.4	Packing group	III
14.5	Environmental hazards	Classified as a Marine Pollutant./ Environmentally hazardous substance
14.6	Special precautions for user	See Section: 2
14.7	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
14.8	Additional Information	None.

15. SECTION 15: REGULATORY INFORMATION

15.1	Safety, health and environmental regulations/legislation specific for the substance or mixture	
15.1.1	EU regulations	
	Substance(s) of Very High Concern (SVHCs)	None
15.1.2	National regulations	
	Wassergefährdungsklasse (Germany)	Water hazard class: 2
15.2	Chemical Safety Assessment	Not available.

16. SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16.

References: Existing Safety Data Sheet (SDS), Harmonised Classification(s) for Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700) (CAS# 25068-38-6) and N-Butyl Glycidyl Ether (CAS# 2426-08-6). Existing ECHA registration(s) for Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700) (CAS# 25068-38-6) and P-Tertbutylphenyl Glycidyl Ether (CAS# 3101-60-8).

SAFETY DATA SHEET

Revision: 1.1 Date: 25.08.2015

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 2015/830

www.vishaypg.com

Classification of the substance or mixture According to Regulation (EC) No. 1272/2008 (CLP)	Classification Procedure
Skin Irrit. 2; H315	Threshold Calculation
Skin Sens. 1; H317	Threshold Calculation
Eye Irrit. 2; H19	Threshold Calculation
Muta. 2; H341	Threshold Calculation
Carc. 2; H351	Threshold Calculation
Aquatic Chronic 2; H411	Summation Calculation

LEGEND

LTEL	Long Term Exposure Limit
STEL	Short Term Exposure Limit
DNEL	Derived No Effect Level
PNEC	Predicted No Effect Concentration
PBT	PBT: Persistent, Bioaccumulative and Toxic
vPvB	very Persistent and very Bioaccumulative

Training advice: Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required.

Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Vishay Precision Group gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Vishay Precision Group accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

Annex to the extended Safety Data Sheet (eSDS)

No information available.

Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "VPG"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify VPG's terms and conditions of purchase, including but not limited to, the warranty expressed therein.

VPG makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. **To the maximum extent permitted by applicable law, VPG disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.**

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on VPG's knowledge of typical requirements that are often placed on VPG products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. You should ensure you have the current version of the relevant information by contacting VPG prior to performing installation or use of the product, such as on our website at vpgsensors.com.

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of VPG.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling VPG products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify VPG for any damages arising or resulting from such use or sale. Please contact authorized VPG personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Copyright Vishay Precision Group, Inc., 2014. All rights reserved.