

SAFETY DATA SHEET

Revision: 1.1 Date: 28.08.2015

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 2015/830

www.vpgsensors.com

1. SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier**
Product Name RS-200-CK Cement (Grip Cement Liquid)
Chemical Name Mixture
CAS No. Mixture
EINECS No. Mixture
REACH Registration No. None assigned.
- 1.2 Relevant identified uses of the substance or mixture and uses advised against**
Identified Use(s) Adhesives
Uses Advised Against None known.
- 1.3 Details of the supplier of the safety data sheet**
Company Identification VISHAY MEASUREMENTS GROUP, INC.
Post Office Box 27777
Raleigh, NC 27611
USA
Telephone 919-365-3800
Fax 919-365-3945
E-Mail (competent person) mm.us@vishaypg.com
- 1.4 Emergency telephone number** 1-800-424-9300
CHEMTREC

2. SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture**
- 2.1.1 GHS Classification** Flam. Liq. 2; H225
Skin Irrit. 2; H315
Skin Sens. 1; H317
STOT SE 3; H335
- 2.2 Label elements**
Product Name GHS Classification
RS-200-CK Cement (Grip Cement Liquid)
- Hazard Pictogram(s)

- Signal Word(s) Danger
Contains: Methyl methacrylate
- Hazard Statement(s)
H225: Highly flammable liquid and vapour.
H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H335: May cause respiratory irritation.
- Precautionary Statement(s)
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261: Avoid breathing vapours.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352: IF ON SKIN: Wash with plenty of water.
P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
P312: Call a POISON CENTER/doctor if you feel unwell.
- Additional Information None.

SAFETY DATA SHEET

Revision: 1.1 Date: 28.08.2015

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 2015/830

www.vpgsensors.com

2.3 Other hazards

Susceptible to violent exothermic polymerisation, initiated by heating or the presence of catalysts.

3. SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances Not applicable.

3.2 Mixtures

EC Classification Regulation (EC) No. 1272/2008 (CLP)

Chemical identity of the substance	%W/W	CAS No.	EC No.	REACH Registration No.	Hazard Statement(s)
Methyl methacrylate	99	80-62-6	201-297-1	None assigned	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Skin Sens. 1; H317 STOT SE 3; H335
N,N-Dimethyl-p-toluidine	1	99-97-8	202-805-4	None assigned	Acute Tox. 3; H301 Acute Tox. 3; H311 Acute Tox. 3; H331 STOT RE 2; H373 Aquatic Chronic 3; H412

H225: Highly flammable liquid and vapour. H301: Toxic if swallowed. H311: Toxic in contact with skin. H315: Causes skin irritation. H317: May cause an allergic skin reaction. H331: Toxic if inhaled. H335: May cause respiratory irritation. H373: May cause damage to organs through prolonged or repeated exposure. H412: Harmful to aquatic life with long lasting effects.

4. SECTION 4: FIRST AID MEASURES



4.1 Description of first aid measures

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Call a POISON CENTER/doctor if you feel unwell.

Skin Contact

IF ON SKIN (or hair): Remove contaminated clothing and wash all affected areas with plenty of water. Contaminated clothing should be thoroughly cleaned. If skin irritation or rash occurs: Get medical advice/attention.

Eye Contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion

IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Do not give anything by mouth to an unconscious person. If symptoms occur obtain medical attention. Causes skin irritation. May cause an allergic skin reaction. May cause respiratory irritation.

4.2 Most important symptoms and effects, both acute and delayed

Causes skin irritation. May cause an allergic skin reaction. May cause respiratory irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

5. SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable Extinguishing media

As appropriate for surrounding fire. Use CO₂, dry chemical, or foam.

Unsuitable extinguishing media

Do not use water.

5.2 Special hazards arising from the substance or mixture

Highly flammable liquid and vapour. Vapours are heavier than air and may travel considerable distances to a source of ignition and flashback. May polymerise on

SAFETY DATA SHEET

Revision: 1.1 Date: 28.08.2015

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 2015/830

www.vpgsensors.com

5.3 Advice for fire-fighters

exposure to heat. Sealed containers may rupture explosively if hot. May decompose in a fire giving off toxic fumes. Oxides of carbon.
Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Do not breathe fumes. Keep containers cool by spraying with water if exposed to fire. Avoid run off to waterways and sewers.

6. SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Stop leak if safe to do so. Eliminate all ignition sources if safe to do so. Avoid breathing vapours. Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. See Section: 8.

6.2 Environmental precautions

Avoid release to the environment. Prevent liquid entering sewers, basements and workpits; vapour may create explosive atmosphere.

6.3 Methods and material for containment and cleaning up

Ensure suitable personal protection (including respiratory protection) during removal of spillages. Use non-sparking equipment when picking up flammable spill.

Small spillages: Adsorb spillages onto sand, earth or any suitable adsorbent material. Transfer to a container for disposal.

Large spillages: Contain spillages. Collect mechanically and dispose of according to Section 13.

Ventilate the area and wash spill site after material pick-up is complete. Dispose of this material and its container as hazardous waste.

6.4 Reference to other sections

See Section: 8, 13

7. SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Ensure adequate ventilation. Avoid breathing vapours. Avoid contact with skin, eyes or clothing. In case of inadequate ventilation wear respiratory protection. Use personal protective equipment as required. See Section: 8. Do not eat, drink or smoke when using this product. Wash hands before breaks and after work. Do not eat, drink or smoke when using this product. Take precautionary measures against static discharge. Protect from light.

7.2 Conditions for safe storage, including any incompatibilities

Ground/bond container and receiving equipment. Keep container tightly closed, in a cool, well ventilated place. Keep only in original container. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from light.

Storage temperature

Keep at a temperature not exceeding (°C): 30

Storage life

Stable under normal conditions.

Incompatible materials

Keep away from: Acids, strong bases, Strong oxidising agents, Reducing agent, Amines and UV light.

7.3 Specific end use(s)

Adhesives.

8. SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

8.1.1 Occupational Exposure Limits

SUBSTANCE	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m ³)	STEL (ppm)	STEL (mg/m ³)	Note
Methyl methacrylate	80-62-6	100	410	-	-	NIOSH/OSHA

Note: OSHA 1910.1000 TABLE Z-1 / NIOSH

8.1.2 Biological limit value

Not established.

8.1.3 PNECs and DNELs

Not established.




8.2 Exposure controls

SAFETY DATA SHEET

Revision: 1.1 Date: 28.08.2015

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 2015/830

www.vpgsensors.com

8.2.1	Appropriate engineering controls	Ensure adequate ventilation or use appropriate containment. Atmospheric levels should be controlled in compliance with the occupational exposure limit. Use non-sparking ventilation systems, approved explosion-proof equipment, and intrinsically safe electrical systems. Guarantee that the eye flushing systems and safety showers are located close to the working place.
8.2.2	Individual protection measures, such as personal protective equipment (PPE)	General hygiene measures for the handling of chemicals are applicable. Avoid breathing vapours. Avoid contact with skin, eyes or clothing. Wash hands before breaks and after work. Keep work clothes separately. Do not eat, drink or smoke at the work place.
	Eye/ face protection	Wear goggles giving complete protection to eyes to protect against liquid splashes (EN166).
		
	Skin protection	Hand protection: Wear impervious gloves (EN374). Gloves should be changed regularly to avoid permeation problems. Breakthrough time of the glove material: refer to the information provided by the gloves' producer.
		
	Respiratory protection	Body protection: Wear impervious protective clothing, including boots, lab coat, apron or coveralls, as appropriate, to prevent skin contact.
		
	Thermal hazards	In case of inadequate ventilation wear respiratory protection. Open system(s): Wear suitable respiratory protective equipment.
		Not applicable.
8.2.3	Environmental Exposure Controls	Avoid release to the environment.

9. SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1	Information on basic physical and chemical properties	
	Appearance	Colourless liquid
	Odour	Strong acrid acrylic odor
	Odour threshold	Not available.
	pH	Not established.
	Melting point/freezing point	- 48 °C
	Initial boiling point and boiling range	100.36 °C (Methylmethacrylate (CAS# 80-62-6))
	Flash point	9 °C [Closed cup]
	Evaporation rate	>1 (BuAc = 1)
	Flammability (solid, gas)	Not applicable - Liquid
	Upper/lower flammability or explosive limits	Flammable Limits (Lower) (%v/v): 2.1 Flammable Limits (Upper) (%v/v): 12.5
	Vapour pressure	29 mm Hg
	Vapour density	3.5 (Air = 1)
	Relative density	0.94 (H ₂ O = 1)
	Solubility(ies)	15.3 g/L (Water @ 20 °C) (Methylmethacrylate (CAS# 80-62-6))
	Partition coefficient: n-octanol/water	1.24 Log Pow (Methylmethacrylate (CAS# 80-62-6))
	Auto-ignition temperature	320 °C (Mixture)
	Decomposition Temperature	Not available.
	Viscosity	0.6 mPa s (20 °C)
	Explosive properties	Not explosive.
	Oxidising properties	Not oxidising.
9.2	Other information	None.

SAFETY DATA SHEET

Revision: 1.1 Date: 28.08.2015

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 2015/830

www.vpgsensors.com

10. SECTION 10: STABILITY AND REACTIVITY

10.1	Stability and reactivity	Stable under normal conditions.
10.2	Chemical stability	Stable under normal conditions.
10.3	Possibility of hazardous reactions	Highly flammable liquid and vapour. The vapour may be invisible, heavier than air and spread along ground. Susceptible to violent exothermic polymerisation, initiated by heating or the presence of catalysts.
10.4	Conditions to avoid	Keep away from heat, sources of ignition and direct sunlight.
10.5	Incompatible materials	Keep away from: Acids, strong bases, Strong oxidising agents, Reducing agent, Amines and UV light.
10.6	Hazardous decomposition product(s)	May decompose in a fire giving off toxic fumes. Carbon monoxide, Carbon dioxide and Acrid smoke.

11. SECTION 11: TOXICOLOGICAL INFORMATION

11.1	Information on toxicological effects (Substances in preparations / mixtures)	
	Acute toxicity	
	Ingestion	Based upon the available data, the classification criteria are not met. Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 2000 mg/kg bw/day.
	Inhalation	Based upon the available data, the classification criteria are not met. Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 20 mg/l.
	Skin Contact	Based upon the available data, the classification criteria are not met. Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 2000 mg/kg bw/day.
	Skin corrosion/irritation	Skin Irrit. 2: Causes skin irritation.
	Serious eye damage/irritation	Based upon the available data, the classification criteria are not met.
	Respiratory or skin sensitization	Skin Sens. 1: May cause an allergic skin reaction.
	Germ cell mutagenicity	Based upon the available data, the classification criteria are not met.
	Carcinogenicity	Based upon the available data, the classification criteria are not met.
	Reproductive toxicity	Based upon the available data, the classification criteria are not met.
	STOT - single exposure	STOT SE 3: May cause respiratory irritation.
	STOT - repeated exposure	Based upon the available data, the classification criteria are not met.
	Aspiration hazard	Based upon the available data, the classification criteria are not met.
11.2	Other information	
	NTP Report on Carcinogens	Not listed.
	IARC Monographs	Not listed.

12. SECTION 12: ECOLOGICAL INFORMATION

12.1	Toxicity	Based upon the available data, the classification criteria are not met. Estimated Mixture LC50 > 100 mg/l (Fish)
12.2	Persistence and degradability	This product is readily biodegradable in water.
12.3	Bioaccumulative potential	The product has no potential for bioaccumulation.
12.4	Mobility in soil	The product is predicted to have high mobility in soil. Water Soluble / Highly volatile.
12.5	Results of PBT and vPvB assessment	Not classified as PBT or vPvB.
12.6	Other adverse effects	None known.

13. SECTION 13: DISPOSAL CONSIDERATIONS

13.1	Waste treatment methods	Do not release undiluted and unneutralised to the sewer. Containers of this material may be hazardous when empty since they retain product residue. This material and its container must be disposed of as hazardous waste.
13.2	Additional Information	Disposal should be in accordance with local, state or national legislation.

SAFETY DATA SHEET

Revision: 1.1 Date: 28.08.2015

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 2015/830

www.vpgsensors.com

14. SECTION 14: TRANSPORT INFORMATION

	ADR/RID / IMDG / IATA
14.1 UN number	UN 1247
14.2 UN proper shipping name	METHYL METHACRYLATE MONOMER, STABILIZED
14.3 Transport hazard class(es)	3
14.4 Packing group	II
14.5 Environmental hazards	Not classified as a Marine Pollutant./Environmentally hazardous substance
14.6 Special precautions for user	See Section: 2
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
14.8 Additional Information	None.

15. SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture	
15.1.2 National regulations	
OSHA Occupational Safety and Health Standards	None.
15.1.1 European regulations	
Substances of Very High Concern (SVHCs)	None.
Authorisations and/or Restrictions On Use	None.
Wassergefährdungsklasse (Germany)	Water hazard class: 1
15.2 Chemical Safety Assessment	Not available.

16. SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16.

References: Existing Safety Data Sheet (SDS). Harmonised Classification(s) for Methylmethacrylate (CAS# 80-62-6) and N,N-Dimethyl-p-toluidine (CAS# 99-97-8). Existing ECHA registration(s) for Harmonised Classification(s) for Methylmethacrylate (CAS# 80-62-6) and N,N-Dimethyl-p-toluidine (CAS# 99-97-8).

GHS Classification of the substance or mixture	Classification Procedure
Flam. Liq. 2; H225	Flash Point [Closed cup] Test Result/ Estimated Boiling Point (°C)
Skin Irrit. 2; H315	Threshold Calculation
Skin Sens. 1; H317	Threshold Calculation
STOT SE 3; H335	Threshold Calculation

LEGEND

LTEL	Long Term Exposure Limit
STEL	Short Term Exposure Limit
DNEL	Derived No Effect Level
PNEC	Predicted No Effect Concentration
PBT	PBT: Persistent, Bioaccumulative and Toxic
vPvB	very Persistent and very Bioaccumulative
NTP	National Toxicology Program
IARC	International Agency for Research on Cancer
OSHA	The Occupational Safety & Health Administration
NIOSH	National Institute for Occupational Safety and Health

Training advice: Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required.

Disclaimers

SAFETY DATA SHEET



Revision: 1.1 Date: 28.08.2015

**ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 2015/830**

www.vpgsensors.com

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Vishay Precision Group gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Vishay Precision Group accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

Annex to the extended Safety Data Sheet (eSDS)

No information available.



Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "VPG"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify VPG's terms and conditions of purchase, including but not limited to, the warranty expressed therein.

VPG makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. **To the maximum extent permitted by applicable law, VPG disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.**

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on VPG's knowledge of typical requirements that are often placed on VPG products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. You should ensure you have the current version of the relevant information by contacting VPG prior to performing installation or use of the product, such as on our website at vpgsensors.com.

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of VPG.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling VPG products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify VPG for any damages arising or resulting from such use or sale. Please contact authorized VPG personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Copyright Vishay Precision Group, Inc., 2014. All rights reserved.