

# SAFETY DATA SHEET

Version: 4.0  
Date of Issue: 08 May 2017  
Date of First Issue: 20 March 2012


www.vishaypg.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

## SECTION 1: IDENTIFICATION

<b>Product identifier used on the label</b>	M-Bond 450 Part B
<b>Other means of identification</b>	Not applicable
<b>Recommended use of the chemical and restrictions on use</b>	
Recommended use	Adhesives.
Restrictions on use	For professional users only.
<b>Details of the supplier of the safety data sheet</b>	
Supplier	VISHAY MEASUREMENTS GROUP, INC.
Address of Supplier	Post Office Box 27777 Raleigh, NC 27611 USA
Telephone	+1 919-365-3800
Fax	+1 919-365-3945
E-Mail (competent person)	<a href="mailto:mm.us@vishaypg.com">mm.us@vishaypg.com</a>
<b>Emergency telephone number</b>	1-800-424-9300 CHEMTREC (24 hours)

## SECTION 2: HAZARD(S) IDENTIFICATION

<b>Classification of the substance or mixture in accordance with paragraph (d) of 29 CFR 1910.1200</b>	
Physical hazards	Flammable Liquid, Category 2
Health hazards	Acute toxicity, Category 4 – Inhalation Eye Irritation, Category 2 Specific target organ toxicity — single exposure, Category 3 Specific target organ toxicity — single exposure, Category 2 Specific target organ toxicity — repeated exposure, Category 2 Reproductive toxicity, Category 1B Hazardous to the aquatic environment, Chronic, Category 3
Environmental hazards	
Hazard Symbol	
Signal Word(s)	DANGER
Hazard Statement(s)	Highly flammable liquid and vapour. Harmful if inhaled. Causes serious eye irritation. May cause drowsiness or dizziness. May cause damage to organs. May cause damage to organs through prolonged or repeated exposure. May damage fertility. May damage the unborn child. Harmful to aquatic life with long lasting effects.
Precautionary Statement(s)	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed.

# SAFETY DATA SHEET

Version: 4.0  
Date of Issue: 08 May 2017  
Date of First Issue: 20 March 2012

www.vishaypg.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Do not breathe vapour.  
Wash hands and exposed skin thoroughly after handling.  
Wear protective gloves/protective clothing/eye protection/face protection.  
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
Call a POISON CENTER/doctor if you feel unwell.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If eye irritation persists, get medical advice/attention.  
IF exposed or concerned: Call a POISON CENTER/doctor.

## Other hazards

Repeated exposure may cause skin dryness or cracking.

Percent of the mixture consists of ingredient(s) of unknown acute toxicity: 0%

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

**Substances** Not applicable

**Mixtures** Substances in preparations / mixtures

Chemical identity of the substance	%W/W	CAS No.	EC No.	Hazard classification
2-Ethoxyethanol	50 - 55	110-80-5	203-804-1	Flammable Liquid, Category 3 Acute toxicity, Category 4 – Oral Acute toxicity, Category 3 – Inhalation Reproductive toxicity, Category 1B
Methyl ethyl ketone	25 – 30	78-93-3	201-159-0	Flammable Liquid, Category 2 Eye Irritation, Category 2 Specific target organ toxicity — single exposure, Category 3
4,4'-Sulfonyldianiline	15 – 20	80-08-0	201-248-4	Acute toxicity, Category 4 – Oral Specific target organ toxicity — single exposure, Category 2 Specific target organ toxicity — repeated exposure, Category 2 Hazardous to the aquatic environment, Chronic, Category 2
Xylene	< 7.5	1330-20-7	215-535-7	Flammable Liquid, Category 3 Acute toxicity, Category 4 – Dermal Acute toxicity, Category 4 – Inhalation Skin Corrosion/Irritation, Category 2 Aspiration hazard, Category 1 Eye Irritation, Category 2 Specific target organ toxicity — single exposure, Category 3 Specific target organ toxicity — repeated exposure, Category 2
Boron trifluoride ethylamine complex	< 0.5	75-23-0	200-852-5	Skin Corrosion/Irritation, Category 1

## SECTION 4: FIRST AID MEASURES



### Description of first aid measures

Self-protection of the first aider

Do not breathe vapour. Wear suitable protective clothing. Wear suitable respiratory protective equipment if exposure to high levels of material are likely. Avoid all contact.

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

# SAFETY DATA SHEET

Version: 4.0  
Date of Issue: 08 May 2017  
Date of First Issue: 20 March 2012

www.vishaypg.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Skin Contact	Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Apply artificial respiration if necessary. Call a POISON CENTER/doctor. IF ON SKIN (or hair): Remove contaminated clothing and wash all affected areas with plenty of water. Contaminated clothing should be thoroughly cleaned. If skin irritation occurs, get medical advice/attention. IF exposed or concerned: Get medical advice/attention.
Eye Contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	IF SWALLOWED: Rinse mouth. Do not give anything by mouth to an unconscious person. Do not induce vomiting. Call a POISON CENTER/doctor if you feel unwell. IF exposed or concerned: Get medical advice/attention.
<b>Most important symptoms and effects, both acute and delayed</b>	Harmful if inhaled. Repeated exposure may cause skin dryness or cracking. Causes serious eye irritation. May cause drowsiness or dizziness. May cause damage to organs. May cause damage to organs through prolonged or repeated exposure. May damage fertility. May damage the unborn child.
<b>Indication of any immediate medical attention and special treatment needed</b>	Treat symptomatically. Due to possible delayed effect of poisoning and for safety reasons, they should be kept under medical observation for at least 48 hours.

## SECTION 5: FIRE-FIGHTING MEASURES

<b>Extinguishing media</b> Suitable Extinguishing Media	As appropriate for surrounding fire. Extinguish preferably with foam, carbon dioxide or dry chemical.
Unsuitable extinguishing Media	Do not use water jet. Direct water jet may spread the fire.
<b>Special hazards arising from the substance or mixture</b>	May decompose in a fire giving off toxic fumes. Carbon monoxide, Carbon dioxide and Nitrogen oxides. May form explosive mixture with air particularly in enclosed spaces. Vapours are heavier than air and may travel considerable distances to a source of ignition and flashback.
<b>Special protective equipment and precautions for fire fighters</b>	Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Do not breathe fumes. Keep containers cool by spraying with water if exposed to fire. Avoid run off to waterways and sewers.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

<b>Personal precautions, protective equipment and emergency procedures</b>	Ensure adequate ventilation. Avoid all contact. Do not breathe vapour. Stop leak if safe to do so. Eliminate all ignition sources if safe to do so. Use personal protective equipment as required. See Section: 8.
<b>Environmental precautions</b>	Avoid release to the environment. Do not allow to enter drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be alerted to the Environment Agency or other appropriate regulatory body.
<b>Methods and material for containment and cleaning up</b>	Ensure full personal protection (including respiratory protection) during removal of spillages. Use non-sparking equipment when picking up flammable spill. Avoid contact with plastic. Use waterspray to 'knock down' vapour. Adsorb spillages onto sand, earth or any suitable adsorbent material. Do not absorb spillage in sawdust or other combustible material. Transfer to a container for disposal. Ventilate the area and wash spill site after material pick-up is complete. Dispose of this material and its container as hazardous waste.

## SECTION 7: HANDLING AND STORAGE

<b>Precautions for safe handling</b>	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid all contact. Do not breathe vapour. Use personal protective equipment as required. See Section: 8. Ensure adequate ventilation. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not eat, drink or smoke when using this
--------------------------------------	---

# SAFETY DATA SHEET

Version: 4.0  
 Date of Issue: 08 May 2017  
 Date of First Issue: 20 March 2012

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

### Conditions for safe storage, including any incompatibilities

Storage temperature  
 Storage life  
 Incompatible materials

product. Wash hands before breaks and after work. Take precautionary measures against static discharges.  
 Ground/bond container and receiving equipment. Keep only in original container. Store in a well-ventilated place. Keep container tightly closed. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ambient. 5 - 25°C  
 Stable under normal conditions.  
 Keep away from: Strong oxidising agents, Reducing agents, strong bases, halogenated compounds, Acids, Amines, Ammonia, Copper and Aluminium (and their alloys).  
 Can react with - Rubber and Resin. Avoid contact with plastic.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### Occupational Exposure Limits

SUBSTANCE	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m³)	STEL (ppm)	STEL (mg/m³)	Note
2-Ethoxyethanol	110-80-5	0.5	1.8	-	-	NIOSH, Sk
		200	740	-	-	OSHA, Sk
		5	-	-	-	ACGIH, Sk
Ethyl methyl ketone	78-93-3	200	590	300^	885^	NIOSH
		200	590	-	-	OSHA
		200	-	300	-	ACGIH
Xylene	1330-20-7	100	435	150^	655^	NIOSH
		100	435	-	-	OSHA
		100	-	150	-	ACGIH, A4

Note: OSHA PELs 1910.1000 TABLE Z-1/ NIOSH RELs / ACGIH TLVs

Sk - Can be absorbed through skin.

^NIOSH average value of 15 minutes.

A4: Not Classifiable as a Human Carcinogen: Agents which cause concern that they could be carcinogenic for humans but which cannot be assessed conclusively because of the lack of data. In vitro or animal studies do not provide indications of carcinogenicity which are sufficient to classify the agent into one of the other categories.

The other components listed in Section 3 do not have occupational exposure limits.

### Biological Exposure Indices

SUBSTANCE	CAS No.	Determinant	Biological Exposure Indices	Sampling Time	Note
2-Ethoxyethanol (EGGG) and 2-Ethoxyethyl acetate (EGEEA)	110-80-5 / 111-15-9	2-Ethoxyacetic acid in urine	100 mg/g creatinine	End of shift at end of workweek	-
Ethyl methyl ketone	78-93-3	Ethyl methyl ketone in urine	2 mg/L	End of shift	Ns
Xylene, o-,m-,p- or mixed isomers	1330-20-7	Methylhippuric acids in urine.	15 g/g Creatinine	End of shift	-

Source: 2015 ACGIH Biological Exposure Indices (BEIs)

Ns – Nonspecific

The other components listed in Section 3 do not have biological exposure indices.

### Appropriate engineering controls

Ensure adequate ventilation or use appropriate containment. Local exhaust

# SAFETY DATA SHEET

Version: 4.0  
Date of Issue: 08 May 2017  
Date of First Issue: 20 March 2012

www.vishaypg.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

## Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection



recommended. Atmospheric levels should be controlled in compliance with the occupational exposure limit. Use non-sparking ventilation systems, approved explosion-proof equipment, and intrinsically safe electrical systems. Guarantee that the eye flushing systems and safety showers are located close to the working place.

Keep good industrial hygiene. Avoid all contact. Do not breathe vapour. Wash hands before breaks and after work. Keep work clothes separately. Contaminated clothing should be laundered before reuse. Do not eat, drink or smoke at the work place.

Wear eye protection with side protection (EN166). Wear protective eye glasses for protection against liquid splashes. Recommended: Safety spectacles / goggles / full face shield.

Skin protection



Hand protection: Wear impervious gloves (EN374). Gloves should be changed regularly to avoid permeation problems. Breakthrough time of the glove material: refer to the information provided by the gloves' producer. Recommended: Butyl rubber.

Body protection: Wear impervious protective clothing, including boots, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Respiratory protection



In case of inadequate ventilation wear respiratory protection. Open system(s): Wear suitable respiratory protective equipment. Long Term Exposure: A self contained breathing apparatus may be appropriate.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Appearance	Amber Coloured liquid.
Odor	Sweetish ketone odor.
Odor Threshold	Not available.
pH	Not established.
Melting Point/Freezing Point	Not available.
Initial boiling point and boiling range	Not available.
Flash Point	Not available.
Evaporation rate (Butyl acetate = 1)	Not available.
Flammability (solid, gas)	Not applicable - Liquid
Upper/lower flammability or explosive limits	Not available.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	0.89 g/cm <sup>3</sup> (H <sub>2</sub> O = 1)
Solubility(ies)	Water: >10%
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature	Not available.
Decomposition Temperature	Not available.
Viscosity	Not available.

## SECTION 10: STABILITY AND REACTIVITY

<b>Reactivity</b>	Stable under normal conditions.
<b>Chemical stability</b>	Stable under normal conditions.
<b>Possibility of hazardous reactions</b>	Highly flammable liquid and vapour. The vapour may be invisible, heavier than air and spread along ground.

# SAFETY DATA SHEET

Version: 4.0  
Date of Issue: 08 May 2017  
Date of First Issue: 20 March 2012

www.vishaypg.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

<b>Conditions to avoid</b>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharges.
<b>Incompatible materials</b>	Keep away from: Strong oxidising agents, Reducing agents, strong bases, halogenated compounds, Acids, Amines, Ammonia, Copper and Aluminium (and their alloys).
<b>Hazardous decomposition product(s)</b>	Can react with - Rubber and Resin. Avoid contact with plastic. May decompose in a fire giving off toxic fumes. Carbon monoxide, Carbon dioxide and Nitrogen oxides.

## SECTION 11: TOXICOLOGICAL INFORMATION

### Information on toxicological effects (Substances in preparations / mixtures)

<b>Acute toxicity - Ingestion</b>	Based on available data, the classification criteria are not met. Acute Toxicity Estimate Mixture Calculation: Estimated LC50 >2000 mg/kg bw/day.
<b>Acute toxicity - Inhalation</b>	Acute toxicity, Category 4; Harmful if inhaled. Acute Toxicity Estimate Mixture Calculation: Estimated LC50 13.4 mg/l.
<b>Acute toxicity - Skin Contact</b>	Based on available data, the classification criteria are not met. Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 2000 mg/kg bw/day.
<b>Skin corrosion/irritation</b>	Repeated exposure may cause skin dryness or cracking.
<b>Serious eye damage/irritation</b>	Eye Irritation, Category 2; Causes serious eye irritation.
<b>Respiratory or skin sensitization</b>	Based on available data, the classification criteria are not met.
<b>Germ cell mutagenicity</b>	Based on available data, the classification criteria are not met.
<b>Carcinogenicity</b>	Based on available data, the classification criteria are not met.
<b>Reproductive toxicity</b>	Reproductive toxicity, Category 1B; May damage fertility. May damage the unborn child.
<b>STOT - single exposure</b>	Specific target organ toxicity — single exposure, Category 2; May cause damage to organs. Specific target organ toxicity — single exposure, Category 3; May cause drowsiness or dizziness.
<b>STOT - repeated exposure</b>	Specific target organ toxicity — repeated exposure, Category 2; May cause damage to organs through prolonged or repeated exposure.
<b>Aspiration hazard</b>	Aspiration hazard, Category 1; May cause allergy or asthma symptoms or breathing difficulties if inhaled.

### Information on likely routes of exposure

Inhalation	Possible – accidental exposure
Ingestion	Unlikely – accidental exposure
Skin Contact	Possible – accidental exposure
Eye Contact	Unlikely – accidental exposure

### Early onset symptoms related to exposure

Harmful if inhaled. Causes serious eye irritation. May cause drowsiness or dizziness. May cause damage to organs (Blood).

### Delayed health effects from exposure

Symptoms may be delayed for as long as 48 hours following exposure. Harmful if inhaled. Repeated exposure may cause skin dryness or cracking. May cause damage to organs (central nervous system, liver, kidney) through prolonged or repeated exposure. May damage fertility. May damage the unborn child.

### Other information

NTP Report on Carcinogens	All chemicals are not listed
IARC Monographs	4,4'-Sulfonyldianiline: Group 3 - Not classifiable as to its carcinogenicity to humans
OSHA Designated Carcinogen	Xylene: Group 3 - Not classifiable as to its carcinogenicity to humans All chemicals are not listed

# SAFETY DATA SHEET



Version: 4.0  
Date of Issue: 08 May 2017  
Date of First Issue: 20 March 2012

www.vishaypg.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

## SECTION 12: ECOLOGICAL INFORMATION

<b>Ecotoxicity</b>	Aquatic Chronic 3: Harmful to aquatic life with long lasting effects. Estimated Mixture LC50 >10 ≤ 100 mg/l (Fish)
<b>Persistence and degradability</b>	Readily biodegradable.
<b>Bioaccumulative potential</b>	The product has low potential for bioaccumulation.
<b>Mobility in soil</b>	The product is predicted to have high mobility in soil.
<b>Other adverse effects</b>	None known.

## SECTION 13: DISPOSAL CONSIDERATIONS

<b>Waste treatment methods</b>	Do not release undiluted and unneutralised to the sewer. This material and its container must be disposed of as hazardous waste. Dispose of wastes in an approved waste disposal facility. Containers of this material may be hazardous when empty since they retain product residue.
<b>Additional Information</b>	Dispose of contents in accordance with local, state or national legislation.

## SECTION 14: TRANSPORT INFORMATION

	<b>ADR/RID</b>	<b>IMDG</b>	<b>IATA</b>
<b>UN number</b>	UN 1133	UN 1133	UN 1133
<b>UN proper shipping name</b>	ADHESIVES containing flammable liquid	ADHESIVES containing flammable liquid	ADHESIVES containing flammable liquid
<b>Transport hazard class(es)</b>	3	3	3
<b>Packing group</b>	II	II	II
<b>Environmental hazards</b>	Not classified	Not classified as a Marine Pollutant.	Not classified
<b>Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code</b>	Not applicable		
<b>Special precautions for user</b>	See Section: 2		

## SECTION 15: REGULATORY INFORMATION

### Safety, health and environmental regulations/legislation specific for the substance or mixture

#### US Federal Regulations

TSCA (Toxic Substance Control Act)	2-Ethoxyethanol: Subject to 2,500 lb reporting threshold Methyl ethyl ketone: Subject to 2,500 lb reporting threshold 4,4'-Sulfonyldianiline: Subject to 2,500 lb reporting threshold Xylene: Subject to 2,500 lb reporting threshold Boron trifluoride ethylamine complex: Subject to 2,500 lb reporting threshold All chemicals are not listed
EPCRA/SARA Section 302 Extremely Hazardous Substances	
EPCRA Section 313 Toxics Release Inventory (TRI) Program	2-Ethoxyethanol: De Minimis limit: 1% Xylene: De Minimis limit: 1%
NIOSH Occupational Carcinogen List	All chemicals are not listed
OSHA List of highly hazardous chemicals, toxics and reactives	All chemicals are not listed
NTP Report on Carcinogens (RoC) List	All chemicals are not listed
Poison Prevention Packaging Act	Xylene: Substance requiring special packaging - Solvents for paint or other similar surface-coating material
<b>US State Regulations</b>	
California State, Proposition 65 List	2-Ethoxyethanol: Safe harbor level - MADL: 750 (oral) ug/day, 960 (inhalation) ug/day
California State, Safer Consumer Products Regulations	2-Ethoxyethanol: Initial Candidate Chemicals List, Group Member List: Glycol ethers Methyl ethyl ketone: Candidate Chemicals List Xylene: Initial Candidate Chemicals List
Maine State, Toxic Chemicals in Children's Products Act	2-Ethoxyethanol: COC list



# SAFETY DATA SHEET



Version: 4.0  
Date of Issue: 08 May 2017  
Date of First Issue: 20 March 2012

www.vishaypg.com

## ACCORDING TO OSHA HCS (29 CFR 1910.1200)

New Jersey State Worker and Community RTK Act	2-Ethoxyethanol: RTKHSL. SHHSL Methyl ethyl ketone: RTKHSL. SHHSL Xylene: RTKHSL. SHHSL
Pennsylvania State, Worker and Community RTK Act	2-Ethoxyethanol: Hazardous Substance List. Environmental Hazard List Methyl ethyl ketone: Hazardous Substance List. Environmental Hazard List Xylene: Hazardous Substance List. Environmental Hazard List
Rhode Island State, Hazardous Substances RTK Act	2-Ethoxyethanol: Hazardous Substance List Methyl ethyl ketone: Hazardous Substance List Xylene: Hazardous Substance List
<b>Non-Regional</b> IARC Monographs, List of Classifications	4,4'-Sulfonyldianiline: Group 3 Xylene: Group 3

## SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: Updated substance / mixture classification. New SDS Regulation compliant with HazCom 2012 format, all sections have been updated to include new information. Please review SDS with care.

Version 4.0  
Revision Date 08 May 2017  
Date of First Issue 20 March 2012

### References:

Existing Safety Data Sheet (SDS). EU Data: Harmonised Classification(s) for 2-Ethoxyethanol (CAS# 110-80-5), Methyl ethyl ketone (CAS# 78-93-3), 4,4'-Sulfonyldianiline (CAS# 80-08-0) and Xylene (CAS# 1330-20-7). Existing ECHA registration(s) for 2-Ethoxyethanol (CAS# 110-80-5), Methyl ethyl ketone (CAS# 78-93-3), 4,4'-Sulfonyldianiline (CAS# 80-08-0) and Xylene (CAS# 1330-20-7), and the Classification and Labelling Inventory for Boron trifluoride ethylamine complex (CAS# 75-23-0).

GHS Classification of the substance or mixture	Classification Procedure
Flammable Liquid, Category 2	Flash Point [Closed cup]/ Estimated Boiling Point (°C)
Acute toxicity, Category 4	Acute Toxicity Estimate (ATE) Calculation.
Eye Irritation, Category 2	Threshold Calculation
Specific target organ toxicity — single exposure, Category 3	Threshold Calculation
Specific target organ toxicity — single exposure, Category 2	Threshold Calculation
Specific target organ toxicity — repeated exposure, Category 2	Threshold Calculation
Reproductive toxicity, Category 1B	Threshold Calculation
Hazardous to the aquatic environment, Chronic, Category 3	Summation Calculation

### LEGEND

ACGIH: American Conference of Governmental Industrial Hygienists  
BEI: Biological Exposure Indices (ACGIH)  
IARC: International Agency for Research on Cancer  
Irr: Irritation  
NIOSH: National Institute of Occupational Safety and Health  
NTP: National Toxicology Program  
OSHA: The Occupational Safety & Health Administration  
PBT: Persistent, Bioaccumulative and Toxic  
PEL: Permissible exposure limit

REL: Recommended exposure limit  
SCL: Specific Concentration Limit  
Skin<sup>2</sup>: Risk of overexposure via dermal contact  
STEL: Short Term Exposure Limit  
TLV: Threshold Limit value  
TSCA: Toxic Substance Control Act  
TWA: Time Weighted Average  
URT: Upper respiratory tract  
vPvB: very Persistent and very Bioaccumulative

Training advice: Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required.

### Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Vishay Precision Group gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Vishay Precision Group accepts no liability for loss or damage (other than that arising from death or personal injury caused by



# SAFETY DATA SHEET



Version: 4.0  
Date of Issue: 08 May 2017  
Date of First Issue: 20 March 2012

[www.vishaypg.com](http://www.vishaypg.com)

**ACCORDING TO OSHA HCS (29 CFR 1910.1200)**

---

defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.



## Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "VPG"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify VPG's terms and conditions of purchase, including but not limited to, the warranty expressed therein.

VPG makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. **To the maximum extent permitted by applicable law, VPG disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.**

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on VPG's knowledge of typical requirements that are often placed on VPG products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. You should ensure you have the current version of the relevant information by contacting VPG prior to performing installation or use of the product, such as on our website at [vpgsensors.com](http://vpgsensors.com).

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of VPG.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling VPG products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify VPG for any damages arising or resulting from such use or sale. Please contact authorized VPG personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Copyright Vishay Precision Group, Inc., 2014. All rights reserved.